

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 1 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

#### Product information

Commercial Product Name : **CUROX M-202**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

### 1.3 Details of the supplier of the safety data sheet

Company : **United Initiators GmbH & Co. KG**  
Dr. Gustav-Adolph-Str. 3  
82049 Pullach  
Germany  
E-mail address : contact@united-in.com

### 1.4 Emergency telephone number

+49 / 89 / 74422 – 0

In case of an emergency in the United States, contact:

**For chemical Emergency ONLY call CHEMTREC : 1-800-424-9300**

**For ALL other inquiries about this product call :**

**United Initiators Inc.**

**555 Garden Street, Elyria Ohio 44035 at 1 (440) 323-3112**

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

#### **Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3  
Organic peroxides, Type D  
Acute toxicity, Category 4  
Skin corrosion, Category 1B

H226: Flammable liquid and vapour.  
H242: Heating may cause a fire.  
H302: Harmful if swallowed.  
H314: Causes severe skin burns and eye damage.

#### **Classification (67/548/EEC, 1999/45/EC)**

Oxidising

R 7: May cause fire.

Corrosive

R34: Causes burns.

Harmful

R22: Harmful if swallowed.

### 2.2 Label elements

#### **Labelling (REGULATION (EC) No 1272/2008)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 2 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
H242 Heating may cause a fire.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.  
P235 Keep cool.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P315 Get immediate medical advice/ attention.  
P378 Use dry sand, dry chemical or alcohol-resistant foam for extinction.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

- 1338-23-4 methylethylketoneperoxide

**Labelling according to EC Directives: 1999/45/EC**

Hazard symbols



Oxidising

Corrosive

Harmful

R-phrases(s)

: R 7 May cause fire.  
R22 Harmful if swallowed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 3 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

S-phrase(s)	<p>R34 Causes burns.</p> <p>: S 3/7 S14</p> <p>S26</p> <p>S36/37/39</p> <p>S45</p> <p>S50</p>	<p>Keep container tightly closed in a cool place. Keep away from strong acids, bases, heavy metal salts and other reducing substances. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Do not mix with activators and catalyst promoters.</p>
-------------	---	--

Hazardous components which must be listed on the label:

- 1338-23-4 methylethylketoneperoxide

## 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

## 3. Composition/information on ingredients

### 3.1 Mixtures

Chemical nature : Liquid mixture

#### Hazardous components

Chemical Name	CAS-No.	Classification (67/548/EEC)	Classification (1272/2008/EC)	Concentration [%]
	EC-No.			
	Registration number			
methylethylketoneperoxide	1338-23-4	O; R 7 Xn; R22 C; R34	Org. Perox. C; H242 Acute Tox. 4; H302 Skin Corr. 1B; H314	>= 25 - < 35
	215-661-2			
	01-2119514691-43-0000			
butanone	78-93-3	F; R11 R66 R67 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 5
	201-159-0			
hydrogen peroxide solution	7722-84-1	O; R 8 R 5 C; R35 Xn; R20/22	Ox. Liq. 1; H271 Acute Tox. 4; H332 Acute Tox. 4; H302 Skin Corr. 1A; H314	<= 2
	231-765-0			

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 4 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

## 4. First aid measures

### 4.1 Description of first aid measures

- General advice : Take off all contaminated clothing immediately. Never give anything by mouth to an unconscious person. Remove from exposure, lie down. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- If inhaled : Remove to fresh air. Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Clean mouth with water and drink afterwards plenty of water. If a person vomits when lying on his back, place him in the recovery position. Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label.

### 4.2 Most important symptoms and effects, both acute and delayed

no data available

### 4.3 Indication of any immediate medical attention and special treatment needed

no data available

## 5. Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 5 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Wear personal protective equipment.

### 6.2 Environmental precautions

Avoid subsoil penetration. Do not allow material to contaminate ground water system. Do not contaminate water. If the product contaminates rivers and lakes or drains inform respective authorities. Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Remove mechanically and with care (e.g. with clean polyethylene plastic shovel). Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

### 6.4 Reference to other sections

see chapter: 7, 8, 11, 12 and 13

### 6.5 Other information

Never add other substances or waste material to product residue. Move product residue to a safe place and dispose of properly.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Dust explosion class : no data available

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. No smoking.

Further information on storage conditions : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Advice on common storage : Store apart from other dangerous and incompatible substances.

Storage temperature : < 30 °C

Other data : Storing temperature for reasons of quality

liquid up to -25 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 6 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

## 7.3 Specific end uses

no data available

## 8. Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Control parameters	Basis	Update
butanone	78-93-3	AGW: 600 mg/m <sup>3</sup> , 200 ppm DFG, EU, H, Y,	DE TRGS 900	2010-08-04
Components	CAS-No.	Control parameters	Basis	Update
butanone	78-93-3	TWA: 600 mg/m <sup>3</sup> , 200 ppm STEL: 900 mg/m <sup>3</sup> , 300 ppm	2000/39/EC	2000-06-16

Other information on limit values: see chapter 16

### Biological occupational exposure limits - TRGS903

Substance name	CAS-No.	Control parameters	Sampling time	Update
butanone	78-93-3	2-butanon: 5 mg/l (U)	a	2004-08-01

#### Remarks:

- a No time limit
- b Immediately after exposition or after working hours
- c In case of long-term exposition: after more than one shift
- d Before the next shift

### 8.2 Exposure controls

#### Engineering measures

Provide adequate ventilation.

#### Personal protective equipment

Respiratory protection : Short duration filter unit: Filter A

#### Hand protection

Material : butyl-rubber  
 Glove thickness : 0,5 mm  
 Break through time : >= 8 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 7 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

- Remarks** : Skin should be washed after contact.
- Eye protection** : Tightly fitting safety goggles  
Face protection
- Skin and body protection** : Protective suit  
Remove and wash contaminated clothing before re-use.
- Hygiene measures** : Wash hands before breaks and immediately after handling the product.  
Keep away from food, drink and animal feedingstuffs.
- Environmental exposure controls**
- General advice** : Avoid subsoil penetration.  
Do not allow material to contaminate ground water system.  
Do not contaminate water.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not let product enter drains.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid  
 Colour : colourless  
 Odour : characteristic  
 Odour Threshold : Not relevant  
 pH : not applicable  
 Melting point/freezing point : < -25 °C
- Initial boiling point and boiling range : not applicable, Decomposition  
 Flash point : 56 °C  
 Method: ISO 3679, Seta-Flash
- Evaporation rate : Not relevant  
 Flammability (solid, gas) : not applicable
- Lower explosion limit : not applicable  
 Upper explosion limit : not applicable  
 Vapour pressure : no data available  
 Relative vapour density : no data available  
 Density : 1,01 g/cm<sup>3</sup> at 20 °C
- Water solubility : no data available  
 Partition coefficient: n- : no data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page **8** of **13**

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

octanol/water

Solubility in other solvents : Mixable  
Medium: Phthalates

Autoignition temperature : not applicable, Decomposes on heating.

Decomposition temperature : ca. 60 °C, SADT (UN test H.4), SADT possible at temperatures above approximately 60 °C.

Viscosity, dynamic : 16 mPa.s at 20 °C

Viscosity, kinematic : no data available

Explosive properties : no data available

Oxidizing properties : Organic peroxide

## 9.2 Other information

Ignition temperature : not applicable

Refraction index : 1,437  
at 20 °C

Miscibility in water : immiscible

## 10. Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.

### 10.2 Chemical stability

Contact with incompatible substances can cause disintegration at or below SADT.

### 10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Stability: Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Keep away from heat and sources of ignition.

### 10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents, Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

Thermal decomposition : ca. 60 °C  
Method: SADT (UN test H.4)  
Note: SADT possible at temperatures above approximately 60 °C.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 9 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

## 11. Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Acute oral toxicity : LD50 rat: 1.017 mg/kg  
Test substance: methylethylketoneperoxide (40% in dimethylphthalate)

Acute inhalation toxicity : Acute toxicity estimate : 550 mg/l  
Method: Calculation method

Acute dermal toxicity : LD50 rat: 4.000 mg/kg  
Test substance: methylethylketoneperoxide (40% in dimethylphthalate)

#### Skin corrosion/irritation

Skin irritation : Causes burns.

#### Serious eye damage/eye irritation

Eye irritation : Causes burns.

#### Respiratory or skin sensitization

Sensitisation : Result: Product is not sensitizing.  
Method: Maximisation Test  
Test substance: methylethylketoneperoxide (60% in dimethylphthalate/diacetone alcohol)

#### Germ cell mutagenicity

Genotoxicity in vitro : Result: Not mutagenic in Ames Test.

#### Carcinogenicity

no data available

#### Reproductive toxicity

no data available

#### Teratogenicity

no data available

#### STOT - single exposure

no data available

#### STOT - repeated exposure

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page **10** of **13**

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

no data available

## Aspiration hazard

Aspiration toxicity

no data available

## Further information

butanone

: Inhalation of high vapour concentrations can cause CNS-depression and narcosis.

Inhalation of vapours in high concentration may cause shortness of breath (lung oedema).

## 12. Ecological information

### 12.1 Toxicity

Toxicity to fish

: LC50 (Poecilia reticulata (guppy)): 44,2 mg/l

Exposure time: 96 h

Test substance: methylethylketoneperoxide (33% in dimethylphthalate)

Toxicity to daphnia and other aquatic invertebrates.

: EC50 (Daphnia): 39 mg/l

Exposure time: 48 h

Test substance: methylethylketoneperoxide (40% in dimethylphthalate)

Toxicity to algae

: EC50 (Pseudokirchneriella subcapitata): 5,6 mg/l

Exposure time: 72 h

Test substance: methylethylketoneperoxide (40% in dimethylphthalate)

Toxicity to bacteria

: EC50 (Bacteria): 48 mg/l

Exposure time: 30 min

Test substance: methylethylketoneperoxide (33% in dimethylphthalate)

### 12.2 Persistence and degradability

Biodegradability

: Result: Readily biodegradable.

Method: Closed Bottle Test

Test substance: methylethylketoneperoxide (MEKP)

### 12.3 Bioaccumulative potential

no data available

### 12.4 Mobility in soil

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 11 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

no data available

## 12.5 Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

## 12.6 Other adverse effects

no data available

## 13. Disposal considerations

### 13.1 Waste treatment methods

Advice on disposal and packaging : Disposal:  
Dispose of in conjunction with appropriate waste disposal authorities and in accordance with disposal regulations.  
Waste codes should be assigned by the user based on the application for which the product was used.

## 14. Transport information

### ADR

UN number : 3105  
Description of the goods : ORGANIC PEROXIDE TYPE D, LIQUID  
(methylethylketoneperoxide)  
Class : 5.2  
Packing group : --  
Classification Code : P1  
Labels : 5.2  
Limited quantity : LQ16  
Tunnel restriction code : (D)  
Environmentally hazardous : no

### RID

UN number : 3105  
Description of the goods : ORGANIC PEROXIDE TYPE D, LIQUID  
(methylethylketoneperoxide)  
Class : 5.2  
Packing group : --  
Classification Code : P1  
Hazard identification No : 539  
Labels : 5.2  
Limited quantity : LQ16  
Environmentally hazardous : no

### IATA

UN number : 3105  
Description of the goods : Organic peroxide type D, liquid  
(methylethylketoneperoxide)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 12 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

Class : 5.2  
 Packing group : --  
 Labels : 5.2 (HEAT)  
 Packing instruction (cargo aircraft) : 570  
 Environmentally hazardous : no  
 Packing instruction (passenger aircraft) : 570

## IMDG

UN number : 3105  
 Description of the goods : ORGANIC PEROXIDE TYPE D, LIQUID  
 (methylethylketoneperoxide)

Class : 5.2  
 Packing group : --  
 Labels : 5.2  
 EmS Number 1 : F-J  
 EmS Number 2 : S-R

Marine pollutant : no

**Special precautions for user**  
 see chapter: 6, 7 and 8

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National legislation

Water contaminating class : WGK 1 (slightly water endangering)  
 (Germany) VwVwS (German water pollution authority), appendix 4

Other regulations : BGV B4 organische Peroxide. (German regulatory requirements)  
 BG-Merkblatt M001 beachten (German regulatory requirements)  
 Produkt unterliegt nicht dem Sprengstoffgesetz (SprengG). (German regulatory requirements)  
 Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.  
 Take note of Dir 94/33/EC on the protection of young people at work.  
 Störfallverordnung Anhang I (German regulatory requirements)

Gefahrengruppe nach § 3 BGV B4: (German regulatory requirements) Ib (German regulatory requirements)

### 15.2 Chemical Safety Assessment

no data available

## 16. Other information

Full text of R-phrases referred to under sections 2 and 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Print Date: 23.09.2011

Revision Date : 23.09.2011

Page 13 of 13

Commercial Product Name: CUROX M-202

DE / EN

Version: 1.4

R 5	Heating may cause an explosion.
R 7	May cause fire.
R 8	Contact with combustible material may cause fire.
R11	Highly flammable.
R20/22	Harmful by inhalation and if swallowed.
R22	Harmful if swallowed.
R34	Causes burns.
R35	Causes severe burns.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

#### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

#### Other information

DFG	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).
EU	European Union (The EU has established a limit value: deviations in value and peak limit are possible)
H	Skin absorption
Y	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.