

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

SECTION 1. IDENTIFICATION

Trade name : APS-5F

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street
Elyria OH 44035 USA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300
CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person responsible for the SDS : cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Oxidizing agents
polymerization initiators

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Oxidizing solids : Category 3

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6 Revision Date: 04/24/2024 SDS Number: 600000000016 Date of last issue: 06/24/2020
Date of first issue: 02/14/2017

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H272 May intensify fire; oxidizer.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.

Precautionary Statements :

Prevention:

P210 Keep away from heat.
P220 Keep/Store away from clothing/ combustible materials.
P221 Take any precaution to avoid mixing with combustibles.
P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use water spray to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6 Revision Date: 04/24/2024 SDS Number: 600000000016 Date of last issue: 06/24/2020
Date of first issue: 02/14/2017

tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

May cause fire or explosion; strong oxidizer.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Persulphate
Solid

Components

Chemical name	CAS-No.	Concentration (% w/w)
Ammonium persulphate	7727-54-0	$\geq 95 - \leq 100$
Silicon dioxide	7631-86-9	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Take off contaminated clothing and shoes immediately.
Call a physician immediately.
Never give anything by mouth to an unconscious person.
If unconscious, place in recovery position and seek medical advice.
Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.

If inhaled : Administer oxygen if breathing is difficult or cyanosis is observed.
If breathed in, move person into fresh air.
If not breathing, give artificial respiration.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

- Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
- In case of skin contact : If symptoms persist, call a physician.
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.
Rinse mouth thoroughly with water.
Keep respiratory tract clear.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
sensitizing effects
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

Do not allow run-off from fire fighting to enter drains or water courses.

Cool closed containers exposed to fire with water spray.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.
Suppress (knock down) gases/vapors/mists with a water spray jet.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.
Remove all sources of ignition.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

Clear spills immediately.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

Suppress (knock down) gases/vapors/mists with a water spray jet.

To clean the floor and all objects contaminated by this material, use plenty of water.

Soak up with inert absorbent material.

Isolate waste and do not reuse.

Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

- | | | |
|---|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Advice on protection against fire and explosion | : | Keep away from combustible material.
Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed. |
| Advice on safe handling | : | Avoid formation of respirable particles.
Protect from contamination.
Protect from moisture.
Do not swallow.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. |
| Conditions for safe storage | : | Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep in a dry place.
Observe label precautions.
Store in accordance with the particular national regulations. |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6 Revision Date: 04/24/2024 SDS Number: 600000000016 Date of last issue: 06/24/2020
Date of first issue: 02/14/2017

Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Electrical installations / working materials must comply with the technological safety standards.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Materials to avoid : Never allow product to get in contact with water during storage.
Keep away from combustible materials.
Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 30 °C

< 86 °F

Further information on storage stability : Stable under recommended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ammonium persulphate	7727-54-0	TWA	0.1 mg/m ³ (Persulphate)	ACGIH
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Engineering measures : Minimize workplace exposure concentrations.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : Filter type P

Use NIOSH approved respiratory protection.

Hand protection

Material : butyl-rubber

Break through time : 480 min

Glove thickness : 0.47 mm

Material : Nitrile rubber

Break through time : 480 min

Glove thickness : 0.40 mm

Remarks : The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

Hygiene measures : Avoid contact with skin, eyes and clothing.
Keep away from food and drink.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: crystalline
Color	: white
Odor	: not significant
Odor Threshold	: not determined
pH	: 4 Concentration: 10 g/l
Melting point/freezing point	: Decomposition: Decomposes below the melting point.
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not expected to form explosive dust-air mixtures.
Self-ignition	: The substance or mixture is not classified as pyrophoric.
Upper explosion limit / Upper flammability limit	: Upper explosion limit No data available
Lower explosion limit / Lower flammability limit	: Lower explosion limit No data available
Vapor pressure	: < 0.001 hPa (25 °C)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Relative vapor density	:	not determined
Relative density	:	not determined
Density	:	not determined
Bulk density	:	ca. 1,100 kg/m ³ (20 °C)
Solubility(ies)	:	
Water solubility	:	850 g/l soluble (25 °C)
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	not determined
Self-Accelerating decomposition temperature (SADT)	:	130 °C Method: UN-Test H.4 SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
Viscosity	:	
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is classified as oxidizing with the category 3.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Particle size	:	not determined
Particle Size Distribution	:	D10 = 9 µm Type of distribution: volume distribution Measurement technique: laser diffraction

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions. May intensify fire; oxidizer.
------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

- | | | |
|------------------------------------|---|---|
| Chemical stability | : | Stable under recommended storage conditions.
No decomposition if stored normally. |
| Possibility of hazardous reactions | : | Avoid moisture.
Even small amounts of moisture or impurities can noticeably reduce the self-accelerating decomposition temperature (SADT). |
| Conditions to avoid | : | Protect from contamination.
Protect from moisture.
Contact with incompatible substances can cause decomposition at or below SADT.
Even small amounts of moisture or impurities can noticeably reduce the self-accelerating decomposition temperature (SADT). |
| Incompatible materials | : | Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents |
| Hazardous decomposition products | : | Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition |
-

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Components:

Ammonium persulphate:

- | | | |
|---------------------------|---|--|
| Acute oral toxicity | : | LD50 (Rat, male): 742 mg/kg
Method: OECD Test Guideline 401
Assessment: The component/mixture is moderately toxic after single ingestion.
Remarks: Based on test data |
| Acute inhalation toxicity | : | LC50 (Rat): > 5.1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Expert judgment |
| Acute dermal toxicity | : | LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Expert judgment |

Silicon dioxide:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC0 (Rat): > 0.139 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Remarks : May cause skin irritation in susceptible persons.

Components:

Ammonium persulphate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Silicon dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Remarks : May cause irreversible eye damage.

Components:

Ammonium persulphate:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405

Silicon dioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitization by skin contact.

Routes of exposure : inhalation (dust/mist/fume)
Result : May cause sensitization by inhalation.

Remarks : Causes sensitization.

Components:

Ammonium persulphate:

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitization by skin contact.

Routes of exposure : inhalation (dust/mist/fume)
Result : May cause sensitization by inhalation.

Silicon dioxide:

Remarks : This information is not available.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Ammonium persulphate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative

Silicon dioxide:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Species: Rat
Application Route: Inhalation
Exposure time: 90 d
Method: No information available.
Result: negative

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Not classified due to lack of data.

Components:

Ammonium persulphate:

Species : Mouse
Application Route : Skin contact
Exposure time : 52 weeks
Method : OECD Test Guideline 451
Result : negative

Silicon dioxide:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA OSHA specifically regulated carcinogen
Silicon dioxide 7631-86-9
(crystalline silica)
(crystalline silica)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

Components:

Ammonium persulphate:

Effects on fertility : Species: Rat
Application Route: Ingestion
General Toxicity Parent: NOAEL: \geq 250 mg/kg body weight
General Toxicity F1: NOAEL: \geq 250 mg/kg body weight
Method: OECD Test Guideline 421

Silicon dioxide:

Reproductive toxicity - Assessment : No toxicity to reproduction

STOT-single exposure

May cause respiratory irritation.

Product:

Assessment : May cause respiratory irritation.

Components:

Ammonium persulphate:

Assessment : May cause respiratory irritation.

Silicon dioxide:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.
Remarks : Not classified due to data which are conclusive although insufficient for classification.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Components:

Ammonium persulphate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Silicon dioxide:

Assessment : The substance or mixture is not classified as specific target

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Remarks : organ toxicant, repeated exposure.
: Not classified due to data which are conclusive although insufficient for classification.

Repeated dose toxicity

Components:

Ammonium persulphate:

Species : Rat
NOAEL : 1,000 mg/kg
LOAEL : 3,000 mg/kg
Application Route : Ingestion
Exposure time : 90 d
Method : OECD Test Guideline 408

Species : Rat
NOAEL : 41.1 mg/kg
Application Route : oral (feed)
Exposure time : 28 d
Method : OECD Test Guideline 407

Species : Rat
NOAEL : 0.0103 mg/l
Application Route : inhalation (dust/mist/fume)
Method : OECD Test Guideline 413

Species : Rat
NOAEL : 0.005 mg/l
Application Route : inhalation (dust/mist/fume)
Method : OECD Test Guideline 413

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ammonium persulphate:

Toxicity to fish : LC50 (Scophthalmus maximus (turbot)): 107.6 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

- Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 120 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Phaeodactylum): 320 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Phaeodactylum): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC10 (Pseudomonas putida): 36 mg/l
Exposure time: 18 h
- Silicon dioxide:**
- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Ammonium persulphate:

- Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Bioaccumulative potential

Components:

Ammonium persulphate:

- Partition coefficient: n-octanol/water : Remarks: Not applicable

Mobility in soil

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility. The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.
Clean container with water.
Dispose of contents/ container to an approved waste disposal plant.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1444
Proper shipping name : AMMONIUM PERSULPHATE
Class : 5.1
Packing group : III
Labels : 5.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1444
Proper shipping name : Ammonium persulphate
Class : 5.1
Packing group : III
Labels : Oxidizer

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

Packing instruction (cargo aircraft) : 563

Packing instruction (passenger aircraft) : 559

IMDG-Code

UN number : UN 1444

Proper shipping name : AMMONIUM PERSULPHATE

Class : 5.1

Packing group : III

Labels : 5.1

EmS Code : F-A, S-Q

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1444

Proper shipping name : Ammonium persulfate

Class : 5.1

Packing group : III

Labels : OXIDIZER

ERG Code : 140

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Oxidizer (liquid, solid or gas)
Acute toxicity (any route of exposure)
Respiratory or skin sensitization

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version 1.6	Revision Date: 04/24/2024	SDS Number: 600000000016	Date of last issue: 06/24/2020 Date of first issue: 02/14/2017
----------------	------------------------------	-----------------------------	---

Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

Maine Chemicals of High Concern

This product does not contain any chemicals that are listed as Maine Chemicals of High Concern.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

International Regulations

The ingredients of this product are reported in the following inventories:

TCSI (TW)	: On the inventory, or in compliance with the inventory
TSCA (US)	: All substances listed as active on the TSCA inventory
AiIC (AU)	: All components are listed on the inventory, regulatory obligations/restrictions apply
DSL (CA)	: All components of this product are on the Canadian DSL
ENCS (JP)	: On the inventory, or in compliance with the inventory
ISHL (JP)	: On the inventory, or in compliance with the inventory
KECI (KR)	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TECI (TH) : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification. These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/24/2024

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Haz-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



APS-5F

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2020
1.6	04/24/2024	600000000016	Date of first issue: 02/14/2017

ardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8