BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

SECTION 1. IDENTIFICATION

Product name : BENOX[®]A-75

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street

Elyria OH 44035 USA

Unit 3 – 363 Broadway, Suite 324 Winnipeg, MB R3C 3N9 CANADA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300

CHEMTREC WORLD (24h): +1-703-527-3887 CANUTEC (24h): 1-613-966-6666

E-mail address of person

responsible for the SDS

cs-initiators.nafta@united-in.com

For Transportation Incidents : TERRAPURE EMERGENCY RESPONSE SERVICES (24h):

1-800-567-7455

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

polymerization initiators

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Organic peroxides : Type C

Combustible dust : Category 1

Eye irritation : Category 2A

Skin sensitization : Category 1

Short-term (acute) aquatic

hazard

: Category 1

Long-term (chronic) aquatic

hazard

Category 1

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

GHS label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H242 Heating may cause a fire.

May form combustible dust concentrations in air. H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234 Keep only in original packaging.

P240 Ground and bond container and receiving equipment.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage:

P403 Store in a well-ventilated place.

P410 Protect from sunlight.

P411 Store at temperatures not exceeding 30 °C/86 °F.

P420 Store separately.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

BENOX®A-75



Version **Revision Date:** SDS Number: Date of last issue: 02/16/2018 11/28/2019 600000000135 Date of first issue: 10/27/2016 2.1

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Organic Peroxide Chemical nature

Solid mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Dibenzoyl peroxide 94-36-0		>= 70 - < 75	

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended. Call a physician immediately.

If inhaled If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician. If breathed in, move person into fresh air.

In case of skin contact In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

If symptoms persist, call a physician.

In the case of contact with eyes, rinse immediately with plenty In case of eye contact

of water and seek medical advice.

Remove contact lenses. Protect unharmed eve.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Call a physician immediately.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

Protection of first-aiders First Aid responders should pay attention to self-protection

and use the recommended protective clothing

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

tire

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

Follow safe handling advice and personal protective

equipment recommendations.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Keep away from heat and sources of ignition.

Use only explosion-proof equipment. Keep away from combustible material.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem-

perature

5 - 30 °C

Further information on stor-

age stability

No decomposition if stored normally.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	CA AB OEL
		TWA	5 mg/m3	CA BC OEL
		TWAEV	5 mg/m3	CA QC OEL
		TWA	5 mg/m3	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : Filter type P

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous

substance and specific to place of work.

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove Wash hands before breaks and at the

end of workday.

Eye protection : Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

protection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Hygiene measures : Keep away from food and drink.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : aromatic

Odor Threshold : No data available

pH : No data available

Melting point/range : Decomposition: Decomposes below the melting point.

Boiling point/boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Bulk density : 590 kg/m3 (20 °C)

Solubility(ies)

Water solubility : 0.0004 g/l insoluble

Solubility in other solvents : soluble

Solvent: Phthalates

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Partition coefficient: n-

octanol/water

: log Pow: 3.2 (20 °C)

Self-Accelerating decomposi-

tion temperature (SADT)

70 °C SADT-Self Accelerating Decomposition Temperature. Lowest

temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reac-

tions

Dust may form explosive mixture in air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 24.3 mg/l

BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 2.1
 11/28/2019
 600000000135
 Date of first issue: 10/27/2016

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

Dibenzoyl peroxide:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit Result : Eye irritation

Method : OECD Test Guideline 405

Remarks : May cause irreversible eye damage.

Components:

Dibenzoyl peroxide:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Species : Mouse

Method : OECD Test Guideline 429
Result : Causes sensitization.

Remarks : Causes sensitization.

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Components:

Dibenzoyl peroxide:

Routes of exposure : Skin contact Species : Mouse

Method : Local lymph node assay (LLNA)

Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Genotoxicity in vitro : Result: negative

Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: negative

Remarks: In vivo tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

Product:

Remarks : negative

Components:

Dibenzoyl peroxide:

Remarks : Not classified due to data which are conclusive although insuf-

ficient for classification.

Reproductive toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Effects on fertility : Species: Rat, male

Application Route: Oral

General Toxicity Parent: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, female Application Route: Oral

General Toxicity Parent: NOAEL: 500 mg/kg body weight

Method: OECD Test Guideline 422

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 2.1
 11/28/2019
 600000000135
 Date of first issue: 10/27/2016

Components:

Dibenzoyl peroxide:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT-repeated exposure

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Species : Rat

NOAEL : 1,000 mg/kg

Application Route : Oral Exposure time : 28 d

Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dibenzoyl peroxide:

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.06

mg/l

10

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.001 mg/l

Exposure time: 21 d

Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

Dibenzoyl peroxide:

Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential

Components:

Dibenzoyl peroxide:

Partition coefficient: n-

octanol/water

: log Pow: 3.2 (20 °C)

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3104

Proper shipping name : ORGANIC PEROXIDE TYPE C, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

IATA-DGR

UN/ID No. : UN 3104

Proper shipping name : Organic peroxide type C, solid

(Dibenzoyl peroxide)

Class : 5,2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen-

570

ger aircraft)

IMDG-Code

UN number : UN 3104

Proper shipping name : ORGANIC PEROXIDE TYPE C, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 2.1 11/28/2019 600000000135 Date of first issue: 10/27/2016

UN number : UN 3104

Proper shipping name : ORGANIC PEROXIDE TYPE C, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2
Packing group : II
Labels : 5.2
ERG Code : 146
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : Dibenzoyl peroxide

The ingredients of this product are reported in the following inventories:

DSL (CA) : All components of this product are on the Canadian DSL

AICS (AU) : On the inventory, or in compliance with the inventory

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 2.1
 11/28/2019
 600000000135
 Date of first issue: 10/27/2016

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average CA AB OEL / TWA : 8-hour Occupational exposure limit CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 11/28/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only

BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 2.1
 11/28/2019
 600000000135
 Date of first issue: 10/27/2016

to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / Z8