

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX®A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	BENOX®A-75
Substance name	:	Dibenzoyl peroxide
Index-No.	:	617-008-00-0
EC-No.	:	202-327-6

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Hardener, polymerisation initiators
------------------------------	---	-------------------------------------

#### 1.3 Details of the supplier of the safety data sheet

Company	:	United Initiators GmbH Dr.-Gustav-Adolph-Str. 3 82049 Pullach
Telephone	:	+49 / 89 / 74422 – 0
E-mail address of person responsible for the SDS	:	contact@united-in.com

#### 1.4 Emergency telephone number

0800 0 621 2139 (toll-free, access from Turkey only)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification T.R. SEA No 28848 and subsequent amendments

Organic peroxides, Type C	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105




## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

### 2.2 Label elements

#### Labelling T.R. SEA No 28848 and subsequent amendments

- Hazard pictograms : 
- Signal word : Danger
- Hazard statements : H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H410 Very toxic to aquatic life with long lasting effects.
- Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P234 Keep only in original packaging.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
P391 Collect spillage.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

- Substance name : Dibenzoyl peroxide
- Index-No. : 617-008-00-0
- EC-No. : 202-327-6
- Chemical nature : Organic Peroxide

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

	EC-No.	
dibenzoyl peroxide	94-36-0 202-327-6	>= 70 - <= 77

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Take off contaminated clothing and shoes immediately.  
Call a physician immediately.  
Never give anything by mouth to an unconscious person.  
If unconscious, place in recovery position and seek medical advice.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Administer oxygen if breathing is difficult or cyanosis is observed.  
If breathed in, move person into fresh air.  
If not breathing, give artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If symptoms persist, call a physician.  
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.  
Keep respiratory tract clear.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms :

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

sensitising effects

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation. May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Risk of explosion if heated under confinement.  
Possible emission of gaseous decomposition products may lead to a dangerous pressure build-up.  
Avoid confinement.  
Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.  
The product burns violently.  
Flash back possible over considerable distance.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Vapours may form explosive mixtures with air.  
The product will float on water and can be reignited on surface water.  
Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Remove undamaged containers from fire area if it is safe to do so.  
Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use a water spray to cool fully closed containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.  
Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Remove all sources of ignition.  
Never return spills in original containers for re-use.  
Treat recovered material as described in the section "Disposal considerations".

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.  
Clear spills immediately.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
To clean the floor and all objects contaminated by this material, use plenty of water.  
Soak up with inert absorbent material.  
Isolate waste and do not reuse.  
Non-sparking tools should be used.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |   |   |  |
|---|---|--|
| Technical measures                              | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  |
| Advice on safe handling                         | : | Open drum carefully as content may be under pressure.<br>Avoid formation of respirable particles.<br>Protect from contamination.<br>Do not breathe vapours/dust.<br>Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>Take precautionary measures against static discharges.<br>Never return any product to the container from which it was originally removed.<br>Provide sufficient air exchange and/or exhaust in work rooms.<br>Avoid confinement.<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Wash thoroughly after handling.<br>For personal protection see section 8.<br>Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. |
| Advice on protection against fire and explosion | : | Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.   |
| Hygiene measures                                | : | Avoid contact with skin, eyes and clothing. Keep away from food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.   |

### 7.2 Conditions for safe storage, including any incompatibilities

- |   |   |   |
|---|---|---|
| Requirements for storage areas and containers | : | Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in cool place. Keep in a well-ventilated place. Contamination may result in dangerous pressure increases - closed containers may rupture. Observe label |
|---|---|---|

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

precautions. Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from combustible materials.  
Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : 5 - 30 °C

Further information on storage stability : Stable under recommended storage conditions.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Dust 15 mg/m<sup>3</sup>  
Value type (Form of exposure): ZOAD/TWA (Total dust)  
Basis: TR OEL DU  
Further information: Allowable occupational exposure limit values of mineral dusts

İnert veya İstenmeyen Toz 5 mg/m<sup>3</sup>  
Value type (Form of exposure): ZOAD/TWA (Respirable part)  
Basis: TR OEL DU  
Further information: Allowable occupational exposure limit values of mineral dusts

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dibenzoyl peroxide	94-36-0	TWA (8 Hour)	5 mg/m <sup>3</sup>	TR OEL

#### Derived No Effect Level (DNEL) :

Substance name	End Use	Exposure routes	Potential health effects	Value
dibenzoyl peroxide	Workers	Inhalation	Long-term systemic	39 mg/m <sup>3</sup>

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

			effects	
	Workers	Skin contact	Long-term systemic effects	34,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,5 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	17 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) :

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0,02 µg/l
	Marine water	0,002 µg/l
	Sewage treatment plant	0,35 mg/l
	Fresh water sediment	0,013 mg/kg dry weight (d.w.)
	Marine sediment	0,001 mg/kg dry weight (d.w.)
	Soil	0,003 mg/kg dry weight (d.w.)

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.

### Personal protective equipment

Eye/face protection : Ensure that eyewash stations and safety showers are close to the workstation location.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Tightly fitting safety goggles  
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.

### Hand protection

Material : butyl-rubber  
Break through time : 480 min  
Glove thickness : 0,47 mm

Material : Nitrile rubber  
Break through time : 480 min  
Glove thickness : 0,40 mm

Remarks : The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protec-



# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

tive glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Wear as appropriate: Flame retardant antistatic protective clothing.
- Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
- Filter type : Filter type P
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : powder
- Colour : white
- Odour : aromatic
- Odour Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/ range : Decomposition: Decomposes below the melting point.
- Boiling point/boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : No data available

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Flammability (solid, gas)	:	Organic peroxide
Upper explosion limit / Upper flammability limit	:	Upper explosion limit No data available
Lower explosion limit / Lower flammability limit	:	Lower explosion limit No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	not determined
Density	:	not determined
Bulk density	:	590 kg/m <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	0,0004 g/l insoluble
Solubility in other solvents	:	soluble Solvent: Phthalates
Partition coefficient: n-octanol/water	:	log Pow: 3,2 (20 °C)
Auto-ignition temperature	:	not determined
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	No data available
Explosive properties	:	Risk of explosion by shock, friction, fire or other sources of ignition. Avoid dust formation.
Oxidizing properties	:	The substance or mixture is not classified as oxidizing. Organic peroxide

### 9.2 Other information

Self-Accelerating decomposition temperature (SADT)	:	70 °C Method: UN-Test H.4 SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
Self-heating substances	:	The substance or mixture is not classified as self heating.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Impact sensitivity : Sensitive to impact and/ or friction.

Particle size : not determined

Particle Size Distribution : No data available

Self-ignition : The substance or mixture is not classified as pyrophoric.

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Stable under recommended storage conditions.  
Heating may cause a fire or explosion.

#### 10.2 Chemical stability

Stable under recommended storage conditions.  
No decomposition if stored normally.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Dust may form explosive mixture in air.

#### 10.4 Conditions to avoid

Conditions to avoid : Protect from contamination.  
Contact with incompatible substances can cause decomposition at or below SADT.  
Heat, flames and sparks.  
Avoid confinement.

#### 10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

#### 10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.  
Not classified due to lack of data.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

---

### **Product:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): 24,3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : Remarks: No data available

### **Components:**

#### **dibenzoyl peroxide:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 24,3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Remarks: No data available

### **Skin corrosion/irritation**

Not classified based on available information.  
Based on available data, the classification criteria are not met.

### **Product:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

Remarks : May cause skin irritation in susceptible persons.

### **Components:**

#### **dibenzoyl peroxide:**

Species : Rabbit  
Exposure time : 4 h  
Method : OECD Test Guideline 404

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.  
Causes serious eye irritation.

#### Product:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 7 days

Remarks : Product dust may be irritating to eyes, skin and respiratory system.

#### Components:

##### **dibenzoyl peroxide:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 7 days

### Respiratory or skin sensitisation

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### Product:

Exposure routes : Skin contact  
Species : Mouse  
Method : Local lymph node assay (LLNA)  
Result : Causes sensitisation.

Remarks : Causes sensitisation.

Remarks : Causes sensitisation.

#### Components:

##### **dibenzoyl peroxide:**

Exposure routes : Skin contact  
Species : Mouse

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Method : Local lymph node assay (LLNA)  
Result : May cause sensitisation by skin contact.

### **Germ cell mutagenicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **Product:**

Genotoxicity in vitro : Method: OECD Test Guideline 471  
Result: negative  
  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test  
Species: Mouse  
Result: negative

#### **Components:**

##### **dibenzoyl peroxide:**

Genotoxicity in vitro : Method: OECD Test Guideline 471  
Result: negative  
  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test  
Species: Mouse  
Result: negative

### **Carcinogenicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **Product:**

Remarks : This information is not available.

#### **Components:**

##### **dibenzoyl peroxide:**

Remarks : This information is not available.

### **Reproductive toxicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **Product:**

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

### Components:

#### **dibenzoyl peroxide:**

Effects on fertility : Species: Rat, male  
Application Route: Oral  
General Toxicity - Parent: NOAEL: 1.000 mg/kg body weight  
Method: OECD Test Guideline 422

Species: Rat, female  
Application Route: Oral  
General Toxicity - Parent: NOAEL: 500 mg/kg body weight  
Method: OECD Test Guideline 422

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

#### **STOT - single exposure**

Not classified based on available information.  
Based on available data, the classification criteria are not met.

### Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### Components:

#### **dibenzoyl peroxide:**

Exposure routes : Ingestion  
Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

#### **STOT - repeated exposure**

Not classified based on available information.  
Based on available data, the classification criteria are not met.

### Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Components:

#### **dibenzoyl peroxide:**

Exposure routes : Ingestion  
Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

### Repeated dose toxicity

#### Product:

Species	: Rat
NOAEL	: 1.000 mg/kg
Application Route	: Oral
Exposure time	: 28 d
Method	: OECD Test Guideline 422

#### Components:

##### **dibenzoyl peroxide:**

Species	: Rat
NOAEL	: 1.000 mg/kg
Application Route	: Oral
Exposure time	: 28 d
Method	: OECD Test Guideline 422

### Aspiration toxicity

Not classified based on available information.  
Based on available data, the classification criteria are not met.

#### Product:

No aspiration toxicity classification

#### Components:

##### **dibenzoyl peroxide:**

No aspiration toxicity classification

### Further information

#### Product:

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish	: EC50 (Oncorhynchus mykiss (rainbow trout)): 0,06 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0,11 mg/l Exposure time: 48 h
---	---



# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version 3.0      Revision Date: 02.10.2024      SDS Number: 600000000135      Date of last issue: 09.03.2023  
Date of first issue: 09.03.2017

---

- Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0,071 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 0,02 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 0,001 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l  
Exposure time: 30 min  
Method: OECD Test Guideline 209

### Ecotoxicology Assessment

- Acute aquatic toxicity : Very toxic to aquatic life.
- Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### Components:

#### **dibenzoyl peroxide:**

- Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0,06 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,11 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0,071 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 0,02 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 10

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l  
Exposure time: 30 min  
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 0,001 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 10

### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### **dibenzoyl peroxide:**

Biodegradability : Result: Biodegradable  
Method: OECD Test Guideline 301D

## 12.3 Bioaccumulative potential

### Components:

#### **dibenzoyl peroxide:**

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

### Product:

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Dispose of wastes in an approved waste disposal facility.  
The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.  
Clean container with water.  
Dispose of contents/ container to an approved waste disposal plant.  
Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 3104  
RID : UN 3104  
IMDG : UN 3104  
IATA : UN 3104

#### 14.2 UN proper shipping name

ADR : ORGANIC PEROXIDE TYPE C, SOLID (DIBENZOYL PEROXIDE)  
RID : ORGANIC PEROXIDE TYPE C, SOLID (DIBENZOYL PEROXIDE)  
IMDG : ORGANIC PEROXIDE TYPE C, SOLID (DIBENZOYL PEROXIDE)  
IATA : Organic peroxide type C, solid (Dibenzoyl peroxide)

#### 14.3 Transport hazard class(es)

Class	Subsidiary risks
-------	------------------

---

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

<b>ADR</b>	:	5.2	
<b>RID</b>	:	5.2	
<b>IMDG</b>	:	5.2	
<b>IATA</b>	:	5.2	HEAT

### 14.4 Packing group

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : P1  
Labels : 5.2  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : P1  
Hazard Identification Number : 539  
Labels : 5.2

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 5.2  
EmS Code : F-J, S-R

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : yes

**RID**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17) : Not applicable

Regulation on Persistent Organic Pollutants (Number 30595 and subsequent amendments published) : Not applicable

Regulation on prevention of major industrial accidents. Reg number 30702 P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 ENVIRONMENTAL HAZARDS

#### Other regulations:

Gefahrgruppe nach TRGS 741: II, S+ (German regulatory requirements)

Produkt unterliegt dem Sprengstoffgesetz (SprengG; Stoffgruppe C). (German regulatory requirement)

T.R. Regulation on Classification, Labeling and Packaging of Substances and Mixtures, dated December 11, 2013 and numbered 28848 from the Ministry of Environment and Urbanization and the subsequent amendments published.

Regulation on health and safety measures regarding working with chemicals (Number:28733, 2013 as amended (Nr. 32345, 2023). Occupational Exposure Limit Values (Annex 1)

Regulation on Import and Export of Certain Hazardous Chemicals, No. 32087, 2023 : Not applicable

#### The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AiIC (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX®A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TECI (TH) : On the inventory, or in compliance with the inventory

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.  
For further information see eSDS.

---

### SECTION 16: Other information

#### Full text of other abbreviations

TR OEL : Türkiye. Chemical Agents at Work - Annex I: Indicative occupational exposure limit values

TR OEL DU : Türkiye. Regulation on Dust Control. Occupational Dust Exposure Limit Values (Annex 1)

TR OEL / TWA (8 Hour) : Measured or calculated in relation to a reference period of eight-hour time-weighted average

TR OEL DU / ZOAD/TWA : Time Weighted Average Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure-Activity Relationship

# SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



## BENOX® A-75

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	02.10.2024	600000000135	Date of first issue: 09.03.2017

---

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.  
These safety instructions also apply to empty packaging which may still contain product residues.  
The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN