# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

### **SECTION 1. IDENTIFICATION**

: BENOX®A-75 Trade name

CAS-No. 94-36-0

Manufacturer or supplier's details

Company name of supplier United Initiators, Inc.

Address 555 Garden Street

Elyria OH 44035 USA

Telephone +1-440-323-3112

Telefax +1-440-323-2659

Emergency telephone CHEMTREC US (24h): +1-800-424-9300

> CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person

responsible for the SDS

: cs-initiators.nafta@united-in.com

# Recommended use of the chemical and restrictions on use

Recommended use Hardener

polymerization initiators

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Organic peroxides : Type C

Eye irritation Category 2B

Skin sensitization Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

Category 1

hazard

### **GHS** label elements

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H320 Causes eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

### Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.

P234 Keep only in original container.

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

# Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

#### Storage:

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding 30 °C/

86 °F. Keep cool.

P420 Store away from other materials.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Chemical nature : Organic Peroxide

Substance name : Dibenzoyl peroxide

CAS-No. : 94-36-0

# Components

Chemical name	CAS-No.	Concentration (% w/w)
Peroxide, dibenzoyl	94-36-0	> 70 - <= 77

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

If inhaled : Administer oxygen if breathing is difficult or cyanosis is

observed.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If symptoms persist, call a physician.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

If swallowed : Call a physician immediately.

Keep respiratory tract clear.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapors may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions : P

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

# **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors). Keep away from heat and sources of ignition.

# BENOX®A-75



Version 3.2

Revision Date: 08/09/2023

SDS Number: 600000000135

Date of last issue: 04/13/2023 Date of first issue: 10/27/2016

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from combustible material.

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling

Open drum carefully as content may be under pressure.

Avoid formation of respirable particles.

Protect from contamination. Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling.

For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Keep in a well-ventilated place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

5 - 30 °C

41 - 86 °F

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Further information on stor-

age stability

: No decomposition if stored normally.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Peroxide, dibenzoyl	94-36-0	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0

**Engineering measures** : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : Filter type P

Use NIOSH approved respiratory protection.

Hand protection

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.47 mm

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.40 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the

hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Ensure that eyewash stations and safety showers are close

to the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets,

disposable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder

Color : white

Odor : aromatic

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/range : Decomposition: Decomposes below the melting point.

Boiling point/boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Organic peroxide

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

Upper explosion limit

No data available

Lower explosion limit / Lower

flammability limit

Lower explosion limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : not determined

Density : not determined

Bulk density : 590 kg/m3 (20 °C)

Solubility(ies)

Water solubility : 0.0004 g/l insoluble

Solubility in other solvents : soluble

Solvent: Phthalates

Partition coefficient: n-

octanol/water

log Pow: 3.2 (20 °C)

Autoignition temperature : not determined

Self-Accelerating decomposi-

tion temperature (SADT)

70 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : No data available

Explosive properties : Risk of explosion by shock, friction, fire or other sources of

ignition.

Avoid dust formation.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

Impact sensitivity : Sensitive to impact and/ or friction.

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Particle size : not determined

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

No decomposition if stored normally.

Possibility of hazardous reac-

tions

Dust may form explosive mixture in air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks.

Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): 24.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : Remarks: No data available

**Components:** 

Peroxide, dibenzoyl:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 24.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

Remarks : May cause skin irritation in susceptible persons.

**Components:** 

Peroxide, dibenzoyl:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

**Product:** 

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Method : OECD Test Guideline 405

Remarks : Product dust may be irritating to eyes, skin and respiratory

system.

**Components:** 

Peroxide, dibenzoyl:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

# Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified based on available information.

**Product:** 

Routes of exposure : Skin contact

Species : Mouse

Method : Local lymph node assay (LLNA)

Result : Causes sensitization.

Remarks : Causes sensitization.

Remarks : Causes sensitization.

#### **Components:**

Peroxide, dibenzoyl:

Routes of exposure : Skin contact Species : Mouse

Method : Local lymph node assay (LLNA)

Result : May cause sensitization by skin contact.

### Germ cell mutagenicity

Not classified based on available information.

**Product:** 

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test

Species: Mouse Result: negative

**Components:** 

Peroxide, dibenzoyl:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test

Species: Mouse

# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

Result: negative

#### Carcinogenicity

Not classified based on available information.

**Product:** 

Remarks : This information is not available.

**Components:** 

Peroxide, dibenzoyl:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

**Components:** 

Peroxide, dibenzoyl:

Effects on fertility : Species: Rat, male

Application Route: Oral

General Toxicity Parent: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, female Application Route: Oral

General Toxicity Parent: NOAEL: 500 mg/kg body weight

Method: OECD Test Guideline 422

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

**Product:** 

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Components:

Peroxide, dibenzoyl:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT-repeated exposure

Not classified based on available information.

**Product:** 

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

**Components:** 

Peroxide, dibenzoyl:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

**Product:** 

Species : Rat

NOAEL : 1,000 mg/kg

Application Route : Oral Exposure time : 28 d

Method : OECD Test Guideline 422

**Components:** 

Peroxide, dibenzoyl:

Species : Rat

NOAEL : 1,000 mg/kg

Application Route : Oral Exposure time : 28 d

Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

**Product:** 

No aspiration toxicity classification

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

**Components:** 

Peroxide, dibenzoyl:

No aspiration toxicity classification

**Further information** 

**Product:** 

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Product:** 

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.071

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC10 (Daphnia magna (Water flea)): 0.001 mg/l

Exposure time: 21 d

Test Type: semi-static test

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

**Components:** 

Peroxide, dibenzoyl:

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.071

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.001 mg/l Exposure time: 21 d

Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

**Components:** 

Peroxide, dibenzoyl:

Biodegradability : Result: Biodegradable

Method: OECD Test Guideline 301D

# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

**Bioaccumulative potential** 

**Components:** 

Peroxide, dibenzoyl:

Partition coefficient: n-

octanol/water

: log Pow: 3.2 (20 °C / 20 °C)

Mobility in soil

No data available

Other adverse effects

**Product:** 

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

**International Regulations** 

**UNRTDG** 

UN number : UN 3104

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

Proper shipping name : ORGANIC PEROXIDE TYPE C, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

**IATA-DGR** 

UN/ID No. : UN 3104

Proper shipping name : Organic peroxide type C, solid

(Dibenzoyl peroxide)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen: 570

ger aircraft)

**IMDG-Code** 

UN number : UN 3104

Proper shipping name : ORGANIC PEROXIDE TYPE C, SOLID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3104

Proper shipping name : Organic peroxide type C, solid

(Dibenzoyl peroxide, 75%)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 146 Marine pollutant : yes

# Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# BENOX®A-75



Version Revision Date: SDS Number: Date of last issue: 04/13/2023 3.2 08/09/2023 60000000135 Date of first issue: 10/27/2016

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Organic peroxides

Respiratory or skin sensitization Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Peroxide, diben- 94-36-0

zoyl

#### **Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

# California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### International Regulations

Gefahrgruppe nach DGUV 13 Vorschrift 13 (bisher BGV B4): II, S+ (German regulatory requirements)

#### The ingredients of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AIIC (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TECI (TH) : On the inventory, or in compliance with the inventory

#### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 08/09/2023

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation,

# BENOX®A-75



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/13/2023

 3.2
 08/09/2023
 600000000135
 Date of first issue: 10/27/2016

and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8