According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BENOX®L-40LV-EU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Curing chemical

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH

Dr.-Gustav-Adolph-Str. 3

82049 Pullach

Telephone : +49 / 89 / 74422 - 0

E-mail address of person

responsible for the SDS

: contact@united-in.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Organic peroxides, Type E H242: Heating may cause a fire.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Short-term (acute) aquatic hazard, Cate-

gory 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Cat-

egory 1

H410: Very toxic to aquatic life with long lasting

effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal word : Warning

Hazard statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P234 Keep only in original packaging. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection/ hearing protection.

Response:

P370 + P378 In case of fire: Use water spray, alcohol-

resistant foam, dry chemical or carbon dioxide to

extinguish.

P391 Collect spillage.

Hazardous components which must be listed on the label:

dibenzoyl peroxide (CAS-No. 94-36-0)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide

Liquid mixture

Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

	EC-No. Index-No. Registration number		(% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 ——— M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 35 - < 40
Silanamine, 1,1,1-trimethyl-N-	68909-20-6	STOT RE 2; H373	>= 1 - < 5
(trimethylsilyl)-, hydrolysis products with silica	272-697-1 014-052-00-7	(Lungs)	
Substances with a workplace exposure limit :			
Zinc stearate	557-05-1 209-151-9 01-2119982400-42		>= 1 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If inhaled : Administer oxygen if breathing is difficult or cyanosis is ob-

served.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

In case of skin contact : If symptoms persist, call a physician.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Keep respiratory tract clear.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : sensitising effects

Risks : May cause an allergic skin reaction.

Causes serious eye irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

*w*ater.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment. Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material.

Hygiene measures : Avoid contact with skin, eyes and clothing. Keep away from

food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately

after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in cool place. Keep in a well-ventilated place. Contamination may result in dangerous pressure increases - closed containers may rupture. Observe label precautions. Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem-

perature

0 - 30 °C

Further information on stor-

age stability

Stable under recommended storage conditions.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	GB EH40
Zinc stearate	557-05-1	TWA (inhalable dust)	10 mg/m3	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

TWA (Respirable dust)	4 mg/m3	GB EH40
STEL (inhalable dust)	20 mg/m3	GB EH40

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
dibenzoyl peroxide	Workers	Inhalation	Long-term systemic effects	39 mg/m3
	Workers	Skin contact	Long-term systemic effects	34.3 mg/kg bw/day
Zinc stearate	Workers	Inhalation	Long-term systemic effects	0.025683 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.022529 mg/m3

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0.02 μg/l
	Marine water	0.002 μg/l
	Sewage treatment plant	0.35 mg/l
	Fresh water sediment	0.013 mg/kg dry weight (d.w.)
	Marine sediment	0.001 mg/kg dry weight (d.w.)
	Soil	0.003 mg/kg dry weight (d.w.)
Zinc stearate	Fresh water	0.00826 mg/l
	Marine water	0.00826 mg/l
	Intermittent use/release	0.00413 mg/l
	Sewage treatment plant	0.052 mg/l
	Fresh water sediment	13.24328 mg/kg
		dry weight (d.w.)
	Marine sediment	13.24328 mg/kg dry weight (d.w.)
	Soil	6.26389 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.40 mm

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.47 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Skin and body protection : Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tıal.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable

suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

SDS Number: Version **Revision Date:** Date of last issue: 10.03.2023 2.0 Date of first issue: 18.10.2022 28.01.2025 60000000797

Appearance **Emulsion**

Colour white

Odour characteristic

Odour Threshold not determined

pΗ Not applicable substance/mixture is non-soluble (in water)

Melting point/ range not determined

Boiling point/boiling range Decomposition: Decomposes below the boiling point.

Flash point Not applicable

Evaporation rate No data available

Flammability (solid, gas) does not ignite

Upper explosion limit / Upper

flammability limit

Upper explosion limit

not determined

Lower explosion limit / Lower : Lower explosion limit

flammability limit

not determined

Vapour pressure not determined

Relative vapour density not determined

Relative density not determined

1.150 g/cm3 (25 °C) Density

Bulk density Not applicable

Solubility(ies)

Water solubility insoluble

Solubility in other solvents soluble

Solvent: organic solvents

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature not determined

Viscosity

Viscosity, dynamic ca. 1,000 mPa.s (25 °C)

Viscosity, kinematic not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

SDS Number: Version **Revision Date:** Date of last issue: 10.03.2023 2.0 Date of first issue: 18.10.2022 28.01.2025 60000000797

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Organic peroxide

9.2 Other information

Self-Accelerating decomposi- : >= 50 °C

tion temperature (SADT)

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Flammability (liquids) Organic peroxide

Self-heating substances The substance or mixture is not classified as self heating.

Refractive index No data available

Particle size Not applicable

Self-ignition The substance or mixture is not classified as pyrophoric.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

Heating may cause a fire or explosion.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

10.5 Incompatible materials

Materials to avoid Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 (Rat, male): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 24.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : Remarks: No data available

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Zinc stearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 200 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

dibenzoyl peroxide:

Species : Rabbit Exposure time : 4 h

Method : OECD Test Guideline 404

Result : No skin irritation

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Zinc stearate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

dibenzoyl peroxide:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Zinc stearate:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Species : Rabbit
Method : Draize Test
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

dibenzoyl peroxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : May cause sensitisation by skin contact.

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Zinc stearate:

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar sub-

stances.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Test system: mouse lymphoma cells Method: OECD Test Guideline 476

Result: negative GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: negative GLP: yes

Germ cell mutagenicity- As-

sessment

Based on available data, the classification criteria are not met.

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: No information available.

Result: negative

Zinc stearate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat Result: Equivocal

Carcinogenicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Remarks : Not classified due to data which are conclusive although insuf-

ficient for classification.

Carcinogenicity - Assess-

ment

: Based on available data, the classification criteria are not met.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Reproductive toxicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Effects on fertility : Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: NOAEL: 500 mg/kg bw/day

Method: OECD Test Guideline 422

Effects on foetal develop-

ment

Species: Rat

Application Route: Oral

General Toxicity Maternal: NOAEL: 300 mg/kg bw/day Embryo-foetal toxicity: NOAEL: 300 mg/kg bw/day

Method: OECD Test Guideline 414

GLP: yes

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

Zinc stearate:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity F1: NOAEL: 7.5 mg/kg body weight

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Species: Mouse

Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: 30 mg/kg body weight

Teratogenicity: NOAEL: 30 mg/kg body weight Remarks: Based on data from similar materials

STOT - single exposure

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Exposure routes : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Components:

dibenzoyl peroxide:

Exposure routes : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

dibenzoyl peroxide:

Species : Rat, male and female NOAEL : 1000 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Method : OECD Test Guideline 408

Zinc stearate:

Species : Mouse NOAEL : 458 mg/kg

Application Route : Oral

Method : OECD Test Guideline 408

Aspiration toxicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

Components:

Zinc stearate:

Remarks : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

Version SDS Number: Date of last issue: 10.03.2023 Revision Date: Date of first issue: 18.10.2022 2.0 28.01.2025 60000000797

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

: Very toxic to aquatic life with long lasting effects. Chronic aquatic toxicity

Components:

dibenzoyl peroxide:

Toxicity to fish EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.071

mg/l

End point: Growth rate Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to microorganisms EC50 (Bacteria): 35 mg/l

Exposure time: 30 min

Test Type: Respiration inhibition Method: OECD Test Guideline 209

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC10: 0.001 mg/l

End point: reproduction rate

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Toxicity to soil dwelling or-

ganisms

LC50: >

1000 milligram per kilogram

Exposure time: 14 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Zinc stearate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,000 mg/l

Exposure time: 0.5 h Method: DIN 38 412 Part 8

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

12.2 Persistence and degradability

Components:

dibenzoyl peroxide:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 71 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Biodegradability : Remarks: No data available

Zinc stearate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

dibenzoyl peroxide:

Partition coefficient: n- : log Pow: 3.2 (20 °C)

octanol/water Method: OECD Test Guideline 117

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Partition coefficient: n-

octanol/water

: Remarks: Not applicable

Zinc stearate:

Partition coefficient: n-

octanol/water

: Remarks: No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

Components:

Zinc stearate:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : UN 3107
RID : UN 3107
IMDG : UN 3107
IATA : UN 3107

14.2 UN proper shipping name

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

ADR : ORGANIC PEROXIDE TYPE E, LIQUID

(DIBENZOYL PEROXIDE)

RID : ORGANIC PEROXIDE TYPE E, LIQUID

(DIBENZOYL PEROXIDE)

IMDG : ORGANIC PEROXIDE TYPE E, LIQUID

(DIBENZOYL PEROXIDE)

IATA : Organic peroxide type E, liquid

(Dibenzoyl peroxide)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 5.2 RID : 5.2

IMDG : 5.2

IATA : 5.2 HEAT

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : P1 Hazard Identification Number : 539 Labels : 5.2

IMDG

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo

: 570

aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passen- : 570

ger aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADR

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the fol-

lowing entries should be considered:

Number on list 3

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

: Not applicable

Regulation (EC) on substances that deplete the ozone

layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Not applicable

Control of Major Accident Hazards Regulations P6b

2015 (COMAH)

SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC

PEROXIDES

E1 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AIIC (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

IECSC (CN) : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H241 : Heating may cause a fire or explosion. H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Org. Perox. : Organic peroxides
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

The hazards on the label also apply to residues in the con-

tainer.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Org. Perox. E	H242	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Based on product data or assessment
Aquatic Chronic 1	H410	Based on product data or assessment

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BENOX®L-40LV-EU

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2023

 2.0
 28.01.2025
 600000000797
 Date of first issue: 18.10.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN