

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CUROX M-302R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH
Dr.-Gustav-Adolph-Str. 3
82049 Pullach

E-mail address of person
responsible for the SDS : contact@united-in.com

1.4 Emergency telephone number

+49 / 89 / 74422 – 0 (24 h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Organic peroxides, Type D	H242: Heating may cause a fire.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006




CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H242 Heating may cause a fire. H302 + H332 Harmful if swallowed or if inhaled H314 Causes severe skin burns and eye damage. H361d Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials. P233 Keep container tightly closed. P235 Keep cool. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P262 Do not get in eyes, on skin, or on clothing. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P315 Get immediate medical advice/ attention. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Trimethylpentanediol isobutyrate (CAS-No. 6846-50-0)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

2-Butanone, peroxide (CAS-No. 1338-23-4)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide
Liquid mixture

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Trimethylpentanediol isobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 40 - < 45
2-Butanone, peroxide	1338-23-4 215-661-2 01-2119514691-43	Org. Perox. D; H242 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 25 - < 30
Diacetone alcohol	123-42-2 204-626-7 01-2119473975-21	Eye Irrit. 2; H319 STOT SE 3; H335	>= 10 - < 15
Butanone	78-93-3 201-159-0 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 5
Hydrogen peroxide	7722-84-1 231-765-0 01-2119485845-22	Ox. Liq. 1; H271 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Call a physician immediately.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Call a physician immediately.
If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed or if inhaled
Causes serious eye damage.
Suspected of damaging the unborn child.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version 3.0	Revision Date: 15.10.2018	SDS Number: 600000000253	Print Date: 05.11.2018
----------------	------------------------------	-----------------------------	---------------------------

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
The product burns violently.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
The product will float on water and can be reignited on surface water.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Do not swallow.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Protect from contamination.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from combustible material.

Hygiene measures : Keep away from food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Advice on common storage : Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 30 °C

Other data : No decomposition if stored normally.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-Butanone, peroxide	2-Butanone, peroxide	STEL	0.2 ppm 1.5 mg/m ³	GB EH40
Diacetone alcohol	Diacetone alcohol	TWA	50 ppm 241 mg/m ³	GB EH40
		STEL	75 ppm 362 mg/m ³	GB EH40
Butanone	Butanone	TWA	200 ppm 600 mg/m ³	2000/39/EC
Further information	Indicative			
		STEL	300 ppm 900 mg/m ³	2000/39/EC
Further information	Indicative			
		TWA	200 ppm 600 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	300 ppm 899 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Hydrogen peroxide	Hydrogen	TWA	1 ppm	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

	peroxide		1.4 mg/m3	
		STEL	2 ppm 2.8 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Butanone	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Butanone, peroxide	Workers	Inhalation	Long-term systemic effects	2.35 mg/m3
	Workers	Skin contact	Long-term systemic effects	1.33 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	7.05 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-Butanone, peroxide	Fresh water	0.0056 mg/l
	Marine water	0.00056 mg/l
	Intermittent use/release	0.056 mg/l
	Sewage treatment plant	1.2 mg/l
	Fresh water sediment	0.0876 mg/kg
	Marine sediment	0.00876 mg/kg
	Soil	0.0142 mg/kg
	Fresh water	0.0056 mg/l
	Marine water	0.00056 mg/l
	Intermittent use/release	0.056 mg/l
	Sewage treatment plant	1.2 mg/l
	Fresh water sediment	0.0876 mg/kg
	Marine sediment	0.00876 mg/kg
	Soil	0.0142 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Respiratory protection	:	In the case of dust or aerosol formation use respirator with an approved filter.
Filter type	:	ABEK-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	red
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	No data available
Melting point/range	:	< -25 °C
Boiling point/boiling range	:	Decomposition: Decomposes below the boiling point.
Flash point	:	56 °C Method: ISO 3679
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	0.002 hPa (25 °C)
Density	:	1.04 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	6.53 g/l slightly soluble
Viscosity	:	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version 3.0	Revision Date: 15.10.2018	SDS Number: 600000000253	Print Date: 05.11.2018
----------------	------------------------------	-----------------------------	---------------------------

Viscosity, dynamic	:	21 mPa.s (20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing. Organic peroxide

9.2 Other information

Self-Accelerating decomposition temperature (SADT)	:	60 °C Method: UN-Test H.4 SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
Refractive index	:	1.434 at 20 °C
Self-ignition	:	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Vapours may form explosive mixture with air.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid	:	Protect from contamination. Contact with incompatible substances can cause decomposition at or below SADT. Heat, flames and sparks. Avoid confinement.
---------------------	---	---

10.5 Incompatible materials

Materials to avoid	:	Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents
--------------------	---	---

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled

Product:

- Acute oral toxicity : LD50 (Rat): 1,017 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): 4,000 mg/kg
Method: OECD Test Guideline 402

Components:

Trimethylpentanediol isobutyrate:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: Expert judgement
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LCLo (Rat): > 0.12 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg
Method: Expert judgement
Assessment: The substance or mixture has no acute dermal toxicity

2-Butanone, peroxide:

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement
- Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
Method: Expert judgement

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3,002 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): ≥ 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD0 (Rat): $> 1,875$ mg/kg
Method: OECD Test Guideline 402

Butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): $> 5,000$ mg/kg
Method: OECD Test Guideline 402

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): $> 6,500$ mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Extremely corrosive and destructive to tissue.

Components:

Trimethylpentanediol isobutyrate:

Species: Guinea pig
Exposure time: 24 h
Result: No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Remarks: Based on available data, the classification criteria are not met.

2-Butanone, peroxide:

Species: Rabbit

Result: Causes burns.

Diacetone alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Butanone:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Hydrogen peroxide:

Result: Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

Trimethylpentanediol isobutyrate:

Species: Rabbit

Result: No eye irritation

2-Butanone, peroxide:

Result: Irreversible effects on the eye

Diacetone alcohol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

Butanone:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

Hydrogen peroxide:

Result: Irreversible effects on the eye

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Components:

Trimethylpentanediol isobutyrate:

Species: Guinea pig

Result: Does not cause skin sensitisation.

2-Butanone, peroxide:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Assessment: Harmful if swallowed., Harmful if inhaled.

Diacetone alcohol:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Butanone:

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

: Method: OECD Test Guideline 471
Result: negative

: Method: OECD Test Guideline 476
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Components:

Trimethylpentanediol isobutyrate:

Genotoxicity in vitro : Method: OECD Test Guideline 476
Result: negative

: Test Type: Ames test
Result: negative

: Method: OECD Test Guideline 473
Result: negative

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

: Method: OECD Test Guideline 471
Result: negative

: Method: OECD Test Guideline 476
Result: negative

Diacetone alcohol:

Genotoxicity in vitro : Method: OECD Test Guideline 476
Result: negative

: Method: OECD Test Guideline 471
Result: negative

: Method: OECD Test Guideline 473
Result: negative

Butanone:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

: Method: OECD Test Guideline 476
Result: negative

: Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative

Hydrogen peroxide:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

- Genotoxicity in vitro : Test Type: Ames test
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Remarks: This information is not available.

Components:

2-Butanone, peroxide:

Remarks: This information is not available.

Diacetone alcohol:

Application Route: inhalation (vapour)
1.847 mg/l
Method: OECD Test Guideline 451
Remarks: Based on data from similar materials

Reproductive toxicity

Suspected of damaging the unborn child.

Product:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

Components:

Trimethylpentanediol isobutyrate:

Effects on foetal development : Species: Rabbit
Application Route: Oral
300 mg/kg

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

2-Butanone, peroxide:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 50 mg/kg body weight

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Method: OECD Test Guideline 421
Result: negative

Diacetone alcohol:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 300 mg/kg body weight
General Toxicity F1: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 422

Effects on foetal development : Species: Rat
Application Route: inhalation (vapour)
General Toxicity Maternal: NOAEL: 4.106
Embryo-foetal toxicity: NOAEL: 12,292
Method: OECD Test Guideline 414

Butanone:

Effects on fertility : Species: Rat
Application Route: oral (drinking water)
General Toxicity - Parent: NOAEL: 10,000 mg/l
General Toxicity F1: NOAEL: 10,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Species: Rat
Application Route: oral (drinking water)
General Toxicity - Parent: LOAEL: 20,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Effects on foetal development : Species: Rat
Application Route: Inhalation
General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body weight
Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Diacetone alcohol:

Target Organs: Respiratory system
Assessment: May cause respiratory irritation.

Butanone:

Assessment: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Hydrogen peroxide:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Product:

Species: Rat
NOAEL: 200 mg/kg
Application Route: oral (gavage)
Exposure time: 28 d
Method: OECD Test Guideline 407

Components:

2-Butanone, peroxide:

Species: Rat
NOAEL: 200 mg/kg
Application Route: oral (gavage)
Exposure time: 28 d
Method: OECD Test Guideline 407

Diacetone alcohol:

Species: Rat
NOAEL: 1.04 mg/l
LOAEL: 4.685 mg/l
Application Route: inhalation (vapour)
Exposure time: 6 w
Method: OECD Test Guideline 412

Species: Rat
NOAEL: 100 mg/kg
Application Route: oral (gavage)
Method: OECD Test Guideline 422

Hydrogen peroxide:

Species: Mouse
Application Route: Ingestion
Exposure time: 90 d
Symptoms: No adverse effects

Aspiration toxicity

Not classified based on available information.

Components:

Trimethylpentanediol isobutyrate:

Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- NOEC (Poecilia reticulata (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- NOEC (Daphnia magna (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Ecotoxicology Assessment

- Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

Trimethylpentanediol isobutyrate:

- Toxicity to fish : NOEC (Fish): ≥ 6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): ≥ 1.46 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

NOEC (Daphnia (water flea)): 0.7 mg/l
Exposure time: 21 d

Toxicity to algae : EC50 (Chlorella pyrenoidosa (aglae)): > 7.49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : LOEC: 0.7 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Diacetone alcohol:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EbC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 : > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Ecotoxicology Assessment

- Acute aquatic toxicity : This product has no known ecotoxicological effects.
- Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Butanone:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,150 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Hydrogen peroxide:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia pulex (Water flea)): 2.4 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version 3.0	Revision Date: 15.10.2018	SDS Number: 600000000253	Print Date: 05.11.2018
----------------	------------------------------	-----------------------------	---------------------------

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l
Exposure time: 72 h
NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 :
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.63 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Components:

Trimethylpentanediol isobutyrate:

Biodegradability : Result: rapidly biodegradable
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301A

Butanone:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

Trimethylpentanediol isobutyrate:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 1.95

Partition coefficient: n- : log Pow: 4.91 (25 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

octanol/water

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C)

Diacetone alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.9

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)

Hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57
Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 3105
ADR : UN 3105
RID : UN 3105
IMDG : UN 3105
IATA : UN 3105

14.2 UN proper shipping name

ADN : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S))
ADR : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S))
RID : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S))
IMDG : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S))
IATA : Organic peroxide type D, liquid
(Methyl ethyl ketone peroxide(s))

14.3 Transport hazard class(es)

ADN : 5.2
ADR : 5.2
RID : 5.2
IMDG : 5.2
IATA : 5.2

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2

ADR
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : P1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

Hazard Identification Number : 539
Labels : 5.2

IMDG

Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passenger aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P6b	SELF-REACTIVE	Quantity 1 50 t	Quantity 2 200 t
-----	---------------	--------------------	---------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Other regulations : Gefahrengruppe nach § 3 BGV B4: II (German regulatory requirements)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL (CA) : All components of this product are on the Canadian DSL

NZIoC (NZ) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H242 : Heating may cause a fire.
H271 : May cause fire or explosion; strong oxidizer.
H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H361d : Suspected of damaging the unborn child.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Org. Perox. : Organic peroxides
Ox. Liq. : Oxidizing liquids
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
STOT SE : Specific target organ toxicity - single exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CUROX M-302R

Version
3.0

Revision Date:
15.10.2018

SDS Number:
600000000253

Print Date:
05.11.2018

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN