

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CUROX M-340

Manufacturer or supplier's details

Company : United Initiators Pty Ltd

Address : 20-22 McPherson Street
Banksmeadow NSW 2019 Australia 09

Telephone : +61 2 9316 0035 (Monday–Friday office hours only)

Emergency telephone number : +49 89 744220 (24 hours specialist advise)

E-mail address : cs-initiators.au@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Curing chemical

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 1B

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Acute aquatic toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H242 Heating may cause a fire.

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

H302 + H332 Harmful if swallowed or if inhaled
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.

Precautionary statements

:

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
P233 Keep container tightly closed.
P234 Keep only in original container.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

Storage:

P405 Store locked up.
P410 Protect from sunlight.
P411 + P235 Store at temperatures not exceeding < 30 °C/ < 86 °F. Keep cool.
P420 Store away from other materials.

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Organic Peroxide
Liquid mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl phthalate	131-11-3	≥ 30 - < 35
2-Butanone, peroxide	1338-23-4	≥ 25 - < 30
2,4-Pentanedione, peroxide	37187-22-7	≥ 7.5 - < 10
Diacetone alcohol	123-42-2	≥ 7.5 - < 10
Polyethylene glycol	25322-68-3	≥ 7.5 - < 10
Butanone	78-93-3	≥ 1 - < 5
Hydrogen peroxide	7722-84-1	≥ 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Call a physician immediately.

If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Call a physician immediately.
If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.

SAFETY DATA SHEET

CUROX M-340



Version 1.2	Revision Date: 08.06.2018	SDS Number: 600000000413	Print Date: 15.06.2018
----------------	------------------------------	-----------------------------	---------------------------

- Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
The product burns violently.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
The product will float on water and can be reignited on surface water.
Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if nec-

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

for firefighters essary.
Use personal protective equipment.

Hazchem Code : 2WE

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from combustible material.
- Advice on safe handling : Do not swallow.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
-

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Protect from contamination.

Hygiene measures : Keep away from food and drink.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Electrical installations / working materials must comply with the technological safety standards.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 30 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m ³	AU OEL
		TWA	5 mg/m ³	ACGIH
2-Butanone, peroxide	1338-23-4	Peak limit	0.2 ppm 1.5 mg/m ³	AU OEL
		C	0.2 ppm	ACGIH
Diacetone alcohol	123-42-2	TWA	50 ppm 238 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
Butanone	78-93-3	STEL	300 ppm 890 mg/m ³	AU OEL

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

		TWA	150 ppm 445 mg/m ³	AU OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	AU OEL
		TWA	1 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

SAFETY DATA SHEET

CUROX M-340



Version 1.2	Revision Date: 08.06.2018	SDS Number: 600000000413	Print Date: 15.06.2018
----------------	------------------------------	-----------------------------	---------------------------

Colour	:	colourless
Odour	:	No data available
pH	:	Not applicable
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available Decomposition
Flash point	:	53 °C
Flammability (solid, gas)	:	Not applicable
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Density	:	1.14 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	slightly soluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	not determined
Oxidizing properties	:	The substance or mixture is not classified as oxidizing. Organic peroxide

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reac- tions	:	Vapours may form explosive mixture with air.
Conditions to avoid	:	Protect from contamination. Contact with incompatible substances can cause decomposi- tion at or below SADT. Heat, flames and sparks. Avoid confinement.
Incompatible materials	:	Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled

Product:

Acute oral toxicity : Acute toxicity estimate: 1,783 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
Method: Expert judgement

2,4-Pentanedione, peroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

Acute inhalation toxicity : LC50 (Rat, male): > 13.1 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: Expert judgement
Assessment: The substance or mixture has no acute dermal toxicity

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3,002 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): >= 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD0 (Rat): > 1,875 mg/kg
Method: OECD Test Guideline 402

Polyethylene glycol:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute dermal toxicity : Remarks: No data available

Butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Extremely corrosive and destructive to tissue.

Components:

dimethyl phthalate:

Species: Rabbit

Method: Draize Test

Result: No skin irritation

2-Butanone, peroxide:

Species: Rabbit

Result: Causes burns.

2,4-Pentanedione, peroxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Diacetone alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Polyethylene glycol:

Result: No skin irritation

Butanone:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Hydrogen peroxide:

Result: Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

dimethyl phthalate:

Species: Rabbit

Result: No eye irritation

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Method: OECD Test Guideline 405

2-Butanone, peroxide:

Result: Irreversible effects on the eye

2,4-Pentanedione, peroxide:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

Diacetone alcohol:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

Polyethylene glycol:

Result: No eye irritation

Butanone:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

Hydrogen peroxide:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: Causes sensitisation.

Components:

dimethyl phthalate:

Species: Mouse

Method: OECD Test Guideline 429

Result: Does not cause skin sensitisation.

2-Butanone, peroxide:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Assessment: Harmful if swallowed., Harmful if inhaled.

2,4-Pentanedione, peroxide:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Probability or evidence of skin sensitisation in humans

Remarks: Causes sensitisation.

Diacetone alcohol:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Polyethylene glycol:

Result: Does not cause skin sensitisation.

Butanone:

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

: Method: OECD Test Guideline 473
Result: negative

: Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration
Species: Rat
Application Route: Intraperitoneal
Result: negative

Test Type: Micronucleus test
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

2-Butanone, peroxide:

- Genotoxicity in vitro
- : Method: OECD Test Guideline 473
Result: negative
 - : Method: OECD Test Guideline 471
Result: negative
 - : Method: OECD Test Guideline 476
Result: negative

2,4-Pentanedione, peroxide:

- Genotoxicity in vitro
- : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive
 - : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
- Genotoxicity in vivo
- : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Diacetone alcohol:

- Genotoxicity in vitro
- : Method: OECD Test Guideline 476
Result: negative
 - : Method: OECD Test Guideline 471
Result: negative
 - : Method: OECD Test Guideline 473
Result: negative

Polyethylene glycol:

- Genotoxicity in vitro
- : Test Type: Ames test
Result: negative

Butanone:

- Genotoxicity in vitro
- : Method: OECD Test Guideline 471
Result: negative
 - : Method: OECD Test Guideline 476
Result: negative
 - : Method: OECD Test Guideline 473
Result: negative
- Genotoxicity in vivo
- : Species: Mouse
Application Route: Intraperitoneal
Method: OECD Test Guideline 474

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 451
Result: negative
Remarks: Based on data from similar materials

2-Butanone, peroxide:

Remarks: This information is not available.

2,4-Pentanedione, peroxide:

Remarks: This information is not available.

Diacetone alcohol:

Application Route: inhalation (vapour)
1.847 mg/l
Method: OECD Test Guideline 451
Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
Method: OECD Test Guideline 440
Result: negative

Effects on foetal development : Species: Rat
Application Route: Ingestion
General Toxicity Maternal: NOAEL: 840 mg/kg body weight
Developmental Toxicity: NOAEL: 3,570 mg/kg body weight
Method: OECD Test Guideline 414

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

2-Butanone, peroxide:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

2,4-Pentanedione, peroxide:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Diacetone alcohol:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 300 mg/kg body weight
General Toxicity F1: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 422

Effects on foetal development : Species: Rat
Application Route: inhalation (vapour)
General Toxicity Maternal: NOAEL: 4,106
Embryo-foetal toxicity: NOAEL: 12,292
Method: OECD Test Guideline 414

Polyethylene glycol:

Butanone:

Effects on fertility : Species: Rat
Application Route: oral (drinking water)
General Toxicity - Parent: NOAEL: 10,000 mg/l
General Toxicity F1: NOAEL: 10,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Species: Rat
Application Route: oral (drinking water)
General Toxicity - Parent: LOAEL: 20,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Effects on foetal development : Species: Rat
Application Route: Inhalation
General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body weight
Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

STOT - single exposure

Not classified based on available information.

Components:

Diacetone alcohol:

Target Organs: Respiratory system

Assessment: May cause respiratory irritation.

Hydrogen peroxide:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

dimethyl phthalate:

Species: Rat

NOAEL: 770 mg/kg

Application Route: Oral

Exposure time: 16 w

Method: OECD Test Guideline 408

2-Butanone, peroxide:

Species: Rat

NOAEL: 200 mg/kg

Application Route: oral (gavage)

Exposure time: 28 d

Method: OECD Test Guideline 407

Repeated dose toxicity - : Harmful if swallowed., Harmful if inhaled.

Assessment

Diacetone alcohol:

Species: Rat

NOAEL: 1.04 mg/l

LOAEL: 4.685 mg/l

Application Route: inhalation (vapour)

Exposure time: 6 w

Method: OECD Test Guideline 412

Species: Rat

NOAEL: 100 mg/kg

Application Route: oral (gavage)

Method: OECD Test Guideline 422

Polyethylene glycol:

Species: Dog

NOAEL: 500 mg/kg

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Application Route: Oral

Hydrogen peroxide:

Species: Mouse
Application Route: Ingestion
Exposure time: 90 d
Symptoms: No adverse effects

Aspiration toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

No aspiration toxicity classification

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

2,4-Pentanedione, peroxide:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dimethyl phthalate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 39 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | LC50 (Daphnia magna (Water flea)): > 52 mg/l
Exposure time: 48 h |
| Toxicity to algae | : | EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l
Exposure time: 72 h |
| Toxicity to fish (Chronic toxicity) | : | NOEC (Oncorhynchus mykiss (rainbow trout)): 11 mg/l
Exposure time: 102 d
Method: OECD Test Guideline 210

LOEC (Oncorhynchus mykiss (rainbow trout)): 24 mg/l
Exposure time: 102 d
Method: OECD Test Guideline 210 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic) | : | NOEC (Daphnia magna (Water flea)): 9.6 mg/l
Exposure time: 21 d |
-

SAFETY DATA SHEET

CUROX M-340



Version	Revision Date:	SDS Number:	Print Date:
1.2	08.06.2018	600000000413	15.06.2018

ic toxicity)

LOEC (*Daphnia magna* (Water flea)): 23 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50: 4,100 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

2-Butanone, peroxide:

Toxicity to fish : LC50 (*Poecilia reticulata* (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (*Poecilia reticulata* (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (*Daphnia magna* (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 5.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 2.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

2,4-Pentanedione, peroxide:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 67.6 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 7.05 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 5.36 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

CUROX M-340



Version 1.2	Revision Date: 08.06.2018	SDS Number: 600000000413	Print Date: 15.06.2018
----------------	------------------------------	-----------------------------	---------------------------

Toxicity to microorganisms : EC50: 614 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Diacetone alcohol:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EbC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Polyethylene glycol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 48 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (Cesar models), etc.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 398,913 mg/l
Exposure time: 72 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (Cesar models), etc.

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

Toxicity to microorganisms : IC50: 1,651,512 mg/l
Exposure time: 46 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (Cesar models), etc.

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,150 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia pulex (Water flea)): 2.4 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l
Exposure time: 72 h
NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.63 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50: Method: OECD Test Guideline 209

Persistence and degradability

Components:

dimethyl phthalate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301E

2-Butanone, peroxide:

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

2,4-Pentanedione, peroxide:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301A

Polyethylene glycol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

Butanone:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 1.54

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C)

2,4-Pentanedione, peroxide:

Partition coefficient: n-octanol/water : log Pow: 1.1 (25 °C)
Method: OECD Test Guideline 117

Diacetone alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.9

Polyethylene glycol:

Bioaccumulation : Bioconcentration factor (BCF): 3.2

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

Partition coefficient: n-octanol/water : log Pow: -2.3 (25 °C)

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)

Hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

Components:

2,4-Pentanedione, peroxide:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

SAFETY DATA SHEET

CUROX M-340



Version 1.2 Revision Date: 08.06.2018 SDS Number: 600000000413 Print Date: 15.06.2018

(METHYL ETHYL KETONE PEROXIDE(S), ACETYL ACETONE PEROXIDE)
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2

IATA-DGR

UN/ID No. : UN 3105
Proper shipping name : Organic peroxide type D, liquid
(Methyl ethyl ketone peroxide(s), Acetyl acetone peroxide)
Class : 5.2
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat
Packing instruction (cargo aircraft) : 570
Packing instruction (passenger aircraft) : 570

IMDG-Code

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S), ACETYL ACETONE PEROXIDE)
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S), ACETYL ACETONE PEROXIDE)
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2
Hazchem Code : 2WE

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons : Schedule 6

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

Commonwealth, State or Territory
legislation.

The components of this product are reported in the following inventories:

DSL (CA)	:	All components of this product are on the Canadian DSL
AICS (AU)	:	On the inventory, or in compliance with the inventory
NZIoC (NZ)	:	On the inventory, or in compliance with the inventory
ENCS (JP)	:	On the inventory, or in compliance with the inventory
ISHL (JP)	:	On the inventory, or in compliance with the inventory
KECI (KR)	:	On the inventory, or in compliance with the inventory
PICCS (PH)	:	On the inventory, or in compliance with the inventory
IECSC (CN)	:	On the inventory, or in compliance with the inventory
TCSI (TW)	:	On the inventory, or in compliance with the inventory
TSCA (US)	:	On TSCA Inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC₅₀ - Lethal Concentration to 50 % of a test population; LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Con-

SAFETY DATA SHEET

CUROX M-340



Version
1.2

Revision Date:
08.06.2018

SDS Number:
600000000413

Print Date:
15.06.2018

trol Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date format : dd.mm.yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN