according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NOROX®KP-100 FRED-3

Chemical nature : Organic Peroxide

Liquid mixture

Manufacturer or supplier's details

Company : United Initiators (Shanghai) Co. Ltd.

Address : Room 201, No. 2398 Hutai Road

200436 Baoshan District Shanghai

Telephone : +86 21 61172758

Emergency telephone number : +86 21 61172758

E-mail address : contact@degussa-aj.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquidColour: redOdour: mint-like

Combustible liquid. Heating may cause a fire. Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. Toxic to aquatic life.

GHS Classification

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 1B

Serious eye damage/eye irri-

tation

Category 1

Short-term (acute) aquatic : Category 2

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

hazard

GHS label elements

Hazard pictograms







Signal word Danger

Hazard statements H227 Combustible liquid.

H242 Heating may cause a fire.

H302 + H332 Harmful if swallowed or if inhaled. H314 Causes severe skin burns and eye damage.

H401 Toxic to aquatic life.

Precautionary statements Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.

P234 Keep only in original container.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

Storage:

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

P405 Store locked up.P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < 30 °C/ <

86 °F. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Physical and chemical hazards

Combustible liquid. Heating may cause a fire.

Health hazards

Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. Causes serious eye damage.

Environmental hazards

Toxic to aquatic life.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl phthalate	131-11-3	>= 55 -< 65
2-Butanone, peroxide	1338-23-4	>= 30 -< 35
Hydrogen peroxide	7722-84-1	>= 2.5 -< 3

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

Call a physician immediately.

If inhaled : Call a physician or poison control centre immediately.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Call a physician immediately.

If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed or if inhaled. Causes serious eye damage.

Causes severe burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating de-

composition reaction with release of flammable vapors which

may auto-ignite.

The product burns violently.

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Specific extinguishing methods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

Remove undamaged containers from fire area if it is safe to do

Use water spray to cool unopened containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition.

Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Prevention of secondary hazards

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 60000000448 Date of first issue: 2019/08/02

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Keep away from heat and sources of ignition.

Use only explosion-proof equipment. Keep away from combustible material.

Advice on safe handling : Do not swallow.

Do not breathe vapours/dust. Avoid contact with skin and eyes. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling. For personal protection see section 8.

Protect from contamination.

Avoidance of contact : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Storage

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

< 30 °C

Further information on stor-

age stability

No decomposition if stored normally.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
	101 11 0	. ,		10000
dimethyl phthalate	131-11-3	TWA	5 mg/m3	ACGIH
2-Butanone, peroxide	1338-23-4	С	0.2 ppm	ACGIH
Hydrogen peroxide	7722-84-1	PC-TWA	1.5 mg/m3	GBZ 2.1-
				2007
		TWA	1 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Eye/face protection : Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Hand protection

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Hygiene measures : Keep away from food and drink.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 60000000448 Date of first issue: 2019/08/02

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : red

Odour : mint-like

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : > 80 °C

Method: ISO 3679

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Density : 1.12 g/cm3 (20 °C)

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Self-Accelerating decomposi-

tion temperature (SADT)

>= 60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : 19 - 23 mPa.s

Explosive properties : Not explosive

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reac-

tions

Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,384 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.01 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Exposure time: 6 h
Test atmosphere: vapour

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg

Method: Expert judgement

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

dimethyl phthalate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

2-Butanone, peroxide:

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Species : Rabbit

Result : Causes burns.

Hydrogen peroxide:

Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

dimethyl phthalate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

2-Butanone, peroxide:

Result : Irreversible effects on the eye

Hydrogen peroxide:

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

dimethyl phthalate:

Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

2-Butanone, peroxide:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Assessment : Harmful if swallowed., Harmful if inhaled.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Germ cell mutagenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

Application Route: Intraperitoneal

Result: negative

Test Type: Micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Components:

dimethyl phthalate:

Species : Rat

Application Route : Skin contact

Method : OECD Test Guideline 451

Result : negative

Remarks : Based on data from similar materials

2-Butanone, peroxide:

Remarks : This information is not available.

Hydrogen peroxide:

Carcinogenicity - Assess-

ment

Carcinogenicity classification not possible from current data.

Reproductive toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

Effects on fertility : Species: Rat

Application Route: oral (gavage) Method: OECD Test Guideline 440

Result: negative

Effects on foetal develop-

ment

Species: Rat

Application Route: Ingestion

General Toxicity Maternal: NOAEL: 840 mg/kg body weight Developmental Toxicity: NOAEL: 3,570 mg/kg body weight

Method: OECD Test Guideline 414

2-Butanone, peroxide:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity - Parent: NOAEL: 50 mg/kg body weight

Method: OECD Test Guideline 421

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Hydrogen peroxide:

Assessment : May cause respiratory irritation.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

dimethyl phthalate:

Species : Rat
NOAEL : 770 mg/kg
Application Route : Oral
Exposure time : 16 w

Method : OECD Test Guideline 408

2-Butanone, peroxide:

Species : Rat
NOAEL : 200 mg/kg
Application Route : oral (gavage)

Exposure time : 28 d

Method : OECD Test Guideline 407

Repeated dose toxicity -

Assessment

: Harmful if swallowed., Harmful if inhaled.

Hydrogen peroxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 90 d

Symptoms : No adverse effects

Aspiration toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

Components:

dimethyl phthalate:

Remarks : No data available

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dimethyl phthalate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 52 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 11 mg/l

Exposure time: 102 d

Method: OECD Test Guideline 210

LOEC (Oncorhynchus mykiss (rainbow trout)): 24 mg/l

Exposure time: 102 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 21 d

LOEC (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 21 d

Toxicity to microorganisms : EC50: 4,100 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 39 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l

Method: OECD Test Guideline 202

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 60000000448 Date of first issue: 2019/08/02

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia pulex (Water flea)): 2.4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l

Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l

Exposure time: 72 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.63 mg/l

Exposure time: 21 d

Persistence and degradability

Components:

dimethyl phthalate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301E

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Bioaccumulative potential

Components:

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57

Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 1.54

2-Butanone, peroxide:

Partition coefficient: n-

octanol/water

log Pow: < 0.3 (25 °C)

Hydrogen peroxide:

Partition coefficient: n-

octanol/water

log Pow: -1.57

Remarks: Calculation

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Components:

dimethyl phthalate:

Additional ecological infor-

mation

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

IATA-DGR

UN/ID No. : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Methyl ethyl ketone peroxide(s))

Class : 5.2

Packing group : Not assigned by regulation

Labels : Division 5.2 - Organic peroxides, Handling Label - Keep Away

From Heat

Packing instruction (cargo :

aircraft)

Packing instruction (passen- :

ger aircraft)

570

570

IMDG-Code

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 60000000448 Date of first issue: 2019/08/02

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Gefahrgruppe nach § 3 BGV B4: Ib (German regulatory requirements) Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W7.2 Organic peroxides 50 t

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AICS (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

KECI (KR) : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

Sources of key data used to

compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

GBZ 2.1-2007 : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

according to GB/T 16483 and GB/T 17519



NOROX®KP-100 FRED-3

Version Revision Date: SDS Number: Date of last issue: 2019/08/02 1.1 2020/07/22 600000000448 Date of first issue: 2019/08/02

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / C : Ceiling limit

GBZ 2.1-2007 / PC-TWA : Permissible concentration - time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN