

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

SECTION 1. IDENTIFICATION

Product name : NOROX[®] MEC RED

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street
Elyria OH 44035

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300
CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person responsible for the SDS : cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1B

Serious eye damage : Category 1

Reproductive toxicity : Category 2

Short-term (acute) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Organic Peroxide
Liquid mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-Butanone, peroxide	1338-23-4	>= 25 - < 30
Trimethylpentanediol isobutyrate	6846-50-0	>= 15 - < 20
cyclohexanone, peroxide	12262-58-7	>= 10 - < 15
Butanone	78-93-3	>= 1 - < 5
Hydrogen peroxide	7722-84-1	>= 1 - < 2.5
2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.	92257-31-3	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Call a physician immediately.

If inhaled : Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Call a physician immediately.
If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty

SAFETY DATA SHEET

NOROX[®] MEC RED



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/04/2019	600000000094	Date of first issue: 04/04/2019

- of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes serious eye damage.
Suspected of damaging fertility or the unborn child.
Causes severe burns.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray jet
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
- The product burns violently.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

NOROX[®] MEC RED



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/04/2019	600000000094	Date of first issue: 04/04/2019

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Follow safe handling advice and personal protective equipment recommendations.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapors/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
Use only explosion-proof equipment.
Keep away from combustible material.

Advice on safe handling : Do not swallow.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Avoid formation of aerosol.

SAFETY DATA SHEET

NOROX® MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Electrical installations / working materials must comply with the technological safety standards.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 38 °C

Further information on storage stability : No decomposition if stored normally.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m ³	CA AB OEL
		TWA	5 mg/m ³	CA BC OEL
		TWAEV	5 mg/m ³	CA QC OEL
		TWA	5 mg/m ³	ACGIH
2-Butanone, peroxide	1338-23-4	(c)	0.2 ppm 1.4 mg/m ³	CA AB OEL
		C	0.2 ppm	CA BC OEL
		C	0.2 ppm 1.5 mg/m ³	CA QC OEL
		C	0.2 ppm	ACGIH
Butanone	78-93-3	TWA	200 ppm 590 mg/m ³	CA AB OEL
		STEL	300 ppm 885 mg/m ³	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL

SAFETY DATA SHEET

NOROX® MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

		TWAEV	50 ppm 150 mg/m ³	CA QC OEL
		STEV	100 ppm 300 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	CA AB OEL
		TWA	1 ppm	CA BC OEL
		TWAEV	1 ppm 1.4 mg/m ³	CA QC OEL
		TWA	1 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
- Hygiene measures : Keep away from food and drink.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : red
- Odor : very faint, mint-like
- pH : Not applicable
- Melting point/range : No data available
- Boiling point/boiling range : not determined
- Flash point : > 76 °C
Method: Seta closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Self-ignition : Not applicable Decomposition
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : No data available
- Relative vapor density : > 1
- Density : 1.1 g/cm³
- Solubility(ies)
Water solubility : soluble
- Partition coefficient: n-octanol/water : No data available
- Self-Accelerating decomposi- : 60 °C

SAFETY DATA SHEET

NOROX[®] MEC RED



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/04/2019	600000000094	Date of first issue: 04/04/2019

tion temperature (SADT) : SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : not determined

Oxidizing properties : The substance or mixture is not classified as oxidizing.
Organic peroxide

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.
Contact with incompatible substances can cause decomposition at or below SADT.
Heat, flames and sparks.
Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,652 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 5.77 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Components:

2-Butanone, peroxide:

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgment
- Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on data from similar materials
- Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
Method: Expert judgment

Trimethylpentanediol isobutyrate:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: Expert judgment
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LCLo (Rat): > 0.12 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist
Method: Expert judgment
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg
Method: Expert judgment
Assessment: The substance or mixture has no acute dermal toxicity

cyclohexanone, peroxide:

- Acute oral toxicity : LD50 (Rat): 1,155 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50: > 2,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Butanone:

- Acute oral toxicity : LD50 (Rat): 2,193 mg/kg
Method: OECD Test Guideline 423
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

NOROX® MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Hydrogen peroxide:

- Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI
- Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

- Remarks : Extremely corrosive and destructive to tissue.

Components:

2-Butanone, peroxide:

- Species : Rabbit
Result : Causes burns.

Trimethylpentanediol isobutyrate:

- Species : Guinea pig
Exposure time : 24 h
Result : No skin irritation
Remarks : Based on available data, the classification criteria are not met.

cyclohexanone, peroxide:

- Species : Rabbit
Result : Severe skin irritation

Butanone:

- Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Hydrogen peroxide:

- Result : Corrosive after 3 minutes or less of exposure

2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.:

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-Butanone, peroxide:

Result : Irreversible effects on the eye

Trimethylpentanediol isobutyrate:

Species : Rabbit
Result : No eye irritation

cyclohexanone, peroxide:

Species : Rabbit
Result : Severe irritation

Butanone:

Species : Rabbit
Result : Eye irritation
Method : OECD Test Guideline 405

Hydrogen peroxide:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2-Butanone, peroxide:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitization.

Assessment : Harmful if swallowed., Harmful if inhaled.

Trimethylpentanediol isobutyrate:

Species : Guinea pig
Result : Does not cause skin sensitization.

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Butanone:

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

Method: OECD Test Guideline 471
Result: negative

Method: OECD Test Guideline 476
Result: negative

Trimethylpentanediol isobutyrate:

Genotoxicity in vitro : Method: OECD Test Guideline 476
Result: negative

Test Type: Ames test
Result: negative

Method: OECD Test Guideline 473
Result: negative

cyclohexanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: positive

Genotoxicity in vivo : Species: Mouse
Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative

Butanone:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

Method: OECD Test Guideline 476
Result: negative

Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Intraperitoneal

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Method: OECD Test Guideline 474

Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Butanone, peroxide:

Remarks : This information is not available.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

2-Butanone, peroxide:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

Trimethylpentanediol isobutyrate:

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

Butanone:

Effects on fertility : Species: Rat
Application Route: oral (drinking water)
General Toxicity Parent: NOAEL: 10,000 mg/l
General Toxicity F1: NOAEL: 10,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Species: Rat
Application Route: oral (drinking water)
General Toxicity Parent: LOAEL: 20,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Effects on fetal development : Species: Rat

SAFETY DATA SHEET

NOROX® MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Application Route: Inhalation
General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body weight
Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight
Method: OECD Test Guideline 414
Result: negative

2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Components:

Butanone:

Assessment : May cause drowsiness or dizziness.

Hydrogen peroxide:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

2-Butanone, peroxide:

Species : Rat
NOAEL : 200 mg/kg
Application Route : oral (gavage)
Exposure time : 28 d
Method : OECD Test Guideline 407

Repeated dose toxicity - Assessment : Harmful if swallowed., Harmful if inhaled.

Hydrogen peroxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 90 d
Symptoms : No adverse effects.

Aspiration toxicity

Not classified based on available information.

Components:

Trimethylpentanediol isobutyrate:

Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Trimethylpentanediol isobutyrate:

Toxicity to fish : NOEC (Fish): \geq 6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): \geq 1.46 mg/l
Exposure time: 48 h

NOEC (Daphnia): 0.7 mg/l
Exposure time: 21 d

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Toxicity to algae : EC50 (Chlorella pyrenoidosa): > 7.49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : LOEC (Daphnia magna (Water flea)): 0.7 mg/l
Exposure time: 21 d

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

cyclohexanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 48 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : EC10 (Bacteria): 11.1 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,150 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia pulex (Water flea)): 2.4 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l
Exposure time: 72 h
NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.63 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50: Method: OECD Test Guideline 209

Persistence and degradability

Components:

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Trimethylpentanediol isobutyrate:

Biodegradability : Result: rapidly biodegradable
Exposure time: 28 d
Method: OECD Test Guideline 301B

cyclohexanone, peroxide:

Biodegradability : Result: rapidly biodegradable
Method: OECD Test Guideline 301D

Butanone:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C)

Trimethylpentanediol isobutyrate:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 1.95

Partition coefficient: n-octanol/water : log Pow: 4.91 (25 °C)

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

cyclohexanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: 1.26

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)

Hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S),
CYCLOHEXANONE PEROXIDE(S))
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2

IATA-DGR

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

UN/ID No. : UN 3105
Proper shipping name : Organic peroxide type D, liquid
(Methyl ethyl ketone peroxide(s), Cyclohexanone peroxide(s))
Class : 5.2
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat
Packing instruction (cargo aircraft) : 570
Packing instruction (passenger aircraft) : 570

IMDG-Code

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S),
CYCLOHEXANONE PEROXIDE(S))
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S),
CYCLOHEXANONE PEROXIDE(S))
Class : 5.2
Packing group : II
Labels : 5.2
ERG Code : 145
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : dimethyl phthalate
Butanone
Xylene
ethylbenzene

The ingredients of this product are reported in the following inventories:

DSL (CA) : All components of this product are on the Canadian DSL
KECI (KR) : On the inventory, or in compliance with the inventory
PICCS (PH) : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

NOROX[®] MEC RED



Version 1.0 Revision Date: 04/04/2019 SDS Number: 600000000094 Date of last issue: -
Date of first issue: 04/04/2019

IECSC (CN) : On the inventory, or in compliance with the inventory
TCSI (TW) : On the inventory, or in compliance with the inventory
TSCA (US) : On TSCA Inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIH / C : Ceiling limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA BC OEL / C : ceiling limit
CA QC OEL / TWAEV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value
CA QC OEL / C : Ceiling

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;

SAFETY DATA SHEET

NOROX[®] MEC RED



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/04/2019	600000000094	Date of first issue: 04/04/2019

NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.
These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/04/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / Z8