according to the Hazardous Products Regulations



NOROX[®]410-50OMS

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019

SECTION 1. IDENTIFICATION

Trade name	:	NOROX [®] 410-50OMS	
Other means of identification	:	No data available	
Manufacturer or supplier's c	leta	ails	
Company name of supplier	:	United Initiators, Inc.	
Address	:	555 Garden Street Elyria OH 44035 USA	
		United Initiators Canada Ltd. 2147 PG Pulp Mill Road Prince George, BC-V2N 2S6 CANADA	
Telephone	:	+1-440-323-3112	
Telefax	:	+1-440-323-2659	
Emergency telephone	:	CHEMTREC US (24h): CHEMTREC WORLD (24h): CANUTEC (24h):	+1-800-424-9300 +1-703-527-3887 1-613-996-6666
For Transportation Incidents	:	GFL Environmental Inc. (24h): 1-800-567-7455	
E-mail address of person responsible for the SDS	:	cs-initiators.nafta@united-in.com	
Recommended use of the cl Recommended use	nen :	nical and restrictions on use polymerization initiators	

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids	:	Category 3
Organic peroxides	:	Туре Е
Skin sensitization	:	Category 1
Reproductive toxicity	:	Category 1B

according to the Hazardous Products Regulations



NOROX®410-500MS

Versio 4.2	on	Revision Date: 10/24/2024		DS Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
Ļ	Aspirat	ion hazard	:	Category 1	
	Short-te hazard	erm (acute) aquatic	:	Category 1	
	Long-te hazard	erm (chronic) aquatic	:	Category 2	
		bel elements pictograms	:		
S	Signal	Word	:	Danger	
ŀ	Hazard	Statements	:	H317 May cause H360F May dama H400 Very toxic t	ay cause a fire. al if swallowed and enters airways. an allergic skin reaction. age fertility.
F	Precau	tionary Statements	:	Prevention:	
				 P202 Do not hand and understood. P210 Keep away and other ignition P233 Keep conta P234 Keep only i P240 Ground and P241 Use explosion P242 Use non-sp P243 Take action P261 Avoid breat P272 Contamination the workplace. P273 Avoid relea 	to prevent static discharges. hing mist or vapors. red work clothing should not be allowed out of se to the environment. ctive gloves/ protective clothing/ eye protection/
				CENTER/ doctor. P303 + P361 + P all contaminated	WALLOWED: Immediately call a POISON 353 IF ON SKIN (or hair): Take off immediately clothing. Rinse skin with water. exposed or concerned: Get medical advice/

P308 + P313 IF exposed or concerned: Get medical advice/

according to the Hazardous Products Regulations

NOROX[®]410-500MS



Version 4.2	Revision Date: 10/24/2024	SDS Number: 600000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019	
		P333 + P313 If attention. P362 + P364 Ta reuse. P370 + P378 In	nduce vomiting. skin irritation or rash occurs: Get medical advice/ ake off contaminated clothing and wash it before case of fire: Use water spray, alcohol-resistant ical or carbon dioxide to extinguish. billage.	
		Storage:P403 + P235Store in a well-ventilated place. Keep coolP405Store locked up.P410Protect from sunlight.P411Store at temperatures not exceeding < 50 °F/ < 10		
		Disposal: P501 Dispose o	of contents/ container to an approved waste dis-	

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

posal plant.

Substance / Mixture	:	Mixture	

Chemical nature	:	Organic Peroxide
		Liquid mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
tert-Butyl 2- ethylperoxyhexanoate	tert-Butyl 2- ethylperoxyhex- anoate	3006-82-4	>= 50 - < 55 *
Contains one or both isoparaffinic hydrocar- bons (Naphtha hy- drotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9)	Contains one or both isoparaffin- ic hydrocarbons (Naphtha hy- drotreated heavy CAS 64742-48-9, Alkanes, C10- 13-iso CAS 68551-19-9)		>= 45 - < 50 *

* Actual concentration or concentration range is withheld as a trade secret

according to the Hazardous Products Regulations

NOROX®410-50OMS



Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022	
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019	

SECTION 4. FIRST AID MEASURES

General advice	:	Take off contaminated clothing and shoes immediately. Call a physician immediately. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended. Symptoms of poisoning may appear several hours later. No artificial respiration, mouth-to-mouth or mouth to nose. Use auticable instruments (apparents)
If inhaled	:	suitable instruments/apparatus. Administer oxygen if breathing is difficult or cyanosis is observed. If breathed in, move person into fresh air. If not breathing, give artificial respiration. Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear.
In case of skin contact	:	If symptoms persist, call a physician. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before re-use. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Call a physician immediately. Contact a poison control center. Keep respiratory tract clear. Do NOT induce vomiting. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May damage fertility. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May damage fertility.

according to the Hazardous Products Regulations



Versi 4.2	ion	Revision Date: 10/24/2024		0S Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
				sensitizing effects	
	Protect	ion of first-aiders	:		ers should pay attention to self-protection nmended protective clothing
	Notes t	o physician	:	Treat symptomation	cally and supportively.
SEC	TION 5	. FIRE-FIGHTING ME	ASL	IRES	
	Suitable	e extinguishing media	:	Water spray jet Alcohol-resistant f Carbon dioxide (C Dry chemical	
	Unsuita media	ble extinguishing	:	High volume wate	r jet
	Specific	c hazards during fire	:	Possible emission lead to a dangero Avoid confinemen Contact with incor temperatures exce	npatible materials or exposure to eeding SADT may result in a self- mposition reaction with release of flammable
				Do not allow run-o courses. Vapors may form The product will fl water.	s violently. le over considerable distance. off from fire fighting to enter drains or water explosive mixtures with air. oat on water and can be reignited on surface iners exposed to fire with water spray.
	Specific ods	c extinguishing meth-	:	fire. Remove undamaç so.	I water stream as it may scatter and spread ged containers from fire area if it is safe to do o cool unopened containers.
	Further	information	:	circumstances and Use a water spray Collect contamina must not be disch Fire residues and	measures that are appropriate to local d the surrounding environment. to cool fully closed containers. ted fire extinguishing water separately. This arged into drains. contaminated fire extinguishing water must accordance with local regulations.

according to the Hazardous Products Regulations



Revision Date:

Version



Date of last issue: 01/24/2022

4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019
	Special protective equipment for fire-fighters	: Wear self-contair necessary.	ned breathing apparatus for firefighting if
		Use personal pro	tective equipment.

SDS Number: 60000000165

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Follow safe handling advice and personal protective equipment recommendations. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Never return spills in original containers for re-use. Treat recovered material as described in the section "Disposal considerations".
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contact with incompatible substances can cause decomposition at or below SADT. Clear spills immediately. Suppress (knock down) gases/vapors/mists with a water spray jet. To clean the floor and all objects contaminated by this material, use plenty of water. Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Advice on protection against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

according to the Hazardous Products Regulations





Version 4.2	Revision Date: 10/24/2024		0S Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
			Use only explosic Keep away from a ignition. Keep away from a	heat and sources of ignition. on-proof equipment. open flames, hot surfaces and sources of combustible material. a naked flame or any incandescent material.
Adv	rice on safe handling	:	Protect from cont Do not swallow. Do not breathe va Avoid exposure - Avoid contact with Avoid formation of Take precautiona Never return any originally removed Provide sufficient Avoid confinement Keep away from I other ignition sou Smoking, eating a application area. Wash thoroughly For personal prot Persons suscepti allergies, chronic	apors/dust. obtain special instructions before use. h skin and eyes. if aerosol. ry measures against static discharges. product to the container from which it was d. air exchange and/or exhaust in work rooms. nt. heat, hot surfaces, sparks, open flames and rces. No smoking. and drinking should be prohibited in the
Cor	nditions for safe storage	:	Store in cool plac Contamination ma closed containers Observe label pre Store in accordan Avoid impurities (Electrical installat the technological	tightly closed in a cool, well-ventilated place. e. ay result in dangerous pressure increases - a may rupture. ecautions. ace with the particular national regulations. e.g. rust, dust, ash), risk of decomposition. ions / working materials must comply with safety standards. are opened must be carefully resealed and
Mat	erials to avoid	:		combustible materials. strong acids, bases, heavy metal salts and bstances.
	commended storage tem- ature	:	< 10 °C	
	ther information on stor- stability	:	Stable under reco	ommended storage conditions.

according to the Hazardous Products Regulations



NOROX®410-50OMS

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9)	64742-48-9	TWA	525 mg/m3	CA ON OEL
Engineering measures	: Minimize worl	kplace exposure	concentrations.	
Personal protective equipment	nt			
Respiratory protection	In the case of approved filte		formation use respira	ator with an
Filter type	: ABEK-filter			
	Use NIOSH a	pproved respira	tory protection.	
Hand protection Material Break through time Glove thickness	Nitrile rubber <= 480 min 0.4 mm			
Material Break through time Glove thickness	: butyl-rubber : <= 60 min : 0.5 mm			
Remarks	standard valu material has t protective glo chemicals dep hazardous su For special a resistance to gloves with th	es! The exact br o be obtained fr ve. Choose glov pending on the c bstance and spe pplications, we r chemicals of the	time/strength of mat reak through time/stre om the producer of th res to protect hands a concentration and qua ecific to place of work recommend clarifying a aforementioned prot cturer. Wash hands b	ength of le lgainst antity of the the ective
Eye protection	to the worksta Please follow selecting prot Always wear	ation location. all applicable lo ective measures eye protection w	and safety showers a cal/national requirem for a specific workpl then the potential for cannot be excluded.	ents when ace.

according to the Hazardous Products Regulations



NOROX®410-500MS

Version 4.2	Revision Date: 10/24/2024	SDS Number: 600000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
		Please wea	g safety goggles r suitable protective goggles. Also wear face there is a splash hazard.
Skin	and body protection		opriate protective clothing based on chemical lata and an assessment of the local exposure
		task being p disposable s Wear as ap	ody garments should be used based upon the performed (e.g., sleevelets, apron, gauntlets, suits) to avoid exposed skin surfaces. propriate: dant antistatic protective clothing.
Prote	ective measures	to the conce	protective equipment must be selected according entration and amount of the dangerous substance fic workplace.
Hygi	ene measures	Keep away When using When using	ct with skin, eyes and clothing. from food and drink. do not eat or drink. do not smoke. s before breaks and immediately after handling

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	colorless
Odor	:	ester-like
рН	:	No data available
Melting point/ range	:	< -25 °C Active ingredient
Boiling point/boiling range	•	Not applicable Decomposition
Flash point	:	55 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Self-ignition	:	Not applicable

according to the Hazardous Products Regulations



NOROX®410-500MS

Versio 4.2	n Revision Date: 10/24/2024		S Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
	oper explosion limit / Upper mmability limit	:	No data available	9
	wer explosion limit / Lower mmability limit	:	No data available	9
Va	apor pressure	:	2 Pa (293.2 K) Active ingredient	
De	ensity	:	0.82 g/cm3 (20 °	C)
So	blubility(ies) Water solubility	:	negligible	
	artition coefficient: n- tanol/water	:	log Pow: 4.79 (20	O°C)
	lanol/water		Active ingredient	
	elf-Accelerating decomposi- in temperature (SADT)	:	temperature at w	erating Decomposition Temperature. Lowest hich the tested package size will undergo a decomposition reaction.
Vi	scosity Viscosity, dynamic		3.7 mPa.s (20 °(
		•	,	
	Viscosity, kinematic	:	No data available	9
0	kidizing properties	:	The substance of Organic peroxide	r mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions. Heating may cause a fire or explosion.
Chemical stability	:	Stable under recommended storage conditions. No decomposition if stored normally.
Possibility of hazardous reac- tions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Protect from contamination. Contact with incompatible substances can cause decomposition at or below SADT. Heat, flames and sparks. Avoid confinement.
Incompatible materials	:	Accelerators, strong acids and bases, heavy metals and

according to the Hazardous Products Regulations



		heavy metal s	alts, reducing agents
Hazar produ	dous decomposition cts		c, flammable, noxious/toxic gases and vapours n the case of fire and decomposition
ECTION	11. TOXICOLOGICAL	INFORMATION	
	toxicity I on available data, the	classification criteria	a are not met.
<u>Produ</u>	ıct:		
	oral toxicity	: Assessment: T icity	The substance or mixture has no acute oral tox
Acute	inhalation toxicity	: Assessment: T tion toxicity	he substance or mixture has no acute inhala-
Acute	dermal toxicity	: Assessment: T toxicity	he substance or mixture has no acute dermal
Comp	oonents:		
tert-B	utyl 2-ethylperoxyhe	kanoate:	
Acute	oral toxicity	Assessment: T icity	= 10,000 mg/kg D Test Guideline 401 The substance or mixture has no acute oral to> mortality observed at this dose.
Acute	inhalation toxicity	: LC50 (Rat): > 4 Exposure time Test atmosphe Assessment: T tion toxicity	:4 h
Acute	dermal toxicity		: 16,820 mg/kg D Test Guideline 402 The substance or mixture has no acute dermal
	ins one or both isopa Alkanes, C10-13-iso (ons (Naphtha hydrotreated heavy CAS 6474
	oral toxicity	: LD50 (Rat): > 5	5,000 mg/kg
Acute	inhalation toxicity	: LC50 (Rat): > Exposure time Test atmosphe Assessment: T tion toxicity	:8h

according to the Hazardous Products Regulations



	10/24/2024		S Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019	
			Remarks: Insuff	cient Data to Classify	
				rom similar materials	
Acute dermal toxicity		:	LD50 (Rabbit): > 5,000 mg/kg Assessment: The substance or mixture has no acute derm toxicity		
Skin o	corrosion/irritation				
Not cl	assified due to lack o	of data.			
<u>Produ</u>	<u>ict:</u>				
Rema	rks	:	May cause skin	irritation in susceptible persons.	
<u>Comp</u>	onents:				
tert-B	utyl 2-ethylperoxyh	exano	ate:		
Speci		:	Rabbit		
Metho Resul		:	OECD Test Guid No skin irritation		
48-9 , Asses	Alkanes, C10-13-iso sment		68551-19-9): Repeated expos	ure may cause skin dryness or cracking.	
48-9, Asses Resul	Alkanes, C10-13-iso sment t us eye damage/eye	irritati	68551-19-9): Repeated expose Repeated expose		
48-9, Asses Result Serio Not cl	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack c	irritati	68551-19-9): Repeated expose Repeated expose	ure may cause skin dryness or cracking.	
48-9, Asses Result Serio Not cl <u>Produ</u>	Alkanes, C10-13-iso isment t us eye damage/eye assified due to lack o <u>ict:</u>	irritati	68551-19-9): Repeated expos Repeated expos	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Result Serio Not cl	Alkanes, C10-13-iso isment t us eye damage/eye assified due to lack o <u>ict:</u>	irritati	68551-19-9): Repeated expos Repeated expos	ure may cause skin dryness or cracking.	
48-9, Asses Resul Serio Not cl <u>Produ</u> Rema	Alkanes, C10-13-iso isment t us eye damage/eye assified due to lack o <u>ict:</u>	irritati	68551-19-9): Repeated expos Repeated expos on Vapors may cau	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Resul Serio Not cl <u>Produ</u> Rema	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>lct:</u> rks	irritati of data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin.	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Result Serio Not cl Produ Rema Comp tert-B Specie	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>conents:</u> utyl 2-ethylperoxyh	irritati of data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin.	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Result Serio Not cl Produ Rema Comp tert-B Specia Result	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>ponents:</u> utyl 2-ethylperoxyh es t	irritati if data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin.	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Result Serio Not cl Produ Rema Comp tert-B Specie	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>ponents:</u> utyl 2-ethylperoxyh es t	irritati if data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin.	sure may cause skin dryness or cracking. Sure may cause skin dryness or cracking.	
48-9, Asses Resul Serio Not cl <u>Produ</u> Rema <u>Comp</u> tert-B Specie Resul Metho	Alkanes, C10-13-iso isment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>bonents:</u> utyl 2-ethylperoxyh es t od iins one or both iso	irritati of data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin. ate: Rabbit No eye irritation OECD Test Guide nic hydrocarbor	deline 405	
48-9, Asses Resul Serio Not cl <u>Produ</u> Rema <u>Comp</u> tert-B Specie Resul Metho	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>bonents:</u> utyl 2-ethylperoxyh es t od ins one or both iso Alkanes, C10-13-iso	irritati of data.	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin. ate: Rabbit No eye irritation OECD Test Guide nic hydrocarbor	deline 405	
48-9, Asses Resul Serio Not cl Produ Rema Comp tert-B Specia Resul Metho Conta 48-9, Rema	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>bonents:</u> utyl 2-ethylperoxyh es t od ins one or both iso Alkanes, C10-13-iso	paraffi	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin. ate: Rabbit No eye irritation OECD Test Guid nic hydrocarbor 68551-19-9): No eye irritation	sure may cause skin dryness or cracking. se irritation to the eyes, respiratory system	
48-9, Asses Resul Serio Not cl Produ Rema Comp tert-B Specia Resul Metho Conta 48-9, Rema Respi	Alkanes, C10-13-iso sment t us eye damage/eye assified due to lack o <u>ict:</u> rks <u>conents:</u> utyl 2-ethylperoxyh es t od nins one or both iso Alkanes, C10-13-iso rks	paraffi	68551-19-9): Repeated expose Repeated expose on Vapors may cau and the skin. ate: Rabbit No eye irritation OECD Test Guid nic hydrocarbor 68551-19-9): No eye irritation	deline 405	

according to the Hazardous Products Regulations



sion	Revision Date: 10/24/2024	SDS Number: 600000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
•	iratory sensitization assified due to lack o		
Produ	uct:		
Rema		: Causes sensitiz	zation.
<u>Com</u>	oonents:		
tert-B	utyl 2-ethylperoxyh	exanoate:	
Speci		: Guinea pig	
Metho		: OECD Test Gu	
Resul	t	: May cause sen	sitization by skin contact.
	ains one or both iso Alkanes, C10-13-iso		ns (Naphtha hydrotreated heavy CAS 647
Rema	ırks	: Did not cause s	sensitization on laboratory animals.
Germ	cell mutagenicity		
Not cl	assified due to lack o	f data.	
Com	oonents:		
		oveneete	
	autyl 2-ethylperoxyh toxicity in vitro	: Test Type: Bac	terial reverse mutation assay (AMES) Test Guideline 471
			itro mammalian cell gene mutation test Test Guideline 476
Geno	toxicity in vivo	: Species: Mouse Application Rou Method: OECD Result: negative	ute: Ingestion Test Guideline 474
	ains one or both iso Alkanes, C10-13-iso		ons (Naphtha hydrotreated heavy CAS 647
Germ	cell mutagenicity -	: Classified base	d on benzene content < 0.1% (Regulation (E nex VI, Part 3, Note P)
	nogenicity		
	assified due to lack o	f data.	
Not cl		f data.	
Not cl <u>Com</u> r	assified due to lack o		

according to the Hazardous Products Regulations



NOROX®410-50OMS

sion	Revision Date: 10/24/2024		S Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
	ains one or both isopa Alkanes, C10-13-iso C			ns (Naphtha hydrotreated heavy CAS 6474
Carcii ment	nogenicity - Assess-	:		d on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P)
Repro	oductive toxicity			
May o	damage fertility.			
<u>Com</u>	oonents:			
tert-E	Butyl 2-ethylperoxyhex	anoa	ite:	
Effect	s on fertility		test Species: Rat Application Rou General Toxicit	roduction/Developmental toxicity screening ite: Oral y Parent: NOEL: 300 mg/kg body weight Test Guideline 421
			Species: Rat Application Rou General Toxicit General Toxicit Fertility: NOAEI Early Embryoni weight	-generation reproduction toxicity study ite: Oral y Parent: NOAEL: 300 mg/kg body weight y F1: NOAEL: 300 mg/kg body weight _ Mating/Fertility: 100 mg/kg body weight c Development: NOAEL F2: 300 mg/kg body Test Guideline 443
Effect	s on fetal development		Developmental	
			Developmental	ite: Oral y Maternal: NOEL: 400 mg/kg body weight Toxicity: NOEL: 400 mg/kg body weight Test Guideline 414
Repro sessn	oductive toxicity - As- nent			of adverse effects on sexual function and on animal experiments.
	ains one or both isopa Alkanes, C10-13-iso C			ns (Naphtha hydrotreated heavy CAS 6474
	s on fetal development	:	Species: Rat Application Rou	ite: Oral NOAEL 1 000

Teratogenicity: NOAEL: 1,000 Method: OECD Test Guideline 414

according to the Hazardous Products Regulations





Version	Revision Date:	SDS N
4.2	10/24/2024	600000

DS Number:)0000000165 Date of last issue: 01/24/2022 Date of first issue: 03/15/2019

Remarks: Based on data from similar materials

STOT-single exposure

Not classified due to lack of data.

Components:

tert-Butyl 2-ethylperoxyhexanoate: Remarks : No data available

STOT-repeated exposure

Not classified due to lack of data.

Components:

tert-Butyl 2-ethylperoxyhexanoate:

Remarks : No data available

Repeated dose toxicity

Components:

tert-Butyl 2-ethylperoxyhexanoate:

Species NOAEL Exposure time Method	: : :	Rat, male 316 mg/kg 28 d OECD Test Guideline 407
Species NOAEL Exposure time Method	::	Rat, female 100 mg/kg 28 d OECD Test Guideline 407
Species NOAEL Method	: : :	Rat 450 mg/kg OECD Test Guideline 408

Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):

Species :	Rat
:	1000 mg/kg
NOAEL :	1,000 mg/kg
Application Route :	Oral
Exposure time :	4 wk
Remarks :	Based on data from similar materials

Aspiration toxicity

May be fatal if swallowed and enters airways.

according to the Hazardous Products Regulations



NOROX®410-50OMS

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019

Components:

Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):

May be fatal if swallowed and enters airways.

:

Experience with human exposure

Components:

Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):

Skin contact

Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

Further information

Product:

Remarks

: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

tert-Butyl 2-ethylperoxyhexanoate:

Toxicity to fish		LC50 (Oncorhynchus mykiss (rainbow trout)): 8.66 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
		NOEC (Poecilia reticulata (guppy)): 2.10 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 7.5 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): 0.44 mg/l Exposure time: 72 h Test Type: Growth inhibition Method: OECD Test Guideline 201 GLP: yes
		NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.018 mg/l Exposure time: 72 h Test Type: Growth inhibition

according to the Hazardous Products Regulations



rsion ?	Revision Date: 10/24/2024		DS Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
			Method: OECD T GLP: yes	est Guideline 201
M-Fac icity)	ctor (Acute aquatic tox-	:	1	
Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)			NOEC (Daphnia r Exposure time: 2 ⁷ Method: OECD T	
			LOEC (Daphnia n Exposure time: 27 Method: OECD T	
Toxici	ty to microorganisms	:	EC50: 64 mg/l Exposure time: 0. Method: OECD T	
Ecoto	oxicology Assessment			
Acute	aquatic toxicity	:	Very toxic to aqua	atic life.
Chron	nic aquatic toxicity	:	Toxic to aquatic li	fe with long lasting effects.
	ains one or both isopa Alkanes, C10-13-iso C			। (Naphtha hydrotreated heavy CAS 64742)
Toxici	ty to fish	:	LL50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): > 1,000 mg/l ን h
	ty to daphnia and other ic invertebrates	:	EL50 (Daphnia m Exposure time: 48	agna (Water flea)): > 1,000 mg/l 3 h
	ty to algae/aquatic	:	EL50 (Pseudokiro mg/l Exposure time: 72	hneriella subcapitata (green algae)): > 1,000 2 h
Toxici icity)	ty to fish (Chronic tox-	:	NOELR (Oncorhy Exposure time: 28	nchus mykiss (rainbow trout)): 316 mg/l 3 d
Persi	stence and degradabil	ity		
<u>Comp</u>	oonents:			
	a utyl 2-ethylperoxyhex a gradability	ano :	Theoretical oxyge Result: rapidly bio Biodegradation: (Exposure time: 28 Method: OECD T GLP: yes	degradable 65 %

according to the Hazardous Products Regulations



/ersion 1.2	Revision Date: 10/24/2024		DS Number: 0000000165	Date of last issue: 01/24/2022 Date of first issue: 03/15/2019
			this product is co	nsidered as being readily biodegradable.
	ains one or both isopa Alkanes, C10-13-iso (s (Naphtha hydrotreated heavy CAS 64742
Biode	egradability	:	Result: Readily b	iodegradable.
Bioa	ccumulative potential			
Com	ponents:			
tert-E	Butyl 2-ethylperoxyhe	xano	ate:	
Bioad	ccumulation	:	Bioconcentration Method: QSAR	factor (BCF): 202.4
	ains one or both isopa Alkanes, C10-13-iso (s (Naphtha hydrotreated heavy CAS 6474
	ion coefficient: n- ol/water	:	Pow: > 4	
Mobi	lity in soil			
No da	ata available			
Othe	r adverse effects			
<u>Prod</u>	uct:			
Addit matic	ional ecological infor- n	:	unprofessional ha	I hazard cannot be excluded in the event of andling or disposal. atic life. ife with long lasting effects.
ECTION	13. DISPOSAL CONS	IDEF	RATIONS	
Disp	osal methods			
-	e from residues	:	The product shou courses or the so	ate ponds, waterways or ditches with

Contaminated packaging :	Dispose of in accordance with local regulations. Clean container with water. Dispose of contents/ container to an approved waste disposal plant. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
--------------------------	---

according to the Hazardous Products Regulations



NOROX®410-500MS

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG UN number Proper shipping name	-	UN 3117 ORGANIC PEROXIDE TYPE E, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXY-2-ETHYLHEXANOATE)
Class	:	5.2
Packing group	:	Not assigned by regulation
Labels Environmentally hazardous	÷	5.2 yes
IATA-DGR Not permitted for transport		
IMDG-Code		
UN number	-	UN 3117
Proper shipping name	:	ORGANIC PEROXIDE TYPE E, LIQUID, TEMPERATURE CONTROLLED
		(tert-BUTYL PEROXY-2-ETHYLHEXANOATE)
Class	:	5.2
Packing group	:	Not assigned by regulation
Labels	:	5.2
EmS Code	:	F-F, S-R
Marine pollutant	:	yes
Transport in bulk according	* *~	Appar II of MARROL 72/78 and the IRC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG		
UN number	:	UN 3117
Proper shipping name	:	ORGANIC PEROXIDE TYPE E, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXY-2-ETHYLHEXANOATE)
Class	:	5.2
Packing group	:	II
Labels	:	5.2
ERG Code	:	148
Marine pollutant	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Additional advice

Temperature controlled transport.: Control temperature : 30 °C

according to the Hazardous Products Regulations





Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022	
4.2	10/24/2024	600000000165	Date of first issue: 03/15/2019	

Emergency temperature : 35 °C

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals	:	This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA: Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9) Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9)		
The ingredients of this product are reported in the following inventories:				
TSCA (US)	:	All substances listed as active on the TSCA inventory		
AIIC (AU)	:	On the inventory, or in compliance with the inventory		
DSL (CA)	:	All components of this product are on the Canadian DSL		
ENCS (JP)	:	On the inventory, or in compliance with the inventory		
ISHL (JP)	:	On the inventory, or in compliance with the inventory		
KECI (KR)	:	On the inventory, or in compliance with the inventory		
PICCS (PH)	:	On the inventory, or in compliance with the inventory		
IECSC (CN)	:	On the inventory, or in compliance with the inventory		

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under
		the Occupational Health and Safety Act.
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with

according to the Hazardous Products Regulations



NOROX[®]410-500MS

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2022
4.2	10/24/2024	60000000165	Date of first issue: 03/15/2019

x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/

Revision Date	:	10/24/2024
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / Z8