NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

SECTION 1. IDENTIFICATION

Trade name : NOROX[®]500-90-AL3

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street

Elyria OH 44035 USA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300

CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person

responsible for the SDS

cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : polymerization initiators

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

Organic peroxides : Type C

Aspiration hazard : Category 1

Long-term (chronic) aquatic

hazard

Category 4

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H227 Combustible liquid.

H242 Heating may cause a fire.

H304 May be fatal if swallowed and enters airways.

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

H413 May cause long lasting harmful effects to aquatic life.

Precautionary Statements

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible

materials.

P234 Keep only in original container.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < 30 °C/ <

86 °F. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organic Peroxide

Liquid mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
di-tert-butyl 3,3,5-	6731-36-8	>= 85 - < 90
trimethylcyclohexylidene diperoxide		
Naphta (Petroleum), hydrotreated	64742-48-9	>= 10 - < 15
heavy (Hydrocarbons, C11-C12,		
isoalkanes, <2% aromatics)		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later. No artificial respiration, mouth-to-mouth or mouth to nose. Use

suitable instruments/apparatus. Call a physician immediately.

If inhaled : Call a physician or poison control center immediately.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.
Call a physician immediately.
Contact a poison control center.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-: tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Follow safe handling advice and personal protective

equipment recommendations.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

iet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse.

Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Keep away from heat and sources of ignition.

Use only explosion-proof equipment. Keep away from combustible material.

Advice on safe handling : Do not swallow.

Do not breathe vapors/dust. Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

Recommended storage tem- : < 30 °C

perature

< 86 °F

Further information on stor-

age stability

No decomposition if stored normally.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromatics)	64742-48-9	TWA (Vapor)	171 ppm 1,200 mg/m3 (total hydrocar- bons)	Supplier data
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Engineering measures Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection In the case of dust or aerosol formation use respirator with an

approved filter.

ABEK-filter Filter type

Hand protection

Material Nitrile rubber Break through time 480 min Glove thickness 0.5 mm

Remarks Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous

substance and specific to place of work.

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

potential.

Hygiene measures : Keep away from food and drink.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : musty

Odor Threshold : No data available

pH : No data available

Melting point/range : < -25 °C

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : 72 °C

Method: closed cup

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Density : 0.892 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

log Pow: 7.0 (25 °C)

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Self-Accelerating decomposi-

tion temperature (SADT)

60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : 17.3 mPa.s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

Refractive index : 1.438 (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromatically

ics):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 8 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Method : OECD Test Guideline 404

Result : Mild skin irritation

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

and the skin.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Remarks : No data available

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Result: negative

Genotoxicity in vivo : Remarks: No data available

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromatical):

ics):

Germ cell mutagenicity -

Animal testing did not show any mutagenic effects.

Assessment

Carcinogenicity

Not classified based on available information.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Species : Mouse Application Route : Oral Result : negative

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Carcinogenicity - Assess-

: Animal testing did not show any carcinogenic effects.

ment

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Effects on fertility : Remarks: No data available

Effects on fetal development : Species: Rat

Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 414

STOT-single exposure

Not classified based on available information.

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromatics):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Solvents may degrease the skin.

Components:

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 0.043 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.11

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0128 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility.

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Toxicity to fish : LC0 (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC0 (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC0 (Pseudokirchneriella subcapitata (green algae)): 1,000

mg/l

Exposure time: 72 h

NOELR (Pseudokirchneriella subcapitata (green algae)):

1,000 mg/l

Exposure time: 72 h

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): >= 1 mg/l

Exposure time: 21 d

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Remarks: Information given is based on data on the ingredi-

ents and the ecotoxicology of similar products.

Persistence and degradability

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

Biodegradability : Result: Biodegradable

Method: OECD Test Guideline 301D

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Biodegradability : Result: rapidly biodegradable

Bioaccumulative potential

Components:

di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide:

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

Bioaccumulation : Bioconcentration factor (BCF): 443

Partition coefficient: n-

octanol/water

log Pow: 6.53

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

ics):

Partition coefficient: n-

octanol/water

Remarks: No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

May cause long lasting harmful effects to aquatic life.

Components:

Naphta (Petroleum), hydrotreated heavy (Hydrocarbons, C11-C12, isoalkanes, <2% aromat-

cs):

Additional ecological infor-

mation

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Dispose of in accordance with local regulations.

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3103

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID

(1,1-DI-(tert-BUTYLPEROXY)-3,3,5-

TRIMETHYLCY CLOHE XANE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

IATA-DGR

UN/ID No. : UN 3103

Proper shipping name : Organic peroxide type C, liquid

(1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen- :

ger aircraft)

570

IMDG-Code

UN number : UN 3103

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID

(1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2
EmS Code : F-J, S-R
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3103

Proper shipping name : Organic peroxide type C, liquid

(1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane, <=90%)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 146 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Organic peroxides Aspiration hazard

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311. Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

Maine Chemicals of High Concern

This product does not contain any chemicals that are listed as Maine Chemicals of High Concern.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

International Regulations

Gefahrgruppe nach DGUV 13 Vorschrift 13 (bisher BGV B4): lb, S+ (German regulatory requirements)

NOROX®500-90-AL3



Version Revision Date: SDS Number: Date of last issue: 09/05/2019 1.2 06/24/2021 600000000760 Date of first issue: 07/02/2018

Produkt unterliegt dem Sprengstoffgesetz (SprengG; Stoffgruppe C). (German regulatory requirements)

The ingredients of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AICS (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/24/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

Full text of other abbreviations

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

NOROX®500-90-AL3



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2019

 1.2
 06/24/2021
 600000000760
 Date of first issue: 07/02/2018

OSHA P0 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG -Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL -No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8