# NOROX®757



Version Revision Date: SDS Number: Date of last issue: 02/18/2022 2.0 07/28/2023 600000000155 Date of first issue: 02/20/2019

### **SECTION 1. IDENTIFICATION**

Trade name : NOROX<sup>®</sup>757

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street

Elyria OH 44035 USA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300

CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person

responsible for the SDS

cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : polymerization initiators

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1B

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 1B

Reproductive toxicity : Category 1B

Specific target organ toxicity:

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity : Category 2

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

- repeated exposure

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 3

#### **GHS** label elements

Hazard pictograms









Signal Word : Danger

Hazard Statements : H227 Combustible liquid.

H242 Heating may cause a fire. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or

repeated exposure. H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible

materials.

P234 Keep only in original container. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

# NOROX®757



Date of last issue: 02/18/2022 Version Revision Date: SDS Number: 07/28/2023 60000000155 Date of first issue: 02/20/2019 2.0

> P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

# Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up. P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < 100 °F/ < 38 °C. Keep cool.

P420 Store away from other materials.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Chemical nature Organic Peroxide

Liquid mixture

#### Components

-		
Chemical name	CAS-No.	Concentration (% w/w)
N-Methyl-2-pyrrolidone	872-50-4	>= 30 - < 35
2,4-Pentanedione, peroxide	37187-22-7	>= 20 - < 25
Cumene hydroperoxide	80-15-9	>= 10 - < 15

# NOROX<sup>®</sup>757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Cumene	98-82-8	>= 1 - < 5

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

If inhaled : Administer oxygen if breathing is difficult or cyanosis is

observed.

Call a physician immediately.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Respiratory tract burning possible if aerosols are inhaled. Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : If symptoms persist, call a physician.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with

difficulty.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

# NOROX®757



Version 2.0

Revision Date: 07/28/2023

SDS Number: 600000000155

Date of last issue: 02/18/2022 Date of first issue: 02/20/2019

Rinse mouth thoroughly with water.

Keep respiratory tract clear. Do NOT induce vomiting.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

May cause cancer.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapors may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

so.

Use water spray to cool unopened containers.

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec-: tive equipment and emergency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

iet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

# NOROX®757



Version 2.0

Revision Date: 07/28/2023

SDS Number: 600000000155

Date of last issue: 02/18/2022 Date of first issue: 02/20/2019

#### CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors). Keep away from heat and sources of ignition.

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from combustible material.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling

Open drum carefully as content may be under pressure.

Protect from contamination.

Do not swallow.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem-

perature

< 100 °F

# NOROX<sup>®</sup>757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

< 38 °C

Further information on stor-

age stability

: No decomposition if stored normally.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N-Methyl-2-pyrrolidone	872-50-4	TWA	15 ppm 60 mg/m3	US WEEL
		STEL	30 ppm 120 mg/m3	US WEEL
Cumene hydroperoxide	80-15-9	TWA	1 ppm	US WEEL
Cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
N-Methyl-2-pyrrolidone	872-50-4	5-Hydroxy- N-methyl-2- pyrrolidone	Urine	End of shift (As soon as possible after exposure ceases)	100 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Use NIOSH approved respiratory protection.

Hand protection

Material : butyl-rubber Break through time : 480 min

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Glove thickness : 0.5 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the

hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Ensure that eyewash stations and safety showers are close

to the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets,

disposable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : light yellow

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Odor : slight

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : 93 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : > 1

Density : 1.1 - 1.2 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

Self-Accelerating decomposi-

tion temperature (SADT)

50 °C SADT-Self Accelerating Decomposition Temperature. Lowest

temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Organic peroxide

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

No decomposition if stored normally.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Acute toxicity

Harmful if swallowed.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 1,783 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 25 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Components:** 

N-Methyl-2-pyrrolidone:

Acute oral toxicity : LD50 (Rat): 4,150 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: No mortality observed at this dose.

2,4-Pentanedione, peroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): > 13.1 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist Method: Expert judgment

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: Expert judgment

Assessment: The substance or mixture has no acute dermal

toxicity

Cumene hydroperoxide:

Acute oral toxicity : LD50 Oral (Rat): 382 mg/kg

Acute inhalation toxicity : LC50: 1.370 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50: 1,200 - 1,520 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.

Cumene:

Acute oral toxicity : LD50 (Rat): 2,260 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Skin corrosion/irritation

Causes severe burns.

**Product:** 

Remarks : Extremely corrosive and destructive to tissue.

**Components:** 

N-Methyl-2-pyrrolidone:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Irritating to skin.

2,4-Pentanedione, peroxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Cumene hydroperoxide:

Species : Rabbit

Result : Causes burns.

Remarks : Extremely corrosive and destructive to tissue.

Cumene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

**Product:** 

Remarks : May cause irreversible eye damage.

Components:

N-Methyl-2-pyrrolidone:

Species : Rabbit
Result : Eye irritation

Method : OECD Test Guideline 405

2,4-Pentanedione, peroxide:

Species : Rabbit Result : Eye irritation

Method : OECD Test Guideline 405

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Cumene hydroperoxide:

Species : Rabbit Result : Corrosive

Remarks : May cause irreversible eye damage.

Cumene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

**Components:** 

N-Methyl-2-pyrrolidone:

Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitization.
Remarks : Based on data from similar materials

2,4-Pentanedione, peroxide:

Test Type : Maximization Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Probability or evidence of skin sensitization in humans

Remarks : Causes sensitization.

**Cumene hydroperoxide:** 

Result : Does not cause skin sensitization.

Cumene:

Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

# Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

2,4-Pentanedione, peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Cumene hydroperoxide:

Genotoxicity in vitro : Test Type: in vitro test

Test system: Salmonella typhimurium

Result: positive

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Application Route: Skin contact

Result: negative

Cumene:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Method: OECD Test Guideline 482

Result: negative

Test Type: Ames test

Result: positive

Genotoxicity in vivo : Species: Rat

Application Route: Intraperitoneal

Exposure time: 72 h

Method: OECD Test Guideline 474

Result: Equivocal

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Species: Mouse

Application Route: inhalation (gas)

Exposure time: 14 w

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

May cause cancer.

**Components:** 

2,4-Pentanedione, peroxide:

Remarks : This information is not available.

Cumene hydroperoxide:

Remarks : This information is not available.

Cumene:

Species : Rat, male and female
Application Route : inhalation (vapor)
Result : carcinogenic effects

Species : Mouse, male and female

Application Route : inhalation (vapor)
Result : carcinogenic effects

Carcinogenicity - Assess-

ment

IARC Group 2B: Possibly carcinogenic to humans

Cumene 98-82-8

Sufficient evidence of carcinogenicity in animal experiments

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

Cumene 98-82-8

Reproductive toxicity

May damage fertility or the unborn child.

**Components:** 

N-Methyl-2-pyrrolidone:

Reproductive toxicity - As- : Clear evidence of adverse effects on sexual function and

sessment fertility, and/or on development, based on animal experiments

2,4-Pentanedione, peroxide:

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

**Cumene hydroperoxide:** 

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

Cumene:

Effects on fetal development : Species: Rabbit

Application Route: inhalation (vapor) General Toxicity Maternal: LOAEL: 500 Developmental Toxicity: NOAEL: 2,300 Method: OECD Test Guideline 414

STOT-single exposure

May cause respiratory irritation.

**Components:** 

N-Methyl-2-pyrrolidone:

Assessment : May cause respiratory irritation.

Cumene:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Components:** 

Cumene hydroperoxide:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

**Components:** 

N-Methyl-2-pyrrolidone:

 Species
 : Rat

 NOAEL
 : 0.5 mg/l

 LOAEL
 : 1 mg/l

Application Route : inhalation (vapor)

Exposure time : 90 d

Method : OECD Test Guideline 413

Species : Rat

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

NOAEL : 3,000 mg/kg LOAEL : 7,500 mg/kg Application Route : Ingestion

Exposure time : 90 d

Method : OECD Test Guideline 408

Species : Rat

NOAEL : 6,000 mg/kg LOAEL : 18,000 mg/kg Application Route : oral (feed)

Exposure time : 28 d

Method : OECD Test Guideline 407

Species : Rabbit
NOAEL : 826 mg/kg
Application Route : Skin contact

Exposure time : 20 d

Method : OECD Test Guideline 410

Cumene hydroperoxide:

Species : Rat
NOAEC : 31 mg/m³
Application Route : inhalation (gas)

Exposure time : 90 d

Cumene:

Species : Rat

NOAEL : 154 mg/kg

Application Route : Oral

Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

**Components:** 

Cumene:

May be fatal if swallowed and enters airways.

**Further information** 

Product:

Remarks : No data available

**Components:** 

2,4-Pentanedione, peroxide:

Remarks : No data available

# NOROX®757



Version Revision Date: SDS Number: Date of last issue: 02/18/2022 2.0 07/28/2023 600000000155 Date of first issue: 02/20/2019

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### **Components:**

N-Methyl-2-pyrrolidone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 24 h Method: DIN 38412

EC50 (Palaeomonetes wilgaris (Grass shrimp)): 1,107 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 125 mg/l

Exposure time: 72 h

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 12.5 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

LOEC (Daphnia magna (Water flea)): 25 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 600 mg/l

Exposure time: 0.5 h Method: ISO 8192

2,4-Pentanedione, peroxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 67.6 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 7.05 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5.36

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: 614 mg/l

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Exposure time: 3 h

Method: OECD Test Guideline 209

Cumene hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 18.8 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 3.1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 50 mg/l

End point: Growth rate Exposure time: 16 h

Cumene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.8 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.14 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 2.01 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.35 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 2,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Persistence and degradability

**Components:** 

N-Methyl-2-pyrrolidone:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301C

2,4-Pentanedione, peroxide:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Cumene hydroperoxide:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301B

Cumene:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

**Components:** 

N-Methyl-2-pyrrolidone:

Partition coefficient: n-

octanol/water

log Pow: -0.46 (25 °C / 25 °C)

2,4-Pentanedione, peroxide:

Partition coefficient: n- : log Pow: 1.1 (25 °C / 25 °C)

octanol/water Method: OECD Test Guideline 117

Cumene hydroperoxide:

Partition coefficient: n- : log Pow: 1.6

octanol/water

Cumene:

Bioaccumulation : Bioconcentration factor (BCF): 94.69

Remarks: Calculation

Partition coefficient: n-

octanol/water

: log Pow: 3.55 (23 °C / 23 °C)

Mobility in soil
No data available

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

#### Other adverse effects

**Product:** 

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

## **Components:**

2,4-Pentanedione, peroxide:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

# **International Regulations**

**UNRTDG** 

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE, CUMYL

HYDROPEROXIDE)

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

**IATA-DGR** 

UN/ID No. : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Acetyl acetone peroxide, Cumyl hydroperoxide)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen-

ger aircraft)

570

**IMDG-Code** 

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE, CUMYL

HYDROPEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Acetyl Acetone Peroxide, <=20%, Cumyl Hydroperoxide,

<=12%)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 145 Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
------------	---------	--------------	-----------------------

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

		(lbs)	(lbs)
Cumene hydroperoxide	80-15-9	10	83

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Organic peroxides

Acute toxicity (any route of exposure) Respiratory or skin sensitization

Carcinogenicity
Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

N-Methyl-2- 872-50-4

pyrrolidone

Cumene hydrop- 80-15-9

eroxide

Cumene 98-82-8

#### **Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Cumene 98-82-8

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Cumene hydroperoxide 80-15-9 Cumene 98-82-8

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311. Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

# NOROX<sup>®</sup>757



Version Revision Date: SDS Number: Date of last issue: 02/18/2022 2.0 07/28/2023 60000000155 Date of first issue: 02/20/2019

### California Prop. 65

WARNING: This product can expose you to chemicals including Cumene, which is/are known to the State of California to cause cancer, and

N-Methyl-2-pyrrolidone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **International Regulations**

#### The ingredients of this product are reported in the following inventories:

On the inventory, or in compliance with the inventory TCSI (TW)

TSCA (US) All substances listed as active on the TSCA inventory

: On the inventory, or in compliance with the inventory AIIC (AU)

All components of this product are on the Canadian DSL DSL (CA)

ENCS (JP) On the inventory, or in compliance with the inventory

ISHL (JP) On the inventory, or in compliance with the inventory

KECI (KR) On the inventory, or in compliance with the inventory

PICCS (PH) On the inventory, or in compliance with the inventory

IECSC (CN) On the inventory, or in compliance with the inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements: N-Methyl-2-pyrrolidone 872-50-4

# **SECTION 16. OTHER INFORMATION**

#### **Further information**

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

compile the Material Safety

Data Sheet

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 07/28/2023

# NOROX®757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

US WEEL / STEL : Short-Term TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

# NOROX<sup>®</sup>757



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/18/2022

 2.0
 07/28/2023
 600000000155
 Date of first issue: 02/20/2019

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8