

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX®KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NOROX®KP-200

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH
Dr.-Gustav-Adolph-Str. 3
82049 Pullach

Telephone : +49 / 89 / 74422 – 0

E-mail address of person
responsible for the SDS : contact@united-in.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Organic peroxides, Type D	H242: Heating may cause a fire.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.

2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)**

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

Hazard pictograms :



Signal word : Danger

Hazard statements : H242 Heating may cause a fire.
H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Hazardous components which must be listed on the label:

2-Butanone, peroxide (CAS-No. 1338-23-4)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide
Liquid mixture

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-Butanone, peroxide	1338-23-4 700-954-4 01-2119514691-43-0000	Org. Perox. D; H242 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 30 - < 35
Ethylene glycol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 5 - < 7.5
hydrogen peroxide	7722-84-1 231-765-0 008-003-00-9 01-2119485845-22	Ox. Liq. 1; H271 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412	>= 3 - < 5

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

		>= 63 %	
Substances with a workplace exposure limit :			
dimethyl phthalate	131-11-3 205-011-6 01-2119437229-36		>= 55 - < 65

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Take off contaminated clothing and shoes immediately.
Call a physician immediately.
Never give anything by mouth to an unconscious person.
If unconscious, place in recovery position and seek medical advice.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Administer oxygen if breathing is difficult or cyanosis is observed.
Call a physician immediately.
If breathed in, move person into fresh air.
If not breathing, give artificial respiration.
Respiratory tract burning possible if aerosols are inhaled.
Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
- In case of skin contact : If symptoms persist, call a physician.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.
Rinse mouth thoroughly with water.
Keep respiratory tract clear.
Do NOT induce vomiting.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed or if inhaled.
Causes serious eye damage.
Causes severe burns.

Harmful if swallowed or if inhaled.
Causes serious eye damage.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Risk of explosion if heated under confinement.
Possible emission of gaseous decomposition products may lead to a dangerous pressure build-up.
Avoid confinement.
Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

The product burns violently.
Flash back possible over considerable distance.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours may form explosive mixtures with air.
The product will float on water and can be reignited on surface water.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
- Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Use personal protective equipment.
Remove all sources of ignition.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Open drum carefully as content may be under pressure.
Protect from contamination.
Do not swallow.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material. Do not spray on a naked flame or any incandescent material.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

Hygiene measures : Avoid contact with skin, eyes and clothing. Keep away from food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in cool place. Keep in a well-ventilated place. Contamination may result in dangerous pressure increases - closed containers may rupture. Observe label precautions. Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from combustible materials. Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 30 °C

Further information on storage stability : Stable under recommended storage conditions.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m ³	GB EH40
		STEL	10 mg/m ³	GB EH40
2-Butanone, peroxide	1338-23-4	STEL	0.2 ppm 1.5 mg/m ³	GB EH40
Ethylene glycol	107-21-1	TWA (particles)	10 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

		TWA (Vapour)	20 ppm 52 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL (Vapour)	40 ppm 104 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 52 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	40 ppm 104 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	GB EH40
		STEL	2 ppm 2.8 mg/m ³	GB EH40

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl phthalate	Workers	Inhalation	Long-term systemic effects	66.1 mg/m ³
	Workers	Skin contact	Long-term systemic effects	135 mg/kg bw/day
2-Butanone, peroxide	Workers	Inhalation	Long-term systemic effects	2.35 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1.33 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	7.05 mg/m ³
Ethylene glycol	Workers	Inhalation	Long-term systemic effects	35 mg/m ³
	Workers	Skin contact	Long-term systemic effects	106 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	53 mg/kg bw/day
hydrogen peroxide	Workers	Inhalation	Acute local effects	3 mg/m ³
	Workers	Inhalation	Long-term local effects	1.4 mg/m ³

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

dimethyl phthalate	Fresh water	0.192 mg/l
	Marine water	0.0192 mg/l
	Sewage treatment plant	4 mg/l
	Fresh water sediment	1.3 mg/kg dry weight (d.w.)
	Soil	3.16 mg/kg dry weight (d.w.)
2-Butanone, peroxide	Marine sediment	0.13 mg/kg dry weight (d.w.)
	Fresh water	0.0056 mg/l
	Marine water	0.00056 mg/l
	Intermittent use/release	0.056 mg/l
	Sewage treatment plant	1.2 mg/l
Ethylene glycol	Fresh water sediment	0.0876 mg/kg
	Marine sediment	0.00876 mg/kg
	Soil	0.0142 mg/kg
	Fresh water	10 mg/l
	Marine water	1 mg/l
hydrogen peroxide	Intermittent use/release	10 mg/l
	Sewage treatment plant	199.5 mg/l
	Fresh water sediment	20.9 mg/kg
	Soil	1.53 mg/kg
	Sewage treatment plant	4.66 mg/l
	Fresh water	0.0126 mg/l
	Marine sediment	0.047 mg/l
	Fresh water sediment	0.047 mg/l
	Marine water	0.0126 mg/l
	Soil	0.0023 mg/l

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.

Hand protection

Material : Nitrile rubber
Break through time : < 30 min
Glove thickness : 0.40 mm

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.47 mm

Remarks : The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.
Wear as appropriate:
Flame retardant antistatic protective clothing.

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless, clear
Odour : mint-like
Odour Threshold : not determined
pH : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Melting point/ range	:	No data available
Boiling point/boiling range	:	Decomposition: Decomposes below the boiling point.
Flash point	:	> 65 °C Method: ISO 3679, closed cup
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	Upper explosion limit not determined
Lower explosion limit / Lower flammability limit	:	Lower explosion limit not determined
Vapour pressure	:	No data available
Relative vapour density	:	not determined
Relative density	:	not determined
Density	:	1.12 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	slightly soluble
Solubility in other solvents	:	soluble Solvent: Phthalates
Partition coefficient: n-octanol/water	:	Pow: 1.54 (25 °C) (for a component of this mixture)
Viscosity		
Viscosity, dynamic	:	18 - 22 mPa.s
Viscosity, kinematic	:	not determined
Explosive properties	:	Not explosive In use, may form flammable/explosive vapour-air mixture.
Oxidizing properties	:	The substance or mixture is not classified as oxidizing. Organic peroxide

9.2 Other information

Self-Accelerating decomposition temperature (SADT)	:	60 °C Method: UN-Test H.4 SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
--	---	--

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Flammability (liquids) : Flammable liquid, Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

Self-ignition : The substance or mixture is not classified as pyrophoric.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
Heating may cause a fire or explosion.

10.2 Chemical stability

Stable under recommended storage conditions.
No decomposition if stored normally.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from contamination.
Contact with incompatible substances can cause decomposition at or below SADT.
Heat, flames and sparks.
Avoid confinement.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,126 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
Method: Expert judgement

Ethylene glycol:

Acute inhalation toxicity : LC50 (Rat): > 2.5 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Mouse): > 3,500 mg/kg

hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male and female): 431 mg/kg
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 9,200 mg/kg
Remarks: No adverse effect has been observed in acute toxicity tests.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

2-Butanone, peroxide:

Species : Rabbit
Result : Causes burns.

Ethylene glycol:

Species : Rabbit
Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

hydrogen peroxide:

Result : Corrosive after 3 minutes or less of exposure

dimethyl phthalate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-Butanone, peroxide:

Result : Irreversible effects on the eye

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Ethylene glycol:

Species : Rabbit
Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

hydrogen peroxide:

Result : Irreversible effects on the eye
Remarks : hydrogen peroxide, 35%

dimethyl phthalate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

2-Butanone, peroxide:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Assessment : Harmful if swallowed., Harmful if inhaled.

Ethylene glycol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

dimethyl phthalate:

Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX®KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

Method: OECD Test Guideline 471
Result: negative

Method: OECD Test Guideline 476
Result: negative

Ethylene glycol:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Chromosomal aberration
Species: Rat
Application Route: Oral
Result: negative

hydrogen peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
positive
Remarks: Information taken from reference works and the literature.

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive
Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse (male and female)
Method: OECD Test Guideline 474
Result: negative
Remarks: hydrogen peroxide, 35%

Germ cell mutagenicity- Assessment : Based on available data, the classification criteria are not met.

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Result: negative

Method: OECD Test Guideline 473
Result: negative

Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration
Species: Rat
Application Route: Intraperitoneal
Result: negative

Test Type: Micronucleus test
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

2-Butanone, peroxide:

Remarks : This information is not available.

Ethylene glycol:

Species : Mouse
Application Route : oral (feed)
Exposure time : 2 Years
NOAEL : 1,500 mg/kg bw/day

Species : Rat
Application Route : oral (feed)
NOAEL : 1,000 mg/kg food

hydrogen peroxide:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

dimethyl phthalate:

Species : Rat
Application Route : Skin contact
Method : OECD Test Guideline 451
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Reproductive toxicity

Not classified due to lack of data.

Components:

2-Butanone, peroxide:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

Ethylene glycol:

Effects on fertility : Species: Mouse
Application Route: oral (drinking water)
General Toxicity - Parent: NOAEL: 1,000 mg/kg body weight
General Toxicity F1: NOAEL: 1,000 mg/kg body weight

Effects on foetal development

: Species: Rabbit
Application Route: oral (gavage)
Duration of Single Treatment: 30 d
General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight
Developmental Toxicity: NOAEL: 2,000 mg/kg body weight

Species: Rat
Application Route: oral (gavage)
Duration of Single Treatment: 21 d
General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight
Developmental Toxicity: NOAEL: 500 mg/kg body weight

Species: Rat
Application Route: oral (gavage)
Duration of Single Treatment: 24 d
General Toxicity Maternal: NOAEL: 250 mg/kg body weight
Developmental Toxicity: NOAEL: 250 mg/kg body weight

Species: Mouse
Application Route: oral (gavage)
Duration of Single Treatment: 18 d
General Toxicity Maternal: NOAEL: 1,500 mg/kg body weight
Developmental Toxicity: NOAEL: 150 mg/kg body weight

Species: Mouse
Application Route: Dermal
Duration of Single Treatment: 18 d
General Toxicity Maternal: NOAEL: 3,549 mg/kg body weight
Developmental Toxicity: NOAEL: 3,549 mg/kg body weight

hydrogen peroxide:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Reproductive toxicity - Assessment : No data available

dimethyl phthalate:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
Method: OECD Test Guideline 440
Result: negative

Effects on foetal development : Species: Rat
Application Route: Ingestion
General Toxicity Maternal: NOAEL: 840 mg/kg body weight
Developmental Toxicity: NOAEL: 3,570 mg/kg body weight
Method: OECD Test Guideline 414

STOT - single exposure

Not classified due to lack of data.

Components:

hydrogen peroxide:

Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified due to lack of data.

Components:

Ethylene glycol:

Exposure routes : Oral
Target Organs : Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

hydrogen peroxide:

Remarks : No data available

Repeated dose toxicity

Components:

2-Butanone, peroxide:

Species : Rat
NOAEL : 200 mg/kg
Application Route : oral (gavage)
Exposure time : 28 d
Method : OECD Test Guideline 407

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Ethylene glycol:

Species : Rat
NOAEL : 150 mg/kg
Application Route : oral (feed)
Exposure time : 1 y
Method : OECD Test Guideline 452

Species : Dog
NOAEL : > 4,000 mg/kg
Application Route : Skin contact
Exposure time : 4 w
Method : OECD Test Guideline 410

hydrogen peroxide:

Species : Mouse, female
NOAEL : 37 mg/kg
Application Route : oral (drinking water)
Exposure time : 90 d
Remarks : hydrogen peroxide, 35%

Species : Mouse, males
NOAEL : 26 mg/kg
Application Route : oral (drinking water)
Exposure time : 90
Remarks : hydrogen peroxide, 35%

dimethyl phthalate:

Species : Rat
NOAEL : 770 mg/kg
Application Route : Oral
Exposure time : 16 w
Method : OECD Test Guideline 408

Aspiration toxicity

Not classified due to lack of data.

Components:

hydrogen peroxide:

Based on available data, the classification criteria are not met.

dimethyl phthalate:

No aspiration toxicity classification

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Further information

Product:

Remarks : No data available

Components:

Ethylene glycol:

Remarks : No data available

dimethyl phthalate:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version 1.2 Revision Date: 08.11.2024 SDS Number: 600000000308 Date of last issue: 06.03.2023
Date of first issue: 24.06.2022

Ethylene glycol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 72,860 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 5,000 mg/l
Exposure time: 96 h
- Toxicity to fish (Chronic toxicity) : NOEC: 15,380 mg/l
Exposure time: 7 d
Species: Pimephales promelas (fathead minnow)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 8,590 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

hydrogen peroxide:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia pulex (Water flea)): 2.4 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l
Exposure time: 72 h
- NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.63 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

dimethyl phthalate:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 52 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX®KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l Exposure time: 72 h
Toxicity to microorganisms	:	EC50 : 4,100 mg/l Exposure time: 0.5 h Method: OECD Test Guideline 209
Toxicity to fish (Chronic toxicity)	:	NOEC: 11 mg/l Exposure time: 102 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210 LOEC: 24 mg/l Exposure time: 102 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 9.6 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) LOEC: 23 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Ethylene glycol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301A

hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

dimethyl phthalate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301E

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

12.3 Bioaccumulative potential

Components:

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C)

Ethylene glycol:

Partition coefficient: n-octanol/water : log Pow: -1.36

hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57 (20 °C)
Remarks: Information refers to the main component.
Calculation

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 1.54

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Components:

Ethylene glycol:

Additional ecological information : No data available

dimethyl phthalate:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | |
|------------------------|--|
| Product | : Dispose of wastes in an approved waste disposal facility.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container. |
| Contaminated packaging | : Dispose of in accordance with local regulations.
Clean container with water.
Dispose of contents/ container to an approved waste disposal plant.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14: Transport information

14.1 UN number

- | | |
|------|-----------|
| ADR | : UN 3105 |
| RID | : UN 3105 |
| IMDG | : UN 3105 |
| IATA | : UN 3105 |

14.2 UN proper shipping name

- | | |
|------|--|
| ADR | : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S)) |
| RID | : ORGANIC PEROXIDE TYPE D, LIQUID
(METHYL ETHYL KETONE PEROXIDE(S)) |
| IMDG | : ORGANIC PEROXIDE TYPE D, LIQUID |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

IATA : (METHYL ETHYL KETONE PEROXIDE(S))
Organic peroxide type D, liquid
(Methyl ethyl ketone peroxide(s))

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 5.2	
RID	: 5.2	
IMDG	: 5.2	
IATA	: 5.2	HEAT

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : P1
Hazard Identification Number : 539
Labels : 5.2

IMDG
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R

IATA (Cargo)
Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)
Packing instruction (passenger aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADR
Environmentally hazardous : no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	hydrogen peroxide
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

The components of this product are reported in the following inventories:

TCSI (TW)	:	On the inventory, or in compliance with the inventory
TSCA (US)	:	All substances listed as active on the TSCA inventory
AiIC (AU)	:	All components are listed on the inventory, regulatory obligations/restrictions apply
DSL (CA)	:	All components of this product are on the Canadian DSL
ENCS (JP)	:	On the inventory, or in compliance with the inventory
ISHL (JP)	:	On the inventory, or in compliance with the inventory
KECI (KR)	:	On the inventory, or in compliance with the inventory
PICCS (PH)	:	On the inventory, or in compliance with the inventory
IECSC (CN)	:	On the inventory, or in compliance with the inventory
TECI (TH)	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H242	:	Heating may cause a fire.
H271	:	May cause fire or explosion; strong oxidizer.
H302	:	Harmful if swallowed.
H314	:	Causes severe skin burns and eye damage.
H318	:	Causes serious eye damage.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure if swallowed.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Org. Perox.	:	Organic peroxides
Ox. Liq.	:	Oxidizing liquids
Skin Corr.	:	Skin corrosion
STOT RE	:	Specific target organ toxicity - repeated exposure

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX® KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
These safety instructions also apply to empty packaging which may still contain product residues.
The hazards on the label also apply to residues in the container.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



NOROX®KP-200

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
1.2	08.11.2024	600000000308	Date of first issue: 24.06.2022

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Org. Perox. D	H242
Acute Tox. 4	H302
Acute Tox. 4	H332
Skin Corr. 1B	H314
Eye Dam. 1	H318

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN