NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NOROX®MEKP-925H

Manufacturer or supplier's details

Company : United Initiators GmbH

Address : Dr.-Gustav-Adolph-Str. 3

82049 Pullach

Telephone : +49 / 89 / 74422 - 0

Emergency telephone number : +49 / 89 / 74422 - 0 (24 h)

E-mail address : contact@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

Flammable liquid

GHS Classification

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irri-

tation

Category 1

Reproductive toxicity : Category 2

Short-term (acute) aquatic

hazard

Category 2

GHS label elements

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Hazard pictograms









Signal word : Danger

Hazard statements : H227 Combustible liquid.

H242 Heating may cause a fire.

H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.

H361 Suspected of damaging fertility or the unborn child.

H401 Toxic to aquatic life.

Precautionary statements : Prevention:

P203 Obtain, read and follow all safety instructions before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234 Keep only in original packaging.

P240 Ground and bond container and receiving equipment.

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 + P361 + P354 IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes

P304 + P340 + P316 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately.

P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.

P318 IF exposed or concerned, get medical advice.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

P410 Protect from sunlight.

P411 Store at temperatures not exceeding < 38 °C/ < 100 °F.

P420 Store separately.

Disposal:

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organic Peroxide

Liquid mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl phthalate	131-11-3	>= 40 - < 45
2-Butanone, peroxide	1338-23-4	>= 30 - < 35
Trimethylpentanediol isobutyrate	6846-50-0	>= 20 - < 25
Butanone	78-93-3	>= 1 - < 5
hydrogen peroxide	7722-84-1	>= 1 - < 2.5

4. FIRST AID MEASURES

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

If inhaled : Administer oxygen if breathing is difficult or cyanosis is ob-

served.

Call a physician immediately.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Respiratory tract burning possible if aerosols are inhaled. Call a physician or poison control centre immediately. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : If symptoms persist, call a physician.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Rinse mouth thoroughly with water.

Keep respiratory tract clear. Do NOT induce vomiting.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed or if inhaled. Causes serious eye damage.

Suspected of damaging fertility or the unborn child.

Causes severe burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

: Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which

may auto-ignite.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment. Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from heat and sources of ignition.

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from combustible material.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

Do not swallow.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling. For personal protection see section 8.

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Keep in a well-ventilated place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

NOROX®MEKP-925H



Version Revision Date: SDS Number: Date of last issue: 04.07.2022 2.1 25.07.2024 60000000117 Date of first issue: 29.04.2021

Recommended storage tem- : < 38 °C

perature

age stability

Further information on stor- : Stable under recommended storage conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m3	ACGIH
2-Butanone, peroxide	1338-23-4	С	0.2 ppm	ACGIH
Butanone	78-93-3	TWA	200 ppm 590 mg/m3	IN OEL
		STEL	300 ppm 885 mg/m3	IN OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
hydrogen peroxide	7722-84-1	TWA	1 ppm 1.5 mg/m3	IN OEL
		TWA	1 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type ABEK-filter

Hand protection

Material Nitrile rubber Break through time < 30 min Glove thickness 0.40 mm

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.47 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable

suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the

product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Colour : colourless

Odour : slight

Odour Threshold : not determined

pH : not determined

Melting point/range : No data available

Boiling point/boiling range : not determined

Flash point : > 76 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Remarks: Organic peroxide

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

Upper explosion limit

No data available

Lower explosion limit / Lower

flammability limit

Lower explosion limit

No data available

Vapour pressure : not determined

Relative vapour density : > 1

Relative density : not determined

Density : ca. 1.1 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

60 °C

Auto-ignition temperature : not determined

Self-Accelerating decomposi-

tion tomporature (CADT)

tion temperature (SADT) Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Explosive properties : Not explosive In use, may form flammable/explosive vapour-

air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

No decomposition if stored normally.

Possibility of hazardous reac-

tions

Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,404 mg/kg

Method: Calculation method

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Acute inhalation toxicity : Acute toxicity estimate: 4.29 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg

Method: Expert judgement

Trimethylpentanediol isobutyrate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: Expert judgement

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LCLo (Rat): > 0.12 mg/l

Exposure time: 6 h
Test atmosphere: vapour
Method: Expert judgement

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Method: Expert judgement

Assessment: The substance or mixture has no acute dermal

toxicity

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on available data, the classification criteria

are not met.

hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male and female): 431 mg/kg

Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 9,200 mg/kg

Remarks: No adverse effect has been observed in acute tox-

icity tests.

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

dimethyl phthalate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

2-Butanone, peroxide:

Species : Rabbit

Result : Causes burns.

Trimethylpentanediol isobutyrate:

Species : Guinea pig Exposure time : 24 h

Result : No skin irritation

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Remarks : Based on available data, the classification criteria are not met.

Butanone:

Species : Rabbit

Assessment : Repeated exposure may cause skin dryness or cracking.

Method : OECD Test Guideline 404

Result : No skin irritation

hydrogen peroxide:

Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

dimethyl phthalate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

2-Butanone, peroxide:

Result : Irreversible effects on the eye

Trimethylpentanediol isobutyrate:

Species : Rabbit Exposure time : 24 h

Result : No eye irritation

Butanone:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Eye irritation

hydrogen peroxide:

Result : Irreversible effects on the eye Remarks : hydrogen peroxide, 35%

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Components:

dimethyl phthalate:

Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

2-Butanone, peroxide:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Assessment : Harmful if swallowed., Harmful if inhaled.

Trimethylpentanediol isobutyrate:

Species : Guinea pig

Result : Does not cause skin sensitisation.

Butanone:

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

Application Route: Intraperitoneal

Result: negative

Test Type: Micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Trimethylpentanediol isobutyrate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Method: Regulation (EC) No. 440/2008, Annex, B.13/14

(Ames test) Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Butanone:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: negative

hydrogen peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

positive

Remarks: Information taken from reference works and the

literature.

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Remarks: Information taken from reference works and the

literature.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Mouse (male and female) Method: OECD Test Guideline 474

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Result: negative

Remarks: hydrogen peroxide, 35%

Germ cell mutagenicity -

Assessment

Based on available data, the classification criteria are not met.

Carcinogenicity

Not classified due to lack of data.

Components:

dimethyl phthalate:

Species : Rat

Application Route : Skin contact

Method : OECD Test Guideline 451

Result : negative

Remarks : Based on data from similar materials

2-Butanone, peroxide:

Remarks : This information is not available.

hydrogen peroxide:

Carcinogenicity - Assess-

ment

Carcinogenicity classification not possible from current data.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

dimethyl phthalate:

Effects on fertility : Species: Rat

Application Route: oral (gavage) Method: OECD Test Guideline 440

Result: negative

Effects on foetal develop-

ment

Species: Rat

Application Route: Ingestion

General Toxicity Maternal: NOAEL: 840 mg/kg body weight Developmental Toxicity: NOAEL: 3,570 mg/kg body weight

Method: OECD Test Guideline 414

2-Butanone, peroxide:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity - Parent: NOAEL: 50 mg/kg body weight

Method: OECD Test Guideline 421

Result: negative

Trimethylpentanediol isobutyrate:

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Effects on foetal develop-

ment

Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

Suspected of damaging fertility or the unborn child., Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Butanone:

Effects on fertility : Species: Rat

Application Route: oral (drinking water)

General Toxicity - Parent: NOAEL: 10,000 mg/l General Toxicity F1: NOAEL: 10,000 mg/l

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Species: Rat

Application Route: oral (drinking water)

General Toxicity - Parent: LOAEL: 20,000 mg/l

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Species: Rat

Application Route: Inhalation

General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body

weiaht

Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight

Method: OECD Test Guideline 414

Result: negative

hydrogen peroxide:

Reproductive toxicity - As-

sessment

No data available

STOT - single exposure

Not classified due to lack of data.

Components:

Butanone:

Assessment : May cause drowsiness or dizziness.

hydrogen peroxide:

Target Organs : Respiratory Tract

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified due to lack of data.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Components:

hydrogen peroxide:

Remarks : No data available

Repeated dose toxicity

Components:

dimethyl phthalate:

Species : Rat

NOAEL : 770 mg/kg

Application Route : Oral

Exposure time : 16 w

Method : OECD Test Guideline 408

2-Butanone, peroxide:

Species : Rat

NOAEL : 200 mg/kg Application Route : oral (gavage)

Exposure time : 28 d

Method : OECD Test Guideline 407

Repeated dose toxicity -

Assessment

: Harmful if swallowed., Harmful if inhaled.

hydrogen peroxide:

Species : Mouse, female NOAEL : 37 mg/kg

Application Route : oral (drinking water)

Exposure time : 90 d

Remarks : hydrogen peroxide, 35%

Species : Mouse, males NOAEL : 26 mg/kg

Application Route : oral (drinking water)

Exposure time : 90

Remarks : hydrogen peroxide, 35%

Aspiration toxicity

Not classified due to lack of data.

Components:

dimethyl phthalate:

No aspiration toxicity classification

Trimethylpentanediol isobutyrate:

Not classified due to data which are conclusive although insufficient for classification.

hydrogen peroxide:

Based on available data, the classification criteria are not met.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Further information

Product:

Remarks : No data available

Components:

dimethyl phthalate:

Remarks : No data available

Trimethylpentanediol isobutyrate:

Remarks : No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dimethyl phthalate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 52 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50: 4,100 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: 11 mg/l

Exposure time: 102 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

LOEC: 24 mg/l Exposure time: 102 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 9.6 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

LOEC: 23 mg/l Exposure time: 21 d

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Species: Daphnia magna (Water flea)

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 39 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Trimethylpentanediol isobutyrate:

Toxicity to fish : NOEC (Fish): >= 6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): >= 1.46 mg/l

Exposure time: 48 h

NOEC (Daphnia (water flea)): 0.7 mg/l

Exposure time: 21 d

Toxicity to algae/aquatic

plants

EC50 (Chlorella pyrenoidosa (algae)): > 7.49 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

LOEC: 0.7 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029

mg/

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,150 mg/l

Exposure time: 16 h Method: DIN 38 412 Part 8

hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

LC50 (Daphnia pulex (Water flea)): 2.4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l

Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0.63 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Persistence and degradability

Components:

dimethyl phthalate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301E

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Method: OECD Test Guideline 301D

Trimethylpentanediol isobutyrate:

Biodegradability : Result: rapidly biodegradable

Exposure time: 28 d

Method: OECD Test Guideline 301B

Butanone:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57

Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 1.54

2-Butanone, peroxide:

Partition coefficient: n-

octanol/water

log Pow: < 0.3 (25 °C)

Trimethylpentanediol isobutyrate:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 1.95

Partition coefficient: n-

octanol/water

: log Pow: 4.91 (25 °C)

Butanone:

Partition coefficient: n-

octanol/water

log Pow: 0.3 (40 °C)

hydrogen peroxide:

Partition coefficient: n- : log Pow: -1.57 (20 °C)

octanol/water Remarks: Information refers to the main component.

Calculation

Mobility in soil

No data available

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Components:

dimethyl phthalate:

Additional ecological infor-

mation

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Methyl ethyl ketone peroxide(s))

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

aircraft)

Packing instruction (passen- : 570

ger aircraft)

IMDG-Code

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Gefahrgruppe nach TRGS 741: lb (German regulatory requirements)

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AllC (AU) : All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

DSL (CA) : All components of this product are on the Canadian DSL

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TECI (TH) : On the inventory, or in compliance with the inventory

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

16. OTHER INFORMATION

Revision Date : 25.07.2024

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

The hazards on the label also apply to residues in the con-

tainer.

Sources of key data used to

compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

IN OEL : India. Permissible levels of certain chemical substances in

work environment.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

IN OEL / TWA : Time-Weighted Average Concentration (TWA) (8 hrs.)

IN OEL / STEL : Short-term exposure Limit STEL (15 min)

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect

NOROX®MEKP-925H



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.07.2022

 2.1
 25.07.2024
 600000000117
 Date of first issue: 29.04.2021

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IN / EN