according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NOROX®P-20

Chemical nature : Organic Peroxide

Liquid mixture

Manufacturer or supplier's details

Company : United Initiators (Shanghai) Co., Ltd

Address : Room 501, Bldg. 1, No. 1 Shangda Road

Shanghai, China, 200444

Emergency telephone number : +86 21 61172762

E-mail address : cs-initiators.cn@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : polymerisation initiators

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquidColour: light yellowOdour: ester-like

Flammable liquid and vapour. Heating may cause a fire. May be harmful if swallowed or in contact with skin. Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 3

Organic peroxides : Type C

Acute toxicity (Oral) : Category 5

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 5

Skin corrosion/irritation : Category 2

3

Serious eye damage/eye irritation

Category 2B

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H303 + H313 May be harmful if swallowed or in contact with

skin.

H315 + H320 Causes skin and eye irritation. H317 May cause an allergic skin reaction.

H332 Harmful if inhaled. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/ Store away from clothing/ combustible materials.

P233 Keep container tightly closed. P234 Keep only in original container.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/ doctor if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage:

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding 30 °C/ 86 °F. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Flammable liquid and vapour. Heating may cause a fire.

Health hazards

May be harmful if swallowed. Harmful if inhaled. May be harmful in contact with skin. Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction.

Environmental hazards

Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
tert-Butyl perbenzoate	614-45-9	>= 75 -< 80
Acetylacetone	123-54-6	>= 20 -< 25

4. FIRST AID MEASURES

according to GB/T 16483 and GB/T 17519



NOROX®P-20

If inhaled

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later. Administer oxygen if breathing is difficult or cyanosis is ob-

served.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Call a physician or poison control centre immediately. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : If symptoms persist, call a physician.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Rinse mouth thoroughly with water.

Keep respiratory tract clear.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May be harmful if swallowed or in contact with skin.

Causes skin and eye irritation. May cause an allergic skin reaction.

Have (L'C'al ala l

Harmful if inhaled. sensitising effects

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which

may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: Follow safe handling advice and personal protective equip-

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

tive equipment and emergency procedures

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Prevention of secondary hazards

: Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from heat and sources of ignition.

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from combustible material.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Do not swallow.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling.

For personal protection see section 8.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Avoidance of contact Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Storage

Conditions for safe storage Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

10 - 30 °C

age stability

Further information on stor- : Stable under recommended storage conditions.

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
		- 1 /		
Acetylacetone	123-54-6	TWA	25 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Eye/face protection : Ensure that eyewash stations and safety showers are close

to the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Hand protection

Material : Nitrile rubber
Break through time : <= 10 min
Glove thickness : 0.40 mm

Material : butyl-rubber
Break through time : <= 240 min
Glove thickness : 0.70 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazard-

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

ous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : ester-like

Odour Threshold : not determined

pH : substance/mixture is non-soluble (in water)

Melting point/ range : < 0 °C

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : 48 °C

Method: ISO 3679, closed cup

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Flammable liquid and vapour., Organic peroxide

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

: 11.4 %(V)

(for a component of this mixture)

Lower explosion limit / Lower : 2.4 %(V)

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

flammability limit (for a component of this mixture)

Vapour pressure : 7.9 hPa (20 °C)

(for a component of this mixture)

Relative vapour density : not determined

Relative density : not determined

Density : 1.03 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : not determined

Self-Accelerating decomposi-

tion temperature (SADT)

60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : 4 mPa.s (20 °C)

Viscosity, kinematic : not determined

Explosive properties : Not explosive In use, may form flammable/explosive vapour-

air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reac-

tions

Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

11. TOXICOLOGICAL INFORMATION

Acute toxicity

May be harmful if swallowed or in contact with skin. Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 2,850 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 1.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 3,950 mg/kg

Method: Calculation method

Components:

tert-Butyl perbenzoate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

GLP: yes

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat, male and female): > 1.01 - 4.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

GLP: yes

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

according to GB/T 16483 and GB/T 17519



NOROX®P-20

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/07/26

 3.0
 2025/01/22
 600000000203
 Date of first issue: 2018/09/24

Acetylacetone:

Acute oral toxicity : LD50 (Rat, female): 570 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 5.1 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, female): 790 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

tert-Butyl perbenzoate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Acetylacetone:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

tert-Butyl perbenzoate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Acetylacetone:

Species : Rabbit

Result : No eye irritation

according to GB/T 16483 and GB/T 17519



NOROX®P-20

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/07/26

 3.0
 2025/01/22
 600000000203
 Date of first issue: 2018/09/24

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

tert-Butyl perbenzoate:

Species : Mouse

Method : OECD Test Guideline 429

Result : May cause sensitisation by skin contact.

Acetylacetone:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact

Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: positive

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Acetylacetone:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test Type: Ames test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: positive GLP: yes

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test

Method: OECD Test Guideline 474

Result: positive

Test Type: Chromosomal aberration Method: OECD Test Guideline 483

Result: negative

Test Type: Chromosomal aberration Method: OECD Test Guideline 475

Result: negative

Test Type: gene mutation test Method: OECD Test Guideline 478

Result: Equivocal

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified due to lack of data.

according to GB/T 16483 and GB/T 17519



NOROX®P-20

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/07/26

 3.0
 2025/01/22
 600000000203
 Date of first issue: 2018/09/24

Components:

tert-Butyl perbenzoate:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Dose: 0 100, 300, 750, 1000 milligram per kilogram General Toxicity - Parent: NOAEL: 300 mg/kg bw/day General Toxicity F1: NOAEL: 300 mg/kg bw/day

Method: OECD Test Guideline 421

GLP: yes

Acetylacetone:

Effects on foetal develop-

ment

Species: Rat

Application Route: Inhalation

Dose: 0,20, 200, 400 parts per million General Toxicity Maternal: NOAEC: 200 ppm

Method: OECD Test Guideline 414

GLP: yes

STOT - single exposure

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Remarks : Not classified due to data which are conclusive although insuf-

ficient for classification.

STOT - repeated exposure

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

tert-Butyl perbenzoate:

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Species : Rat, male and female

NOAEL : 30 mg/kg Application Route : Oral Exposure time : 90 d

Acetylacetone:

Species : Rat, male and female

NOAEC : 0.42 mg/l Application Route : Inhalation Test atmosphere : vapour Exposure time : 90 d

Method : OECD Test Guideline 413

GLP : yes

Target Organs : Blood, Central nervous system

Aspiration toxicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

No aspiration toxicity classification

Acetylacetone:

Not classified due to lack of data.

Further information

Product:

Remarks : Solvents may degrease the skin.

Components:

Acetylacetone:

Remarks : Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

tert-Butyl perbenzoate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1.6 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

NOEC (Danio rerio (zebra fish)): 0.72 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 11 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

NOEC (Daphnia magna (Water flea)): 7.7 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.44

mg/I

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.8

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.72

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

M-Factor (Acute aquatic tox- :

icity)

: 1

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.49 mg/l

End point: reproduction rate

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): 43 mg/l

Exposure time: 0.5 h

according to GB/T 16483 and GB/T 17519



NOROX®P-20

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/07/26

 3.0
 2025/01/22
 600000000203
 Date of first issue: 2018/09/24

Test Type: Respiration inhibition Method: OECD Test Guideline 209

GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Acetylacetone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 104 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 25.9 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 83.22

mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 10 mg/l

Exposure time: 34 d

Test Type: flow-through test

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 18 mg/l

End point: reproduction rate

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): 107.6 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

GLP: yes

EC10 (activated sludge): 13.2 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

GLP: yes

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Persistence and degradability

Components:

tert-Butyl perbenzoate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Acetylacetone:

Biodegradability : Inoculum: activated sludge

Result: Readily biodegradable.

Biodegradation: > 80 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Bioaccumulative potential

Components:

tert-Butyl perbenzoate:

Partition coefficient: n-

octanol/water

log Pow: 3 (25 °C)

Acetylacetone:

Bioaccumulation : Bioconcentration factor (BCF): 3.16

Remarks: Calculation

Partition coefficient: n-

octanol/water

log Pow: 0.68 (40 °C)

Method: Tested according to Annex V of Directive

67/548/EEC.

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3103

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID

(tert-BUTYL PEROXYBENZOATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3103

Proper shipping name : Organic peroxide type C, liquid

(tert-Butyl peroxybenzoate)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

570

Packing instruction (cargo :

aircraft)

Packing instruction (passen- : 570

ger aircraft)

IMDG-Code

UN number : UN 3103

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID

(tert-BUTYL PEROXYBENZOATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2
EmS Code : F-J, S-R
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

GB 6944/12268

UN number : UN 3103

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID

(tert-BUTYL PEROXYBENZOATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Gefahrgruppe nach TRGS 741: lb, S+ (German regulatory requirements)

Produkt unterliegt dem Sprengstoffgesetz (SprengG; Stoffgruppe C). (German regulatory requirements)

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W5.4 Flammable liquids 5,000 t

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W7.2 Organic peroxides 50 t
Hazardous Chemicals for Priority Management under : Listed

SAWS

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not listed

and Export

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

The components of this product are reported in the following inventories:

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version 3.0	Revision Date: 2025/01/22	_	OS Number: 0000000203	Date of last issue: 2024/07/26 Date of first issue: 2018/09/24
TCS	SI (TW)	:	On the inventory,	or in compliance with the inventory
TSO	CA (US)	:	All substances list	ed as active on the TSCA inventory
AIIC	C (AU)	:	On the inventory,	or in compliance with the inventory
DSI	L (CA)	:	All components of	this product are on the Canadian DSL
EN	CS (JP)	:	On the inventory,	or in compliance with the inventory
ISH	L (JP)	:	On the inventory,	or in compliance with the inventory
KE	CI (KR)	:	On the inventory, or in compliance with the inventory	
PIC	CS (PH)	:	On the inventory, or in compliance with the inventory	
IEC	SC (CN)	:	On the inventory, or in compliance with the inventory	
TEC	CI (TH)	:	On the inventory,	or in compliance with the inventory

16. OTHER INFORMATION

Revision Date : 2025/01/22

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

The hazards on the label also apply to residues in the con-

tainer.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for

according to GB/T 16483 and GB/T 17519



NOROX®P-20

Version Revision Date: SDS Number: Date of last issue: 2024/07/26 3.0 2025/01/22 600000000203 Date of first issue: 2018/09/24

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk, IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN