According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NOROX®SG-10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Curing chemical

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH

Dr.-Gustav-Adolph-Str. 3

82049 Pullach

Telephone : +49 / 89 / 74422 - 0

E-mail address of person

responsible for the SDS

: contact@united-in.com

### 1.4 Emergency telephone number

+44 1235 239670

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Organic peroxides, Type D H242: Heating may cause a fire.

Acute toxicity, Category 4 H302: Harmful if swallowed.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin corrosion, Sub-category 1B H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Hazard pictograms :







Signal word : Danger

Hazard statements : H242 Heating may cause a fire.

H302 + H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P234 Keep only in original packaging.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with

water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Immedi-

ately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P370 + P378 In case of fire: Use water spray, alcohol-

resistant foam, dry chemical or carbon dioxide to

extinguish.

Hazardous components which must be listed on the label:

2-Butanone, peroxide (CAS-No. 1338-23-4)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : Organic Peroxide

Liquid mixture

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

## Components

EC-No. Index-No. Registration number  2-Butanone, peroxide  1338-23-4	Chemical name	CAS-No.	Classification	Concentration
Registration number   1338-23-4				(% w/w)
2-Butanone, peroxide  1338-23-4 700-954-4 01-2119514691-43- 0000  1722-84-1 231-765-0 008-003-00-9 01-2119485845-22  1722-84-1 231-765-0 008-003-00-9 01-2119485845-22  1722-84-1 231-765-0 008-003-00-9 01-2119485845-22  1722-84-1 231-765-0 008-003-00-9 01-2119485845-22  1722-84-1 231-765-0 008-003-00-9 01-2119485845-22  18314  Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412    Specific concentration limit   Ox. Liq. 1; H271   >= 70 % Ox. Liq. 2; H272   50 - < 70 %   Skin Corr. 1A; H314   >= 70 %   Skin Corr. 1B; H314   >= 70 %   Skin Corr. 1B; H314   >= 70 %   Skin Corr. 1B; H315   35 - < 50 %   Eye Dam. 1; H318   8 - < 50 %   Eye Dam. 1; H318   8 - < 50 %   Eye Dam. 1; H318   8 - < 50 %   Eye Irrit. 2; H315   5 - < 8 %   STOT SE 3; H335   >= 35 %   Aquatic Chronic 3; H412   >= 63 %   2-methylpentane-2,4-diol				
01-2119514691-43- 0000    Number   Num	2-Butanone, peroxide	1338-23-4		>= 30 - < 35
Nydrogen peroxide   Nyd				
Skin Corr. 1B; H314				
hydrogen peroxide  7722-84-1 231-765-0 008-003-00-9 01-2119485845-22 Skin Corr. 1A; H318 Eye Dam. 1; H318 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412				
hydrogen peroxide       7722-84-1 231-765-0 008-003-00-9 01-2119485845-22       Ox. Liq. 1; H271 Acute Tox. 4; H302 Skin Corr. 1A; H314 H32 Specific concentration limit Ox. Liq. 1; H271 ⇒ 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 ⇒ 70 % Skin Corr. 1A; H314 ⇒ 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 ⇒ 35 % Aquatic Chronic 3; H412 ⇒ 63 %         2-methylpentane-2,4-diol       107-41-5       Skin Irrit. 2; H315 Skin Irrit. 2; H315       >= 0.1 - < 1				
231-765-0 008-003-00-9 01-2119485845-22  Nation Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412  specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 >= 70 % Skin Corr. 1B; H314 >= 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1	hydrogen peroxide	7722-84-1		>= 3 - < 5
01-2119485845-22  Skin Corr. 1A; H314  Eye Dam. 1; H318  STOT SE 3; H335 (Respiratory system)  Aquatic Chronic 3; H412  ———————————————————————————————————	Trydrogen peroxide		• •	/=0 (0
H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412  specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412  ———————————————————————————————————		01-2119485845-22		
STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412				
tem) Aquatic Chronic 3; H412  specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1			STOT SE 3; H335	
Aquatic Chronic 3; H412  specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
H412  specific concentration limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
tion limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
tion limit Ox. Liq. 1; H271 >= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1			coocific concentra	
>= 70 % Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
Ox. Liq. 2; H272 50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1			Ox. Liq. 1; H271	
50 - < 70 % Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
Skin Corr. 1A; H314 >= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
>= 70 % Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1			Skin Corr. 1A;	
Skin Corr. 1B; H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
H314 50 - < 70 % Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
Skin Irrit. 2; H315 35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
35 - < 50 % Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
Eye Dam. 1; H318 8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 % 2-methylpentane-2,4-diol 107-41-5 Skin Irrit. 2; H315 >= 0.1 - < 1				
8 - < 50 % Eye Irrit. 2; H319 5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
5 - < 8 % STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 % 2-methylpentane-2,4-diol 107-41-5 Skin Irrit. 2; H315 >= 0.1 - < 1			8 - < 50 %	
STOT SE 3; H335 >= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol 107-41-5 Skin Irrit. 2; H315 >= 0.1 - < 1				
>= 35 % Aquatic Chronic 3; H412 >= 63 %  2-methylpentane-2,4-diol  107-41-5  Skin Irrit. 2; H315 >= 0.1 - < 1				
2-methylpentane-2,4-diol			>= 35 %	
>= 63 % 2-methylpentane-2,4-diol 107-41-5 Skin Irrit. 2; H315 >= 0.1 - < 1				
2-methylpentane-2,4-diol 107-41-5 Skin Irrit. 2; H315 >= 0.1 - < 1				
		107.11.5		0.1
	2-metnyipentane-2,4-diol	107-41-5 203-489-0	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 0.1 - < 1

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

	603-053-00-3 01-2119539582-35	Repr. 2; H361d	
Substances with a workplace exposure limit :			
dimethyl phthalate	131-11-3		>= 55 - < 65
	205-011-6		
	01-2119437229-36		

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If inhaled : Administer oxygen if breathing is difficult or cyanosis is ob-

served.

Call a physician immediately.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Respiratory tract burning possible if aerosols are inhaled. Call a physician or poison control centre immediately. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : If symptoms persist, call a physician.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Rinse mouth thoroughly with water. Keep respiratory tract clear. Do NOT induce vomiting.

If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed or if inhaled.

Causes serious eye damage.

Causes severe burns.

Harmful if swallowed or if inhaled. Causes serious eye damage.

Causes severe burns.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which

may auto-ignite.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment. Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

## 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

Do not swallow.

Do not breathe vapours/dust. Avoid contact with skin and eyes. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling. For personal protection see section 8.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material. Do not spray on a naked flame or any incandescent material.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Hygiene measures : Avoid contact with skin, eyes and clothing. Keep away from

food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately

after handling the product.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in cool place. Keep in a well-ventilated place. Contamination may result in dangerous pressure increases - closed containers may rupture. Observe label precautions. Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright

to prevent leakage.

Advice on common storage : Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem-

perature

< 30 °C

Further information on stor-

age stability

Stable under recommended storage conditions.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m3	GB EH40
		STEL	10 mg/m3	GB EH40
2-Butanone, peroxide	1338-23-4	STEL	0.2 ppm 1.5 mg/m3	GB EH40
hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m3	GB EH40
		STEL	2 ppm 2.8 mg/m3	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

2-methylpentane- 2,4-diol	107-41-5	TWA	25 ppm 123 mg/m3	GB EH40
		STEL	25 ppm 123 mg/m3	GB EH40

## **Derived No Effect Level (DNEL):**

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl phthalate	Workers	Inhalation	Long-term systemic effects	66.1 mg/m3
	Workers	Skin contact	Long-term systemic effects	135 mg/kg bw/day
2-Butanone, peroxide	Workers	Inhalation	Long-term systemic effects	2.35 mg/m3
	Workers	Skin contact	Long-term systemic effects	1.33 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	7.05 mg/m3
hydrogen peroxide	Workers	Inhalation	Acute local effects	3 mg/m3
	Workers	Inhalation	Long-term local ef- fects	1.4 mg/m3
2-methylpentane-2,4- diol	Workers	Inhalation	Long-term systemic effects	44.43 mg/m3
	Workers	Inhalation	Long-term local ef- fects	49 mg/m3
	Workers	Inhalation	Acute local effects	98 mg/m3
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day

## **Predicted No Effect Concentration (PNEC):**

Substance name	Environmental Compartment	Value
dimethyl phthalate	Fresh water	0.192 mg/l
	Marine water	0.0192 mg/l
	Sewage treatment plant	4 mg/l
	Fresh water sediment	1.3 mg/kg dry
		weight (d.w.)
	Soil	3.16 mg/kg dry
		weight (d.w.)
	Marine sediment	0.13 mg/kg dry
		weight (d.w.)
2-Butanone, peroxide	Fresh water	0.0056 mg/l
	Marine water	0.00056 mg/l
	Intermittent use/release	0.056 mg/l
	Sewage treatment plant	1.2 mg/l
	Fresh water sediment	0.0876 mg/kg
	Marine sediment	0.00876 mg/kg
	Soil	0.0142 mg/kg
hydrogen peroxide	Sewage treatment plant	4.66 mg/l
	Fresh water	0.0126 mg/l
_	Marine sediment	0.047 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

	Fresh water sediment	0.047 mg/l		
	Marine water	0.0126 mg/l		
	Soil	0.0023 mg/l		
2-methylpentane-2,4-diol	Fresh water	0.429 mg/l		
	Marine water	0.043 mg/l		
	Intermittent use/release	4.29 mg/l		
	Sewage treatment plant	20 mg/l		
	Fresh water sediment	1.59 mg/kg dry		
		weight (d.w.)		
	Marine sediment	0.159 mg/kg dry weight (d.w.)		
	Soil	0.066 mg/kg dry weight (d.w.)		
	Secondary poisoning			
	Remarks:No bioaccumulation is to b	Remarks:No bioaccumulation is to be expected (log Pow <= 4).		

#### 8.2 Exposure controls

### **Engineering measures**

Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye/face protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Hand protection

Material : Nitrile rubber
Break through time : < 30 min
Glove thickness : 0.40 mm

Material : butyl-rubber Break through time : 480 min Glove thickness : 0.47 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

workday.

Skin and body protection : Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable

suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless, clear

Odour : mint-like

Odour Threshold : not determined

pH : 4 - 7 (20 °C)

Melting point/freezing point : not determined

Initial boiling point and boiling :

range

not determined

Flash point : > 80 °C

Method: closed cup

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

Upper explosion limit

not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Lower explosion limit / Lower :

flammability limit

Lower explosion limit

not determined

Vapour pressure : not determined

Relative vapour density : No data available

Relative density : not determined

Density : ca. 1.1 g/cm3 (20 °C)

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : Solvent: organic solvents

Description: soluble

Solvent: Phthalates Description: soluble

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : not determined

Viscosity

Viscosity, dynamic : ca. 15 mPa.s (20 °C)

Viscosity, kinematic : not determined

Explosive properties : Not explosive

In use, may form flammable/explosive vapour-air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

9.2 Other information

Self-Accelerating decomposi-

tion temperature (SADT)

60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Flammability (liquids) : Flammable liquid, Organic peroxide

Self-ignition : The substance or mixture is not classified as pyrophoric.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Stable under recommended storage conditions. Heating may cause a fire or explosion.

### 10.2 Chemical stability

Stable under recommended storage conditions.

No decomposition if stored normally.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

#### 10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

### 10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

### **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### **Acute toxicity**

Harmful if swallowed or if inhaled.

### **Product:**

Acute oral toxicity : Acute toxicity estimate: 1,325 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.04 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

#### **Components:**

#### 2-Butanone, peroxide:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg

Method: Expert judgement

hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male and female): 431 mg/kg

Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 9,200 mg/kg

Remarks: No adverse effect has been observed in acute tox-

icity tests.

2-methylpentane-2,4-diol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat, male): > 55 mg/l

Exposure time: 8 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

toxicity

Remarks: No mortality observed at this dose.

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

**Product:** 

Remarks : Extremely corrosive and destructive to tissue.

**Components:** 

2-Butanone, peroxide:

Species : Rabbit

Result : Causes burns.

hydrogen peroxide:

Result : Corrosive after 3 minutes or less of exposure

2-methylpentane-2,4-diol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on harmonised classification in EU regulation

1272/2008, Annex VI

dimethyl phthalate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

**Product:** 

Remarks : May cause irreversible eye damage.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Components:

2-Butanone, peroxide:

Result : Irreversible effects on the eye

hydrogen peroxide:

Result : Irreversible effects on the eye Remarks : hydrogen peroxide, 35%

2-methylpentane-2,4-diol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : irritating

Remarks : Based on harmonised classification in EU regulation

1272/2008, Annex VI

dimethyl phthalate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

**Components:** 

2-Butanone, peroxide:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Assessment : Harmful if swallowed., Harmful if inhaled.

2-methylpentane-2,4-diol:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

dimethyl phthalate:

Species : Mouse

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

**Components:** 

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 476

Result: negative

hydrogen peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

positive

Remarks: Information taken from reference works and the

literature.

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Remarks: Information taken from reference works and the

literature.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Mouse (male and female) Method: OECD Test Guideline 474

Result: negative

Remarks: hydrogen peroxide, 35%

Germ cell mutagenicity- As-

sessment

Based on available data, the classification criteria are not met.

2-methylpentane-2,4-diol:

Genotoxicity in vitro : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Germ cell mutagenicity- As-

sessment

In vitro tests did not show mutagenic effects

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 473

Result: negative

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

Application Route: Intraperitoneal

Result: negative

Test Type: Micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified due to lack of data.

**Components:** 

2-Butanone, peroxide:

Remarks : This information is not available.

hydrogen peroxide:

Carcinogenicity - Assess-

ment

: Carcinogenicity classification not possible from current data.

2-methylpentane-2,4-diol:

Remarks : This information is not available.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Carcinogenicity - Assess-

ment

Based on available data, the classification criteria are not met.

dimethyl phthalate:

Species : Rat

Application Route : Skin contact

Method : OECD Test Guideline 451

Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified due to lack of data.

**Components:** 

2-Butanone, peroxide:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity - Parent: NOAEL: 50 mg/kg body weight

Method: OECD Test Guideline 421

Result: negative

hydrogen peroxide:

Reproductive toxicity - As-

sessment

No data available

2-methylpentane-2,4-diol:

Effects on fertility : Species: Rat

Strain: wistar

Application Route: oral (gavage) Method: OECD Test Guideline 443

Result: negative

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments., Suspected of damaging the unborn

child.

dimethyl phthalate:

Effects on fertility : Species: Rat

Application Route: oral (gavage) Method: OECD Test Guideline 440

Result: negative

Effects on foetal develop-

ment

Species: Rat

Application Route: Ingestion

General Toxicity Maternal: NOAEL: 840 mg/kg body weight Developmental Toxicity: NOAEL: 3,570 mg/kg body weight

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Method: OECD Test Guideline 414

#### STOT - single exposure

Not classified due to lack of data.

#### **Components:**

hydrogen peroxide:

Target Organs : Respiratory Tract

Assessment : May cause respiratory irritation.

2-methylpentane-2,4-diol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

### STOT - repeated exposure

Not classified due to lack of data.

### **Components:**

hydrogen peroxide:

Remarks : No data available

2-methylpentane-2,4-diol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

#### Repeated dose toxicity

### **Components:**

## 2-Butanone, peroxide:

Species : Rat
NOAEL : 200 mg/kg
Application Route : oral (gavage)

Exposure time : 28 d

Method : OECD Test Guideline 407

hydrogen peroxide:

Species : Mouse, female NOAEL : 37 mg/kg

Application Route : oral (drinking water)

Exposure time : 90 d

Remarks : hydrogen peroxide, 35%

Species : Mouse, males NOAEL : 26 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

Application Route : oral (drinking water)

Exposure time : 90

Remarks : hydrogen peroxide, 35%

2-methylpentane-2,4-diol:

Species : Rat, male and female NOAEL : 450 mg/kg bw/day

Application Route : Ingestion Exposure time : 90

Method : OECD Test Guideline 408

dimethyl phthalate:

Species : Rat
NOAEL : 770 mg/kg
Application Route : Oral
Exposure time : 16 w

Method : OECD Test Guideline 408

**Aspiration toxicity** 

Not classified due to lack of data.

**Components:** 

hydrogen peroxide:

Based on available data, the classification criteria are not met.

2-methylpentane-2,4-diol:

Based on available data, the classification criteria are not met.

dimethyl phthalate:

No aspiration toxicity classification

**Further information** 

Product:

Remarks : No data available

Components:

dimethyl phthalate:

Remarks : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

### **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Components:**

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 39 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia pulex (Water flea)): 2.4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l

Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l

Exposure time: 72 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

Version SDS Number: Date of last issue: 09.10.2023 Revision Date: 2.1 09.12.2024 60000000312 Date of first issue: 29.11.2022

Toxicity to microorganisms EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0.63 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

2-methylpentane-2,4-diol:

Toxicity to fish LC50 (Gambusia affinis (Mosquito fish)): 8,510 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 5,410 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 429

mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)):

729 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to microorganisms

Remarks: No data available

dimethyl phthalate:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 39 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 52 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l

Exposure time: 72 h

Toxicity to microorganisms EC50: 4,100 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-NOEC: 11 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

Version **Revision Date:** SDS Number: Date of last issue: 09.10.2023 2.1 09.12.2024 60000000312 Date of first issue: 29.11.2022

icity) Exposure time: 102 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

LOEC: 24 mg/l Exposure time: 102 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 9.6 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

LOEC: 23 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

### 12.2 Persistence and degradability

## Components:

2-Butanone, peroxide:

Biodegradability Result: Readily biodegradable.

Method: OECD Test Guideline 301D

hydrogen peroxide:

Biodegradability Result: Readily biodegradable.

2-methylpentane-2,4-diol:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Readily biodegradable.

Biodegradation: 81 %

Method: OECD Test Guideline 301F

dimethyl phthalate:

Biodegradability Result: Readily biodegradable.

Method: OECD Test Guideline 301E

### 12.3 Bioaccumulative potential

#### Components:

2-Butanone, peroxide:

Partition coefficient: n-

octanol/water

log Pow: < 0.3 (25 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

hydrogen peroxide:

Partition coefficient: n- : log

octanol/water

: log Pow: -1.57 (20 °C)

Remarks: Information refers to the main component.

Calculation

2-methylpentane-2,4-diol:

Partition coefficient: n-

octanol/water

log Pow: -0.14

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57

Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 1.54

### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Other adverse effects

**Product:** 

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Components:

dimethyl phthalate:

Additional ecological infor-

mation

: No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

Version **Revision Date:** SDS Number: Date of last issue: 09.10.2023 09.12.2024 60000000312 Date of first issue: 29.11.2022 2.1

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14: Transport information**

### 14.1 UN number

**ADR** UN 3105 RID UN 3105 **IMDG** : UN 3105 **IATA UN 3105** 

### 14.2 UN proper shipping name

**ADR** ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

**RID** : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

**IMDG** ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

**IATA** Organic peroxide type D, liquid

(Methyl ethyl ketone peroxide(s))

# 14.3 Transport hazard class(es)

Class Subsidiary risks

**ADR** 5.2 **RID** 5.2 **IMDG** 5.2

**IATA HEAT** 5.2

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

### 14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : P1
Hazard Identification Number : 539
Labels : 5.2

**IMDG** 

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo : 570

aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passen: 570

ger aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

Version SDS Number: Date of last issue: 09.10.2023 Revision Date: Date of first issue: 29.11.2022 2.1 09.12.2024 60000000312

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) Conditions of restriction for the fol-

lowing entries should be considered:

Number on list 3 UK REACH Candidate list of substances of very high Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Britain)

Regulation (EC) on substances that deplete the ozone

layer

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

UK REACH List of substances subject to authorisation Not applicable

(Annex XIV)

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Not applicable

Control of Major Accident Hazards Regulations P6b

2015 (COMAH)

SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC

Not applicable

Not applicable

hydrogen peroxide

**PEROXIDES** 

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### The components of this product are reported in the following inventories:

TCSI (TW) On the inventory, or in compliance with the inventory

TSCA (US) All substances listed as active on the TSCA inventory

AIIC (AU) All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

DSL (CA) : All components of this product are on the Canadian DSL

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TECI (TH) : On the inventory, or in compliance with the inventory

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

For further information see eSDS.

#### **SECTION 16: Other information**

# Full text of H-Statements

H242 : Heating may cause a fire.

H271 : May cause fire or explosion; strong oxidizer.

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H361d : Suspected of damaging the unborn child.
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam.

Eye Irrit.

Org. Perox.

Ox. Liq.

Repr.

Skin Corr.

Skin Irrit.

Serious eye damage

Eye irritation

Organic peroxides

Oxidizing liquids

Reproductive toxicity

Skin corrosion

Skin Irrit.

Skin irritation

STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.10.2023

 2.1
 09.12.2024
 600000000312
 Date of first issue: 29.11.2022

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

The hazards on the label also apply to residues in the con-

tainer.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# NOROX®SG-10

Version 2.1	Revision Date: 09.12.2024	SDS Number: 600000000312	Date of last issue: 09.10.2023 Date of first issue: 29.11.2022
Org. P	erox. D	H242	Based on product data or assessment
Acute	Tox. 4	H302	Calculation method
Acute	Tox. 4	H332	Calculation method
Skin C	orr. 1B	H314	Calculation method
Eye Dam. 1		H318	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN