according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version SDS Number: Date of last issue: 08/09/2021 Revision Date: Date of first issue: 12/16/2016 3.0 05/06/2024 60000000163

#### **SECTION 1. IDENTIFICATION**

NOROX®SHP-90 Trade name

Manufacturer or supplier's details

Company name of supplier United Initiators, Inc.

Address 555 Garden Street

Elyria OH 44035 USA

Telephone +1-440-323-3112

Telefax +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300

CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person responsible for the SDS

cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

#### SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 4

Organic peroxides Type D

Eye irritation Category 2A

Skin sensitization Category 1

Reproductive toxicity Category 2

Specific target organ toxicity:

- single exposure

Category 3 (Respiratory system)

Short-term (acute) aquatic

hazard

Category 2

#### **GHS** label elements

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H227 Combustible liquid.

H242 Heating may cause a fire.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H401 Toxic to aquatic life.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases,

heavy metal salts and other reducing substances /combustible

materials.

P234 Keep only in original container.

P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < 100 °F/ <

38 °C. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organic Peroxide

Liquid

## Components

Chemical name	CAS-No.	Concentration (% w/w)
2,4-Pentanedione, peroxide	37187-22-7	>= 25 - < 30
Diacetone alcohol	123-42-2	>= 25 - < 30
Polyethylene glycol	25322-68-3	>= 20 - < 25
tert-Butyl perbenzoate	614-45-9	>= 7.5 - < 10
Acetylacetone	123-54-6	>= 1 - < 5

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person.

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 60000000163 Date of first issue: 12/16/2016

If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

If inhaled : Administer oxygen if breathing is difficult or cyanosis is

observed.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

In case of skin contact : If symptoms persist, call a physician.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Rinse mouth thoroughly with water.

Keep respiratory tract clear.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye irritation. May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

sensitizing effects

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapors may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec-: tive equipment and emer-

gency procedures

Follow safe handling advice and personal protective equipment recommendations.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Use personal protective equipment. Remove all sources of ignition.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

considerations".

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors). Keep away from heat and sources of ignition.

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from combustible material.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

Do not swallow.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

< 38 °C

< 100 °F

Further information on stor-

age stability

: Stable under recommended storage conditions.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diacetone alcohol	123-42-2	TWA	50 ppm	ACGIH
		TWA	50 ppm 240 mg/m3	NIOSH REL
		TWA	50 ppm	OSHA Z-1
			240 mg/m3	
		TWA	50 ppm	OSHA P0

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

			240 mg/m3	
Polyethylene glycol	25322-68-3	TWA (aero-	10 mg/m3	US WEEL
		sol)		
Acetylacetone	123-54-6	TWA	25 ppm	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Use NIOSH approved respiratory protection.

Hand protection

Material : butyl-rubber
Break through time : <= 480 min
Glove thickness : 0.5 mm

Material : Nitrile rubber
Break through time : <= 120 min
Glove thickness : 0.4 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the

hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Ensure that eyewash stations and safety showers are close

to the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Additional body garments should be used based upon the

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

task being performed (e.g., sleevelets, apron, gauntlets,

disposable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : light yellow

Odor : mild

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : 93 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : The substance or mixture is not classified as self heating. The

substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

No data available

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : > 1

Density : 1.1 - 1.2 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

Self-Accelerating decomposi-

tion temperature (SADT)

> 50 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

No decomposition if stored normally.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks.

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Acute toxicity

Not classified due to lack of data.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 4,019 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

#### **Components:**

2,4-Pentanedione, peroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): > 13.1 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist Method: Expert judgment

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: Expert judgment

Assessment: The substance or mixture has no acute dermal

toxicity

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3,002 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat, male and female): >= 7.6 mg/l

Exposure time: 4 h

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Test atmosphere: vapor

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD0 (Rat): > 1,875 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Polyethylene glycol:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

tert-Butyl perbenzoate:

Acute oral toxicity : LD0 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): 1.01 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Acute dermal toxicity : LD0 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Acetylacetone:

Acute oral toxicity : LD50 (Rat): 570 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.1 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, female): 790 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

**Product:** 

Remarks : May cause skin irritation and/or dermatitis.

**Components:** 

2,4-Pentanedione, peroxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Diacetone alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Polyethylene glycol:

Result : No skin irritation

tert-Butyl perbenzoate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Acetylacetone:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks : May cause irreversible eye damage.

**Components:** 

2,4-Pentanedione, peroxide:

Species : Rabbit
Result : Eye irritation

Method : OECD Test Guideline 405

Diacetone alcohol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Polyethylene glycol:

Result : No eye irritation

tert-Butyl perbenzoate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Acetylacetone:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

**Product:** 

Remarks : Causes sensitization.

**Components:** 

2,4-Pentanedione, peroxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : Probability or evidence of skin sensitization in humans

Remarks : Causes sensitization.

Diacetone alcohol:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

Polyethylene glycol:

Result : Does not cause skin sensitization.

tert-Butyl perbenzoate:

Species : Mouse

Method : OECD Test Guideline 429

Result : May cause sensitization by skin contact.

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Acetylacetone:

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified due to lack of data.

**Components:** 

2,4-Pentanedione, peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)
Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Diacetone alcohol:

Genotoxicity in vitro : Method: OECD Test Guideline 476

Result: negative

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Polyethylene glycol:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

tert-Butyl perbenzoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: positive

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Test Type: Mouse Lymphoma

Result: positive

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Application Route: Oral

Result: negative

Acetylacetone:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 479

Result: positive

Method: OECD Test Guideline 473

Result: positive

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474

Result: positive

Method: OECD Test Guideline 483

Result: negative

Method: OECD Test Guideline 475

Result: negative

Method: OECD Test Guideline 478

Result: Equivocal

Test Type: DNA Repair

Species: Rat

Application Route: Oral

Result: negative

Species: Rat

Application Route: inhalation (vapor)

Method: OPPTS 870.5395

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Result: negative

#### Carcinogenicity

Not classified due to lack of data.

#### **Components:**

2,4-Pentanedione, peroxide:

Remarks : This information is not available.

Diacetone alcohol:

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

tert-Butyl perbenzoate:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

#### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

#### **Components:**

#### 2,4-Pentanedione, peroxide:

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

Diacetone alcohol:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity Parent: NOAEL: 300 mg/kg body weight General Toxicity F1: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 422

Effects on fetal development : Species: Rat

Application Route: inhalation (vapor) General Toxicity Maternal: NOAEL: 4.106 Embryo-fetal toxicity.: NOAEL: 12,292 Method: OECD Test Guideline 414

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Polyethylene glycol:

tert-Butyl perbenzoate:

Effects on fertility : Species: Rat

Application Route: Oral

General Toxicity Parent: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 421

Effects on fetal development : Species: Rat

Application Route: Oral

General Toxicity Maternal: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

Acetylacetone:

Effects on fetal development : Species: Rat

Application Route: inhalation (vapor)
Duration of Single Treatment: 13 d
General Toxicity Maternal: NOAEC: 200
Teratogenicity: NOAEC Parent: 400
Embryo-fetal toxicity.: NOAEC F1: 50
Method: OECD Test Guideline 414

Species: Rat

Application Route: inhalation (vapor)
Duration of Single Treatment: 13 d
General Toxicity Maternal: LOAEC: 400
Embryo-fetal toxicity.: LOAEC F1: 200
Method: OECD Test Guideline 414

STOT-single exposure

May cause respiratory irritation.

**Components:** 

Diacetone alcohol:

Target Organs : Respiratory system

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

**Components:** 

Diacetone alcohol:

Species : Rat

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

NOAEL : 1.04 mg/l LOAEL : 4.685 mg/l Application Route : inhalation (vapor)

Exposure time : 6 w

Method : OECD Test Guideline 412

Species : Rat

NOAEL : 100 mg/kg

Application Route : oral (gavage)

Method : OECD Test Guideline 422

Polyethylene glycol:

Species : Dog NOAEL : 500 mg/kg Application Route : Oral

Acetylacetone:

Species : Rat

NOAEL : 200 mg/kg

LOAEL : 805 mg/kg

Application Route : inhalation (vapor)

Exposure time : 9 d

Species : Rat

NOAEL : 100 mg/kg Application Route : inhalation (vapor)

Exposure time : 90 d

Method : OECD Test Guideline 413

Species : Rabbit
NOAEL : 244 mg/kg
LOAEL : 975 mg/kg
Application Route : Dermal
Exposure time : 9 d

Aspiration toxicity

Not classified due to lack of data.

**Components:** 

Acetylacetone:

No aspiration toxicity classification

**Further information** 

**Product:** 

Remarks : No data available

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

**Components:** 

Acetylacetone:

Remarks : Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Components:

2,4-Pentanedione, peroxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 67.6 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 7.05 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5.36

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: 614 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Diacetone alcohol:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): >

1,000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,000

ng/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 60000000163 Date of first issue: 12/16/2016

Polyethylene glycol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 48 h

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

(CAESAR models), etc.

Toxicity to algae/aquatic

plants

: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mq/l

Exposure time: 72 h

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

(CAESAR models), etc.

Toxicity to microorganisms : IC50: 1,651,512 mg/l

Exposure time: 46 h

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

(CAESAR models), etc.

tert-Butyl perbenzoate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.8

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.72

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

: 1

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.49 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Toxicity to microorganisms : EC50: 43 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Acetylacetone:

Toxicity to fish : LC50 (Fish): 104 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 25.9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 83.22

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 10 mg/l

Exposure time: 34 d

Method: OECD Test Guideline 210

LOEC (Pimephales promelas (fathead minnow)): 22 mg/l

Exposure time: 34 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 18 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 107.6 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

EC10: 13.2 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

**Components:** 

2,4-Pentanedione, peroxide:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

according to the OSHA Hazard Communication Standard



# NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301

Polyethylene glycol:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301F

tert-Butyl perbenzoate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Acetylacetone:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301C

Bioaccumulative potential

**Components:** 

2,4-Pentanedione, peroxide:

Partition coefficient: n- : log Pow: 1.1 (25 °C / 25 °C)

octanol/water Method: OECD Test Guideline 117

Diacetone alcohol:

Partition coefficient: n-

octanol/water

log Pow: -0.09 (20 °C / 20 °C)

Polyethylene glycol:

Bioaccumulation : Bioconcentration factor (BCF): 3.2

Partition coefficient: n-

octanol/water

log Pow: -2.3 (25 °C / 25 °C)

tert-Butyl perbenzoate:

Partition coefficient: n-

octanol/water

log Pow: 2.89 (25 °C / 25 °C)

Acetylacetone:

Bioaccumulation : Bioconcentration factor (BCF): 3.16

Remarks: Calculation

Partition coefficient: n-

octanol/water

: log Pow: 0.68 (40 °C / 40 °C)

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

Mobility in soil

No data available

Other adverse effects

**Product:** 

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

**UNRTDG** 

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE, tert-BUTYL

PEROXYBENZOATE)

Class : 5.:

Packing group : Not assigned by regulation

Labels : 5.2 Environmentally hazardous : no

IATA-DGR

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

UN/ID No. : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Acetyl acetone peroxide, tert-Butyl peroxybenzoate)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen- : 570

ger aircraft)

**IMDG-Code** 

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE, tert-BUTYL

PEROXYBENZOATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Tert-Butyl Peroxybenzoate, <=12%, Acetyl Acetone Perox-

ide, <=32%)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 145 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Organic peroxides

Respiratory or skin sensitization

Reproductive toxicity

Serious eve damage or eve irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Diacetone alcohol 123-42-2 Polyethylene glycol 25322-68-3

### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

#### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

## International Regulations

Gefahrgruppe nach TRGS 741: II (German regulatory requirements)

#### The ingredients of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AIIC (AU) : On the inventory, or in compliance with the inventory

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 60000000163 Date of first issue: 12/16/2016

DSL (CA) : All components of this product are on the Canadian DSL

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Acetylacetone 123-54-6

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 05/06/2024

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

according to the OSHA Hazard Communication Standard



## NOROX®SHP-90

Version Revision Date: SDS Number: Date of last issue: 08/09/2021 3.0 05/06/2024 600000000163 Date of first issue: 12/16/2016

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8