according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TAPPI-75-AL

Chemical nature : Organic Peroxide

Manufacturer or supplier's details

Company : United Initiators (Shanghai) Co., Ltd

Address : Room 501, Bldg. 1, No. 1 Shangda Road

Shanghai, China, 200444

Telephone : +86 21 61172758

Emergency telephone number : +86 21 61172762

E-mail address : cs-initiators.cn@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : polymerisation initiators

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquidColour: colourlessOdour: ester-like

Flammable liquid and vapour. Heating may cause a fire. May be harmful if swallowed or in contact with skin. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 3

Organic peroxides : Type C

Acute toxicity (Oral) : Category 5

Acute toxicity (Dermal) : Category 5

Skin corrosion/irritation : Category 2

Skin sensitisation : Sub-category 1B

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 60000000044 Date of first issue: 2017/01/23

Aspiration hazard Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

GHS label elements

Hazard pictograms









Signal word Danger

H226 Flammable liquid and vapour. Hazard statements

H242 Heating may cause a fire.

H303 + H313 May be harmful if swallowed or in contact with

skin.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible

materials.

P233 Keep container tightly closed.

P234 Keep only in original container.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate-

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

ly all contaminated clothing. Rinse skin with water/ shower. P312 Call a POISON CENTER/ doctor if you feel unwell.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage:

P405 Store locked up.

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < -5 °C/ <

23 °F. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Flammable liquid and vapour. Heating may cause a fire.

Health hazards

May be harmful if swallowed. May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Environmental hazards

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : tert-pentyl peroxypivalate

CAS-No. : 29240-17-3

Components

Chemical name	CAS-No.	Concentration (% w/w)
tert-pentyl peroxypivalate	29240-17-3	>= 70 -<= 77
Hydrocarbons, C4, 1,3-butadiene-free, pol-	93685-81-5	>= 23 -<= 30
ymerised., triisobutylene fraction, hydrogenated		

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 60000000044 Date of first issue: 2017/01/23

4. FIRST AID MEASURES

General advice Take off contaminated clothing and shoes immediately.

Call a physician immediately.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later. No artificial respiration, mouth-to-mouth or mouth to nose. Use

suitable instruments/apparatus.

If inhaled Administer oxygen if breathing is difficult or cyanosis is ob-

served.

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Call a physician or poison control centre immediately. If unconscious, place in recovery position and seek medical

Keep respiratory tract clear.

In case of skin contact If symptoms persist, call a physician.

> In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

In the case of contact with eyes, rinse immediately with plenty In case of eye contact

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Call a physician immediately.

> Contact a poison control center. Rinse mouth thoroughly with water.

Keep respiratory tract clear. Do NOT induce vomiting.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May be harmful if swallowed or in contact with skin.

May be fatal if swallowed and enters airways.

Causes skin irritation.

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

May cause an allergic skin reaction.

sensitising effects

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Risk of explosion if heated under confinement.

Possible emission of gaseous decomposition products may

lead to a dangerous pressure build-up.

Avoid confinement.

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which

may auto-ignite.

The product burns violently.

Flash back possible over considerable distance.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Prevention of secondary

hazards

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from heat and sources of ignition.

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Keep away from combustible material.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Protect from contamination.

Do not swallow.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling.

For personal protection see section 8.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Avoidance of contact : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Storage

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Store in cool place.

Contamination may result in dangerous pressure increases -

closed containers may rupture. Observe label precautions.

Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : Keep away from combustible materials.

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

< -5 °C

Further information on stor- : Stable under recommended storage conditions.

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

age stability

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Respirator with combination filter for vapour/particulate (EN

141)

Filter type : ABEK-filter

Eye/face protection : Ensure that eyewash stations and safety showers are close

to the workstation location.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Hand protection

Material : butyl-rubber
Break through time : <= 30 min
Glove thickness : 0.47 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protec-

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

tive glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazard-ous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Keep away from food and drink. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : ester-like

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/range : < -25 °C

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : 47 °C

Method: ISO 3679

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Flammability (liquids) : Flammable liquid and vapour., Organic peroxide

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper

flammability limit

4 %(V)

(for a component of this mixture)

Lower explosion limit / Lower

flammability limit

0.5 %(V)

(for a component of this mixture)

Vapour pressure : ca. 1 hPa (35 °C)

Relative vapour density : No data available

Relative density : not determined

Density : 0.86 g/cm3 (20 °C)

Solubility(ies)

Water solubility : practically insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

log Pow: 3.3 (30 °C)

Auto-ignition temperature : not determined

Self-Accelerating decomposi-

tion temperature (SADT)

Method: UN-Test H.4

25 °C

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : 2 mPa.s (20 °C)

Viscosity, kinematic : not determined

Explosive properties : Not explosive In use, may form flammable/explosive vapour-

air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

Refractive index : 1.419 (20 °C)

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.

No decomposition if stored normally.

Possibility of hazardous reac-

tions

Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

11. TOXICOLOGICAL INFORMATION

Acute toxicity

May be harmful if swallowed or in contact with skin.

Product:

Acute oral toxicity : LD50 (Rat): 4,270 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 9.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Remarks: Based on test data

Components:

tert-pentyl peroxypivalate:

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Acute oral toxicity : LD50 (Rat): 4,270 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 9.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Remarks: Based on test data

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,000 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: No data available

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,16 ml/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : May cause skin irritation in susceptible persons.

Components:

tert-pentyl peroxypivalate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit

Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

tert-pentyl peroxypivalate:

Species : Rabbit

Result : No eye irritation

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : The product is a skin sensitiser, sub-category 1B.

Remarks : Causes sensitisation.

Components:

tert-pentyl peroxypivalate:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: positive

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Species: Mouse (male and female)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Components:

tert-pentyl peroxypivalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: positive

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Species: Mouse (male and female)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Germ cell mutagenicity -

Assessment

: No known effect.

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : This information is not available.

Components:

tert-pentyl peroxypivalate:

Remarks : This information is not available.

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Carcinogenicity - Assess-

ment

: No known effect.

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

General Toxicity - Parent: NOAEL: 150 mg/kg body weight General Toxicity F1: NOAEL: 150 mg/kg body weight

Fertility: NOAEL: 310 mg/kg body weight Method: OECD Test Guideline 422

Effects on foetal develop-

ment

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: NOAEL: 150 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: NOAEL: 310 mg/kg body weight

Method: OECD Test Guideline 422

Components:

tert-pentyl peroxypivalate:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: NOAEL: 150 mg/kg body weight General Toxicity F1: NOAEL: 150 mg/kg body weight

Fertility: NOAEL: 310 mg/kg body weight Method: OECD Test Guideline 422

Effects on foetal develop-

ment

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: NOAEL: 150 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: NOAEL: 310 mg/kg body weight

Method: OECD Test Guideline 422

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Reproductive toxicity - As-

sessment

: No known effect.

STOT - single exposure

Not classified due to lack of data.

Product:

Remarks : Based on available data, the classification criteria are not met.

Components:

tert-pentyl peroxypivalate:

Remarks : Based on available data, the classification criteria are not met.

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : Based on available data, the classification criteria are not met.

Components:

tert-pentyl peroxypivalate:

Remarks : Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Species : Rat, male and female

NOAEL : 150 mg/kg Application Route : oral (gavage)

Method : OECD Test Guideline 422

Remarks : Based on data from similar materials

Components:

tert-pentyl peroxypivalate:

Species : Rat, male and female

NOAEL : 150 mg/kg Application Route : oral (gavage)

Method : OECD Test Guideline 422

Remarks : Based on data from similar materials

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

tert-pentyl peroxypivalate:

May be fatal if swallowed and enters airways.

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

May be fatal if swallowed and enters airways.

Further information

Product:

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Remarks : Solvents may degrease the skin.

Components:

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Remarks : May cause headache and dizziness.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 56.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0.47 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.1 mg/l

Toxicity to microorganisms : EC50 (Bacteria): 296 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Components:

tert-pentyl peroxypivalate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 56.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): 0.47 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

: 1

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.1 mg/l

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23

aquatic invertebrates (Chron-

ic toxicity)

M-Factor (Chronic aquatic

toxicity)

: 1

Toxicity to microorganisms : EC50 (Bacteria): 296 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): > 0.04 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

IC50 (algae): > 0.04 mg/l Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability

Product:

Biodegradability : Result: Inherently biodegradable.

Method: OECD Test Guideline 301D

Components:

tert-pentyl peroxypivalate:

Biodegradability : Result: Inherently biodegradable.

Method: OECD Test Guideline 301D

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Biodegradability : Result: Not readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Bioconcentration factor (BCF): 1.84 - 2.10

Remarks: Calculation

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Components:

tert-pentyl peroxypivalate:

Bioaccumulation : Bioconcentration factor (BCF): 1.84 - 2.10

Remarks: Calculation

Partition coefficient: n-

octanol/water

log Pow: 3.3 (30 °C)

Hydrocarbons, C4, 1,3-butadiene-free, polymerised., triisobutylene fraction, hydrogenated:

Partition coefficient: n- :

octanol/water

log Pow: 5.94 - 6.16 (20 °C) Remarks: The value is calculated

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Dispose of in accordance with local regulations.

Clean container with water.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3113

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

CONTROLLED

(tert-AMYL PEROXYPIVALATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Environmentally hazardous : no

IATA-DGR

Not permitted for transport

IMDG-Code

UN number : UN 3113

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE

CONTROLLED

(tert-AMYL PEROXYPIVALATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-F, S-R Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 3113

Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE

CONTROLLED

(tert-AMYL PEROXYPIVALATE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Additional advice

Temperature controlled transport.:

Control temperature : 10 °C

Emergency temperature : 15 °C

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23

15. REGULATORY INFORMATION

National regulatory information

Gefahrgruppe nach TRGS 741: Ib (German regulatory requirements)

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W5.4 Flammable liquids 5,000 t

W7.2 Organic peroxides 50 t

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

DSL (CA) : This product contains the following components listed on the

Canadian NDSL. All other components are on the Canadian

DSL.

tert-pentyl peroxypivalate

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Revision Date : 2024/07/15

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

The hazards on the label also apply to residues in the con-

tainer.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

Version Revision Date: SDS Number: Date of last issue: 2024/06/20 5.2 2024/07/15 600000000044 Date of first issue: 2017/01/23

Date format : yyyy/mm/dd

Full text of other abbreviations

AllC - Australian Inventory of Industrial Chemicals: ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN

according to GB/T 16483 and GB/T 17519



TAPPI-75-AL

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/06/20

 5.2
 2024/07/15
 600000000044
 Date of first issue: 2017/01/23