

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	600000000045	Date of first issue: 2017/05/02

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TBHP-70-AQ

Other means of identification : None

Recommended use of the chemical and restrictions on use

Recommended use : polymerisation initiators
Oxidizing agents

Manufacturer or supplier's details

Company : United Initiators GmbH

Address : Dr.-Gustav-Adolph-Str. 3
82049 Pullach

Telephone : +49 / 89 / 74422 – 0

Emergency telephone number : +49 / 89 / 74422 – 0 (24 h)

E-mail address : contact@united-in.com

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Organic peroxides : Type F

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 2

Acute toxicity (Dermal) : Category 3

Skin corrosion/irritation : Category 1C

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 2

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H330 Fatal if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
P233 Keep container tightly closed.
P234 Keep only in original container.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 Protect from sunlight.
P411 + P235 Store at temperatures not exceeding 35 °C/ 95 °F. Keep cool.
P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Substance name : tert-butyl hydroperoxide

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

CAS-No. : 75-91-2

Synonyms : None

Components

Chemical Name	CAS-No.	Concentration (% w/w)
tert-butyl hydroperoxide	75-91-2	> 68 -<= 72

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus.
Call a physician immediately.

First aid measures for different exposure routes

If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Call a physician immediately.
If breathed in, move person into fresh air.
Contact a poison control center.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
Call a physician immediately.
Contact a poison control center.
If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Call a physician immediately.

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	60000000045	Date of first issue: 2017/05/02

- Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Toxic in contact with skin.
May cause an allergic skin reaction.
Causes serious eye damage.
Fatal if inhaled.
May cause respiratory irritation.
Suspected of causing genetic defects.
Suspected of causing cancer.
Causes severe burns.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Treat symptomatically and supportively.
-

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray jet
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
The product burns violently.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	600000000045	Date of first issue: 2017/05/02

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

7. HANDLING AND STORAGE

Handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from heat and sources of ignition.
Use only explosion-proof equipment.
Keep away from combustible material.
- Advice on safe handling : Do not swallow.

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Protect from contamination.

Storage

- Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.
- Materials to avoid : Keep away from strong acids, bases, heavy metal salts and other reducing substances.
- Recommended storage temperature : 2 - 35 °C
- Further information on storage stability : No decomposition if stored normally.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tert-butyl hydroperoxide	75-91-2	TWA	0.1 ppm	ACGIH

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	600000000045	Date of first issue: 2017/05/02

Biological occupational exposure limits

Contains no substances with biological exposure indices.

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber

Break through time : 480 min

Glove thickness : 0.5 mm

Material : Nitrile rubber

Break through time : 480 min

Glove thickness : 0.4 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Keep away from food and drink.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Colour : colourless, clear

Odour : characteristic

Odour Threshold : not determined

pH : ca. 4.3

Melting point/range : < 0 °C

Boiling point/boiling range : 96 °C
(1,013 hPa)
Decomposition: yes

Flash point : 38 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable
Remarks: Organic peroxide

Upper explosion limit / Upper flammability limit : ca. 99.99 %(V)

Lower explosion limit / Lower flammability limit : ca. 5.7 %(V)

Vapour pressure : 50.78 hPa (25 °C)

Relative vapour density : ca. 3.1 (15 - 20 °C)
(Air = 1.0)

Density : ca. 0.93 g/cm³ (20 °C)

Solubility(ies)
Water solubility : > 691 g/l soluble (20 °C)

Partition coefficient: n-octanol/water : log Pow: 0.85 (20 °C)

Self-Accelerating decomposition temperature (SADT) : 80 °C
Method: UN-Test H.4
SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Viscosity

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Viscosity, kinematic : 2.45 mm²/s (40 °C)
4.42 mm²/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.
Organic peroxide

Surface tension : 69.9 mN/m, 20 °C

Refractive index : ca. 1.387 (20 °C)

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.
Contact with incompatible substances can cause decomposition at or below SADT.
Heat, flames and sparks.
Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

11. TOXICOLOGICAL INFORMATION

Symptoms of Overexposure : None known.

Acute toxicity

Harmful if swallowed.
Toxic in contact with skin.
Fatal if inhaled.

Product:

Acute oral toxicity : LD50 (Rat): 805 mg/kg
Method: Acute toxicity estimate
Assessment: The component/mixture is moderately toxic after single ingestion.

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Acute inhalation toxicity : LC50 (Rat): 1.19 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Acute toxicity estimate
Assessment: The component/mixture is highly toxic after short term inhalation.
Remarks: May cause respiratory irritation.

Acute dermal toxicity : LD50 (Rabbit): 633 mg/kg
Method: Acute toxicity estimate
Assessment: The component/mixture is toxic after single contact with skin.
Remarks: Dermal absorption possible

Skin corrosion/irritation

Causes severe burns.

Product:

Species : Rabbit
Method : Draize Test
Result : Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days.

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Causes sensitisation.

: Inhalation

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Remarks : No data available

Remarks : Causes sensitisation.

Chronic toxicity

Germ cell mutagenicity

Suspected of causing genetic defects.

Product:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: Directive 67/548/EEC, Annex, B.13/14
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: Directive 67/548/EEC, Annex, B.17
Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration
Species: Mouse (male and female)
Application Route: Intravenous
Method: Directive 67/548/EEC, Annex V, B.12.
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse (males)
Application Route: Intraperitoneal
Method: Directive 67/548/EEC, Annex, B.22
Result: positive

Test Type: In vivo mammalian alkaline comet assay
Species: Rat (male)
Application Route: inhalation (vapour)
Method: OECD Test Guideline 489
Result: negative

Germ cell mutagenicity - Assessment : Suspected of causing genetic defects., The GHS classification specified by the authority

Carcinogenicity

Suspected of causing cancer.

Product:

Species : Rat, male and female
Application Route : inhalation (vapour)
NOEC : 15 mg/l
Method : OECD Test Guideline 451

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Symptoms : carcinogenic effects, Systemic toxicity
GLP : yes

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat, male and female
Application Route: Oral
General Toxicity F1: NOAEL: 21 mg/kg body weight
Method: OECD Test Guideline 422
GLP: yes

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 35 mg/kg body weight
Developmental Toxicity: NOAEL: \geq 35 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

STOT - single exposure

May cause respiratory irritation.

Product:

Exposure routes : Inhalation
Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Remarks : Not classified due to data which are conclusive although insufficient for classification.

Repeated dose toxicity

Product:

Species : Rat, male and female
NOAEL : 21 mg/kg bw/day
Application Route : Oral
Method : OECD Test Guideline 422
GLP : yes

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Species : Rat, male and female
NOAEC : 22.2 mg/m³
Application Route : inhalation (vapour)
Method : OECD Test Guideline 412
GLP : yes

Aspiration toxicity

Not classified based on available information.

Product:

Not classified due to data which are conclusive although insufficient for classification.

Further information

Product:

Remarks : This information is not available.

Remarks : Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 42.3 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 20 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 24.3 mg/l
Test Type: Respiration inhibition of activated sludge

Toxicity to soil dwelling organisms : LC50: 166 mg/kg
Exposure time: 14 d
End point: Mortality/concentration

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life., Based on test data

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects., Based on test data

Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3109
Proper shipping name : ORGANIC PEROXIDE TYPE F, LIQUID

SAFETY DATA SHEET

TBHP-70-AQ



Version 3.1 Revision Date: 2022/01/10 SDS Number: 600000000045 Date of last issue: 2021/10/01
Date of first issue: 2017/05/02

(tert-BUTYL HYDROPEROXIDE)
Class : 5.2
Subsidiary risk : 8
Packing group : Not assigned by regulation
Labels : 5.2 (8)

IATA-DGR

UN/ID No. : UN 3109
Proper shipping name : Organic peroxide type F, liquid
(tert-Butyl hydroperoxide)
Class : 5.2
Subsidiary risk : 8
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat, Corrosive
Packing instruction (cargo aircraft) : 570
Packing instruction (passenger aircraft) : 570

IMDG-Code

UN number : UN 3109
Proper shipping name : ORGANIC PEROXIDE TYPE F, LIQUID
(tert-BUTYL HYDROPEROXIDE)
Class : 5.2
Subsidiary risk : 8
Packing group : Not assigned by regulation
Labels : 5.2 (8)
EmS Code : F-J, S-R
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Gefahrgruppe nach DGUV 13 Vorschrift 13 (bisher BGV B4): II (German regulatory requirements)

Regulations on Occupational Safety and Health Facilities
Standards for the Storage, Cleanup, Handling and Disposal of Industrial Waste
Regulations on Labelling and Hazard Communication of Hazardous Chemicals
Rules on Road Traffic Safety
Establishment Standards and Safety Control Regulations for Manufacturing, Storing, Processing
Public Hazardous Substances and Flammable Pressurized Gases Places: Quantity subject to control

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	600000000045	Date of first issue: 2017/05/02

The components of this product are reported in the following inventories:

TCSI (TW)	:	On the inventory, or in compliance with the inventory
TSCA (US)	:	All substances listed as active on the TSCA inventory
AIC (AU)	:	On the inventory, or in compliance with the inventory
DSL (CA)	:	All components of this product are on the Canadian DSL
ENCS (JP)	:	On the inventory, or in compliance with the inventory
ISHL (JP)	:	On the inventory, or in compliance with the inventory
KECI (KR)	:	On the inventory, or in compliance with the inventory
PICCS (PH)	:	On the inventory, or in compliance with the inventory
IECSC (CN)	:	On the inventory, or in compliance with the inventory
TECI (TH)	:	On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Further information

Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
Responsible Department	:	
Prepared by	:	
Revision Date	:	2022/01/10
Other information	:	This safety datasheet only contains information relating to safety and does not replace any product information or product specification. These safety instructions also apply to empty packaging which may still contain product residues.
Date format	:	yyyy/mm/dd

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH / TWA	:	8-hour, time-weighted average

SAFETY DATA SHEET

TBHP-70-AQ



Version	Revision Date:	SDS Number:	Date of last issue: 2021/10/01
3.1	2022/01/10	600000000045	Date of first issue: 2017/05/02

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TW / EN