


Technical Data Sheet (TDS)

TBHP-70-AQ
Polymerisations (PO)

TBHP-70-AQ

tert. Butylhydroperoxide
CAS#75-91-2
70%, aqueous solution

Structural Formula



Description

Colourless, mobile liquid consisting of ca. 70 % tert. Butylhydroperoxide, desensitised with water. This alkyl-hydroperoxide is used as an initiator for the polymerisation of monomers, e.g. ethylene, vinyl acetate or (meth-) acrylates. Due to its oxidation potential TBHP-70-AQ is used as oxidizing agent in numerous chemical syntheses.

Technical Data

Appearance	colourless liquid
Desensitising agent	water
Assay	ca. 70 % w/w
Active oxygen (AO)	ca. 12.5 % w/w
Density at 20 °C	ca. 0.93 g/cm ³
Viscosity at 20 °C	ca. 4.1 mPa.s
Refractive index at 20 °C	ca. 1.387
Aqueous phase at 25 °C	max. 0.7 % v/v
Critical temperature (SADT)	ca. 80 °C
Cold storage stability	freezing point below ca. 0 °C
Recommended storage temperature	2 °C to 35 °C
Storage stability as from date of delivery	12 months

Standard Packaging

25 kg in HDPE canister
190 kg drums (for supply ex Germany)

Half-life Data

10 h / 1 h / 1 min (benzene, 0.1 mol/L) 170 °C / 195 °C / 260 °C

Technical Data Sheet (TDS)

TBHP-70-AQ
Polymerisations (PO)



Application

EMULSION POLYMERISATION:

Initiator for the emulsion polymerisation of vinyl acetate, (meth-) acrylates and acrylic resin paint dispersions in combination with suitable reducing agents (Fe-salts, sulphites, dithionites, RONGALITE, ascorbic acid or sugar).

Temperature range: 50 - 80 °C

Dosage level: 0.1 - 0.5 % as supplied

Particularly suitable for reduction of residual monomer.

COPOLYMERISATION:

Initiator for the copolymerisation of styrene / butadiene or acrylonitrile / butadiene / styrene in emulsion.

In combination with redox systems polymerisation temperatures are possible between 5 and 25 °C.

Dosage level: 0.1 - 0.3 % as supplied

CHEMICAL SYNTHESIS:

Selective oxidizing agent for hydrocarbons, olefins, alcohols, etc.

Decomposition Products

Possible detectable decomposition products: tert. Butyl alcohol, acetone, methane.

Storage

Avoid any source of heat and light and protect the product from impurities. Keep within safe temperature limits.

Disclaimer:

The information contained herein and all further technical advice that may be provided by United Initiators reflects our current knowledge and experience based on our internal research and development as to our products and applications. United Initiators does not make any warranties about the information provided as to specific properties of products described, their suitability for a particular application and representing complete instructions for use. Additionally, United Initiators does not make any warranties in respect of product and shelf life properties. We are not legally responsible and liable for the use of any information provided, including with regard to existing third party intellectual property rights, especially patent rights. We reserve the right to make any changes according to technological progress or further developments.

Application and usage of our products based on our technical advice is out of our control, strictly at your own risk and is the sole responsibility of the user. The user is not released from the obligation to conduct careful inspection and testing of incoming products in order to verify their suitability for the intended application.

United Initiators
Europe
T: +49 89 74422 237
F: +49 89 74422 6237
cs-initiators.eu@united-in.com

United Initiators
Nafta
T: +1 800 231 2702
F: +1 440 323 0898
cs-initiators.nafta@united-in.com

United Initiators
China
T: +86 20 6131 1370
F: +86 139 2503 8952
cs-initiators.cn@united-in.com

www.united-initiators.com