

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TBPB-HA-M3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : polymerisation initiators

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH
Dr.-Gustav-Adolph-Str. 3
82049 Pullach

Telephone : +49 / 89 / 74422 – 0

E-mail address of person responsible for the SDS : contact@united-in.com

1.4 Emergency telephone number

0800 0 621 2139 (toll-free, access from Turkey only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848 and subsequent amendments

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Organic peroxides, Type C	H242: Heating may cause a fire.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

2.2 Label elements

Labelling T.R. SEA No 28848 and subsequent amendments

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H242 Heating may cause a fire. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P234 Keep only in original packaging. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish. P391 Collect spillage.

Hazardous components which must be listed on the label:

tert-Butyl perbenzoate (CAS-No. 614-45-9)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide
Liquid mixture

Components

Chemical name	CAS-No.	SEA Classification	Concentration
---------------	---------	--------------------	---------------

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

	EC-No. Index-No. KKDIK Registration No.		(% w/w)
tert-Butyl perbenzoate	614-45-9 210-382-2	Org. Perox. C; H242 Acute Tox. 4; H332 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 <hr/> M-Factor (Acute aquatic toxicity): 1	>= 75 - < 80
Acetylacetone	123-54-6 204-634-0 606-029-00-0	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311	>= 20 - < 25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Take off contaminated clothing and shoes immediately.
Call a physician immediately.
Never give anything by mouth to an unconscious person.
If unconscious, place in recovery position and seek medical advice.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Administer oxygen if breathing is difficult or cyanosis is observed.
If breathed in, move person into fresh air.
If not breathing, give artificial respiration.
Call a physician or poison control centre immediately.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

- If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
- In case of skin contact : If symptoms persist, call a physician.
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.
Rinse mouth thoroughly with water.
Keep respiratory tract clear.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : sensitising effects

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Risk of explosion if heated under confinement.
Possible emission of gaseous decomposition products may lead to a dangerous pressure build-up.
Avoid confinement.
Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
The product burns violently.
Flash back possible over considerable distance.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours may form explosive mixtures with air.
The product will float on water and can be reignited on surface water.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Never return spills in original containers for re-use.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Treat recovered material as described in the section "Disposal considerations".

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Open drum carefully as content may be under pressure.
Protect from contamination.
Do not swallow.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material. Do not spray on a naked flame or any incandescent material.
- Hygiene measures : Avoid contact with skin, eyes and clothing. Keep away from food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in cool place. Contamination may result in dangerous pressure increases - closed containers may rupture. Observe label precautions. Store in accordance with the particular national regulations. Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Advice on common storage : Keep away from combustible materials. Keep away from strong acids, bases, heavy metal salts and other reducing substances.
- Recommended storage temperature : 10 - 30 °C
- Further information on storage stability : Stable under recommended storage conditions.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) :

Substance name	End Use	Exposure routes	Potential health effects	Value
tert-Butyl perbenzoate	Workers	Inhalation	Long-term systemic effects	24,7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	17,5 mg/kg bw/day
Acetylacetone	Workers	Inhalation		84 mg/m ³
	Workers	Skin contact		12 mg/kg bw/day

Predicted No Effect Concentration (PNEC) :

Substance name	Environmental Compartment	Value
tert-Butyl perbenzoate	Fresh water	0,01 mg/l
	Marine water	1,01 µg/l
	Sewage treatment plant	0,6 mg/l
	Fresh water sediment	0,28 mg/kg dry weight (d.w.)
	Marine sediment	0,028 mg/kg dry weight (d.w.)
	Soil	0,049 mg/kg dry weight (d.w.)
Acetylacetone	Fresh water	0,2 mg/l
	Marine water	0,02 mg/l
	Sewage treatment plant	1,32 mg/l
	Fresh water sediment	1,909 mg/kg dry weight (d.w.)
	Marine sediment	0,191 mg/kg dry weight (d.w.)
	Soil	0,193 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Tightly fitting safety goggles

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.

Hand protection

Material : Nitrile rubber
Break through time : <= 10 min
Glove thickness : 0,40 mm

Material : butyl-rubber
Break through time : <= 240 min
Glove thickness : 0,70 mm

Remarks : The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.
Wear as appropriate:
Flame retardant antistatic protective clothing.

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Colour	:	light yellow
Odour	:	ester-like
Odour Threshold	:	not determined
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	< 0 °C
Boiling point/boiling range	:	Decomposition: Decomposes below the boiling point.
Flash point	:	48 °C Method: ISO 3679, closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	11,4 %(V) (for a component of this mixture)
Lower explosion limit / Lower flammability limit	:	2,4 %(V) (for a component of this mixture)
Vapour pressure	:	7,9 hPa (20 °C) (for a component of this mixture)
Relative vapour density	:	not determined
Relative density	:	not determined
Density	:	1,03 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	not determined
Viscosity Viscosity, dynamic	:	4 mPa.s (20 °C)
Viscosity, kinematic	:	not determined
Explosive properties	:	Not explosive In use, may form flammable/explosive vapour-air mixture.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Oxidizing properties : The substance or mixture is not classified as oxidizing.
Organic peroxide

9.2 Other information

Self-Accelerating decomposition temperature (SADT) : 60 °C
Method: UN-Test H.4
SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Flammability (liquids) : Flammable liquid and vapour., Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

Self-ignition : The substance or mixture is not classified as pyrophoric.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
Heating may cause a fire or explosion.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from contamination.
Contact with incompatible substances can cause decomposition at or below SADT.
Heat, flames and sparks.
Avoid confinement.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

tert-Butyl perbenzoate:

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 423
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat, male and female): > 1,01 - 4,9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
GLP: yes
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Acetylacetone:

Acute oral toxicity : LD50 (Rat, female): 570 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 5,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Acute dermal toxicity : LD50 (Rabbit, female): 790 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

tert-Butyl perbenzoate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Acetylacetone:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

tert-Butyl perbenzoate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Acetylacetone:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

Product:

Remarks : Causes sensitisation.

Components:

tert-Butyl perbenzoate:

Species : Mouse
Method : OECD Test Guideline 429
Result : May cause sensitisation by skin contact.

Acetylacetone:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Acetylacetone:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Result: negative
GLP: yes

Test Type: Ames test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: positive
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive
GLP: yes

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Genotoxicity in vivo

: Test Type: Micronucleus test
Method: OECD Test Guideline 474
Result: positive

Test Type: Chromosomal aberration
Method: OECD Test Guideline 483
Result: negative

Test Type: Chromosomal aberration
Method: OECD Test Guideline 475
Result: negative

Test Type: gene mutation test
Method: OECD Test Guideline 478
Result: Equivocal

Germ cell mutagenicity- Assessment

: Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Remarks : No data available

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Reproductive toxicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Dose: 0 100, 300, 750, 1000 milligram per kilogram
General Toxicity - Parent: NOAEL: 300 mg/kg bw/day
General Toxicity F1: NOAEL: 300 mg/kg bw/day
Method: OECD Test Guideline 421
GLP: yes

Acetylacetone:

Effects on foetal development : Species: Rat
Application Route: Inhalation
Dose: 0,20, 200, 400 parts per million
General Toxicity Maternal: NOAEC: 200 ppm
Method: OECD Test Guideline 414
GLP: yes

STOT - single exposure

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Remarks : Not classified due to data which are conclusive although insufficient for classification.

STOT - repeated exposure

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

tert-Butyl perbenzoate:

Species : Rat, male and female
NOAEL : 30 mg/kg
Application Route : Oral
Exposure time : 90 d

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Acetylacetone:

Species : Rat, male and female
NOAEC : 0,42 mg/l
Application Route : Inhalation
Test atmosphere : vapour
Exposure time : 90 d
Method : OECD Test Guideline 413
GLP : yes
Target Organs : Blood, Central nervous system

Aspiration toxicity

Not classified due to lack of data.

Components:

tert-Butyl perbenzoate:

No aspiration toxicity classification

Acetylacetone:

Not classified due to lack of data.

Further information

Product:

Remarks : Solvents may degrease the skin.

Components:

Acetylacetone:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

tert-Butyl perbenzoate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1,6 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

NOEC (Danio rerio (zebra fish)): 0,72 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 11 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202
GLP: yes

NOEC (Daphnia magna (Water flea)): 7,7 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

EC50 (Pseudokirchneriella subcapitata (green algae)): 0,8 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,72 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (activated sludge): 43 mg/l
Exposure time: 0,5 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 0,49 mg/l
End point: reproduction rate
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

Method: OECD Test Guideline 211
GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Acetylacetone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 104 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 25,9 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 83,22 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): 107,6 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
GLP: yes

EC10 (activated sludge): 13,2 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 34 d
Species: Pimephales promelas (fathead minnow)
Test Type: flow-through test
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 18 mg/l
End point: reproduction rate
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Components:

tert-Butyl perbenzoate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Acetylacetone:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: > 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

Components:

tert-Butyl perbenzoate:

Partition coefficient: n-octanol/water : log Pow: 3 (25 °C)

Acetylacetone:

Bioaccumulation : Bioconcentration factor (BCF): 3,16
Remarks: Calculation

Partition coefficient: n-octanol/water : log Pow: 0,68 (40 °C)
Method: Tested according to Annex V of Directive 67/548/EEC.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of wastes in an approved waste disposal facility.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations.
Clean container with water.
Dispose of contents/ container to an approved waste disposal plant.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : UN 3103
RID : UN 3103
IMDG : UN 3103
IATA : UN 3103

14.2 UN proper shipping name

ADR : ORGANIC PEROXIDE TYPE C, LIQUID
(tert-BUTYL PEROXYBENZOATE)
RID : ORGANIC PEROXIDE TYPE C, LIQUID
(tert-BUTYL PEROXYBENZOATE)
IMDG : ORGANIC PEROXIDE TYPE C, LIQUID
(tert-BUTYL PEROXYBENZOATE)
IATA : Organic peroxide type C, liquid
(tert-Butyl peroxybenzoate)

14.3 Transport hazard class(es)

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

	Class	Subsidiary risks
ADR	: 5.2	
RID	: 5.2	
IMDG	: 5.2	
IATA	: 5.2	HEAT

14.4 Packing group

ADR

Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : P1
Hazard Identification Number : 539
Labels : 5.2

IMDG

Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passenger aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17) : Conditions of restriction for the following entries should be considered: Number on list 3

Regulation on Persistent Organic Pollutants (Number 30595 and subsequent amendments published) : Not applicable

Regulation on prevention of major industrial accidents. Reg number 30702 P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 ENVIRONMENTAL HAZARDS

Other regulations:

Gefahrgruppe nach TRGS 741: Ib, S+ (German regulatory requirements)

Produkt unterliegt dem Sprengstoffgesetz (SprengG; Stoffgruppe C). (German regulatory requirement)

T.R. Regulation on Classification, Labeling and Packaging of Substances and Mixtures, dated December 11, 2013 and numbered 28848 from the Ministry of Environment and Urbanization and the subsequent amendments published.

Regulation on Import and Export of Certain Hazardous Chemicals, No. 32087, 2023 : Not applicable

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AiIC (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

ENCS (JP) : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

ISHL (JP)	:	On the inventory, or in compliance with the inventory
KECI (KR)	:	On the inventory, or in compliance with the inventory
PICCS (PH)	:	On the inventory, or in compliance with the inventory
IECSC (CN)	:	On the inventory, or in compliance with the inventory
TECI (TH)	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H242	:	Heating may cause a fire.
H302	:	Harmful if swallowed.
H311	:	Toxic in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H400	:	Very toxic to aquatic life.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Flam. Liq.	:	Flammable liquids
Org. Perox.	:	Organic peroxides
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version 3.0 Revision Date: 22.01.2025 SDS Number: 600000000202 Date of last issue: 09.03.2023
Date of first issue: 13.08.2018

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
These safety instructions also apply to empty packaging which may still contain product residues.
The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 3	H226
Org. Perox. C	H242
Acute Tox. 4	H332
Skin Irrit. 2	H315
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



TBPB-HA-M3

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
3.0	22.01.2025	600000000202	Date of first issue: 13.08.2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN